



350 AND 550

BALANCED FLUE GAS FIREPLACES



350 & 550

Compact, creative versatility. Fitting where other fireplaces don't. A small footprint with flexible venting options offers an array of unique installation possibilities. Enjoy strong heat output, bold flames, a textured brick interior and detailed log set—all in more places than you'd think.

FEATURES & OPTIONS

- RC300 remote control, front and fan included standard
- Standard ceramic glass
- Optional stainless steel front available
- Optional stone conversion kit (available for 550 only)



RC300
REMOTE CONTROL



STANDARD
FRONT



OPTIONAL STAINLESS
STEEL FRONT



550 STONE
CONVERSION KIT



INTELLIFIRE™ IGNITION SYSTEM



The IntelliFire™ Ignition System (IPI) is an advanced intermittent pilot ignition system. IPI constantly monitors ignition, ensures safe functioning and conserves up to \$10/month in energy costs.

BALANCED FLUE TECHNOLOGY




Balanced Flue fireplaces remove 100% of combustion exhaust and odors outside of the home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality.


350 & 550 SPECIFICATIONS

| MODEL | FRONT WIDTH | | BACK WIDTH | | HEIGHT | | DEPTH | | GLASS SIZE | mJh INPUT | EFFICIENCY | FUEL TYPE/ IGNITION SYSTEM |
|-------|-------------|---------|------------|---------|--------|---------|-------|---------|------------|------------------------|------------|-------------------------------|
| | UNIT | FRAMING | UNIT | FRAMING | UNIT | FRAMING | UNIT | FRAMING | | | | |
| 350 | 838 | 864 | 578 | 864 | 827 | 832 | 414 | 413 | 613 x 384 | N - 21, P - 17, B - 20 | 77% | Gas, IntelliFire Plus |
| 550 | 913 | 940 | 653 | 940 | 873 | 882 | 415 | 413 | 691 x 459 | N - 28, P - 26, B - 26 | 78% | Gas, IntelliFire Plus |


LEFT SIDE VIEW




FRONT VIEW



RIGHT SIDE VIEW



TOP VIEW



| Model | A | B | C | D | E | F | G | H | I | J | K | L | M | N | O | P | Q | R | S | T | U | V | W |
|-------|-----|-----|-----|-----|-----|----|-----|-----|-----|------|-----|-----|-----|----|-----|-----|-----|-----|----|-----|----|-----|-----|
| 350 | 838 | 714 | 613 | 384 | 741 | 90 | 175 | 541 | 827 | 984 | 203 | 223 | 414 | 13 | 578 | 289 | 403 | 168 | 55 | 153 | 25 | 712 | 178 |
| 550 | 913 | 791 | 691 | 459 | 790 | 90 | 174 | 593 | 873 | 1010 | 203 | 223 | 415 | 13 | 653 | 326 | 403 | 168 | 55 | 152 | 25 | 764 | 178 |

Dimensions above are in millimeters. Reference dimensions only. We recommend measuring individual units at installation. NOTE: Combustible material should not be installed over the face. Make sure you do NOT cover the decorative door opening.

Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Pictures in this brochure are not a true representation of the fireplace and/or flames.

For complete information on this model, please contact us at:

HEAT & GLO

No one builds a better fire

www.heatnglo.com