

QUADRA-FIRE® WALL SWITCHES & REMOTE CONTROLS

	Controls	Wall or Remote	IPI or SP†	On/Off	Battery Strength Indicator	Automatic Battery Backup	Fan Speed	Flame Control	Flame Modulation	Pilot Activation	AUX Function	Temp Readout	Thermostat Mode	Timer Mode	7-Day Programmable
IntelliFire Plus Wireless Controls	RC300 RC300-QDF	Remote w/ Docking Station	IPI	●	●	●	●	5 Step	●	●	● (Three)‡	●	●	●	
	RC200 RC200-QDF	Remote w/ Docking Station	IPI	●	●	●	●	5 Step		●					
	RC100 RC100-QDF	Wall	IPI	●	●	●									
Wireless Controls	TotalRemote 841-0980	Remote	Both	●			●	High/Low				●	●	●	
	SmartRemote-Battery 841-0970	Remote	Both	●								●	●	●	
	SmartRemote-Hardwired 841-0960	Remote	Both	●								●	●	●	
Wired Wall Controls	TotalSwitch QWSK-MLT	Wall	Both	●			●	High/Low		●	● (One)	●	●		
	IntelliSwitch200 WSK200-QF	Wall	IPI	●	●	●	●			●					
	Programmable Thermostat 811-0520	Wall	Both									●	●		●
	Thermostat 812-3760	Wall	Both									●	●		



QUADRA-FIRE®
CONTROLS FOR GAS HEARTH

Feature Glossary

On/Off: Turns the flames on and off.

Battery Strength Indicator: IntelliSwitch200 – red led blinks to alert homeowner that new batteries are needed; solid-on indicator signifies that the hearth system is operating on battery power. RC100 & 200 – red led blinks when button is pressed. Lack of red led light signifies that the batteries need changed. RC300 - Displays a battery strength icon.

Automatic Battery Backup: Senses power failure and automatically switches the unit to battery operation, keeping you and your family warm.

Fan Speed: Adjusts the speed of the fan, pushing heat into the room.

Flame High/Low: Adjusts the height of the flames, affecting ambiance and heat output.

Pilot Activation: Changes the pilot from ‘energy saving as-needed’ (activated only when the fireplace is turned on) to ‘constant-on’ (seasonal pilot remains on to improve performance during the coldest times of the year).

AUX Function: Controls assigned auxiliary functions, such as accent lighting or electric embers.

Temp Readout: Communicates room temperature.

Thermostat Mode: Maintains the specified room temperature by adjusting the hearth system, much like a furnace thermostat.

Timer Mode: Shuts flames off automatically at a pre-set time.

7-Day Programmable: Control room temperature settings on a weekly cycle.



The IntelliFire Plus Ignition System is an “intelligent” control system providing energy conservation and the comfort of a roaring fire

...all at your fingertips! IntelliFire Plus features intermittent pilot ignition (IPI) allowing you to conserve fuel and money when the fireplace is not in use. Optional constant pilot mode—allows you to leave the pilot flame on in cold climates. In addition, the system offers seamless transition from AC to battery backup in a power outage, as well as built-in safety features and memory settings. Lastly, our new family of IntelliFire Plus wireless controls provides stylish and ergonomic controls with the features and benefits homeowners desire.

† IPI = Intermittent Pilot Ignition
SP = Standing Pilot

‡ Fan speed is one of three auxilliary functions



1445 North Highway, Colville, WA 99114
www.quadrafire.com • 800-926-4356
QDF-1020U-0709

HEAT AT YOUR FINGERTIPS THE WARMTH OF HOME AT YOUR CONTROL.



Enjoying your gas fireplace, stove or insert is only a click away.

Quadra-Fire controls are uniquely designed to conveniently start your fire with a simple, easy click. Select the control that best meets your needs and your hearth features.

A sleek wall switch stays in one convenient location while a remote control goes where you go. Wireless controls bring added convenience of handy remote access, as well as a wall docking station.

All controls are UL listed and approved for use with Quadra-Fire products.



INTELLIFIRE PLUS™ WIRELESS CONTROLS

IntelliFire Plus RC300 is specifically designed for use with our new IntelliFire Plus ignition system. It is easy-to-use, stylish and ergonomic in design. Features an LCD screen, intuitive menus and large buttons. The wireless control allows flexibility for wall placement, or use as a remote only.

Models: RC300-QDF

Features: On/Off, Auto Battery Backup, Pilot Activation, 5 Step Flame Height, Fan Speed (auxiliary 1), two additional Auxiliary Functions, Room Temperature Readout, Thermostat Mode, Timer Mode, Child Lock, Wall Docking Station



IntelliFire Plus RC200 is specifically designed for use with our new IntelliFire Plus ignition system. It is easy-to-use, stylish and ergonomic in design. As a wireless control, it has the flexibility for wall placement, or use as a remote only.

Models: RC200-QDF

Features: On/Off, Auto Battery Backup, Pilot Activation, 5 Step Flame Height, Fan Speed, Child Lock, Wall Docking Station



IntelliFire Plus RC100 Designed specially for fireplaces with IntelliFire Plus, our state-of-the-art intermittent pilot ignition system.

Models: RC100-QDF

Features: On/Off



REMOTE CONTROLS

TotalRemote This remote control effortlessly manages heat output and comfort level. For use with **Quadra-Fire**.

Models: RCT-MLT, 841-0980

Features: Hardwired Receiver, Timer Mode, Thermostat Mode, Room Temperature Readout, Flame High/Low, Fan Speed, On/Off



SmartRemote For homeowners who want an added level of function and convenience in a remote control for fireplaces, stoves, inserts and gas logs. For use with **Quadra-Fire**.

Models: 841-970, 841-0960, SMART-BATT, SMART-STAT

Features: Battery-Powered or Hardwired Receiver, Timer Mode, Thermostat Mode, Room Temperature Readout, On/Off



WALL CONTROLS

Programmable Thermostat Control your hearth system based on your weekly schedule. UL listed for use with **Quadra-Fire**.

Model: 811-0520

Features: 7-Day Programmable, Thermostat Mode, Room Temperature Readout, On/Off



TotalSwitch Command of both comfort and ambiance from one location. For use with **Quadra-Fire**.

Model: WSK-MLT

Features: Thermostat Mode, Room Temperature Readout, Auxiliary Function, Flame High/Low, Pilot Activation, Fan Speed, On/Off



Thermostat Simple temperature-based control of your hearth system. UL listed for use with **Quadra-Fire**.

Model: 812-3760

Features: Room Temperature Readout, On/Off

