

# Non-Confidential Business Information (Non-CBI)

## Certification Test Report

### Hearth & Home Technologies, Inc.

**Heater Type:** Pellet-Fired, Freestanding  
**Model:** Absolute43-C

**Prepared for:** Hearth & Home Technologies, Inc.  
352 Mountain House Road  
Halifax, PA 17032

**Prepared by:** OMNI-Test Laboratories, Inc.  
13327 NE Airport Way  
Portland, OR 97230  
(503) 643-3788

**Test Period:** February 20, 2018

**Report Date:** March, 2018  
**Report Revision Date:** May 24, 2023

**Report Number:** 0135PS039E

*All data and information contained in this report are confidential and proprietary to Hearth & Home Technologies, Inc.. Its significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations, or surveys made. The contents of this report cannot be copied or quoted, except in full, without specific, written authorization from Hearth & Home Technologies, Inc. and OMNI-Test Laboratories, Inc. No use of the OMNI-Test Laboratories, Inc. name, logo, or registered mark (O-TL) is permitted, except as expressly authorized by OMNI-Test Laboratories, Inc. in writing.*


Hearth & Home Technologies, Inc.  
Model: Absolute43-C  
Report: 0135PS039E

OMNI-Test Laboratories, Inc.


## AUTHORIZED SIGNATORIES

This report has been reviewed and approved by the following authorized signatories:

### Technician:

  
\_\_\_\_\_  
Riley Tieg, Technician  
OMNI-Test Laboratories, Inc

### Evaluator:

  
\_\_\_\_\_  
Ken Morgan, Technical Services Director  
OMNI-Test Laboratories, Inc

## TABLE OF CONTENTS

PREFACE .....	(3 pages)
<b>Section 1 –Appliance, Testing, &amp; Results .....</b>	<b>4</b>
1.1 Appliance Description .....	5
1.2 Procedures & Results Summary .....	7
1.3 Summary Tables .....	9
Table 1 – Pellet Stove Results Summary .....	9
Table 2 – Test Facility Conditions .....	9
Table 3 – Fuel Measurement Summary .....	9
Table 4 – Dilution Tunnel and Flue Gas Measurements .....	9
Table 5 – Heater Configuration .....	9
<b>Section 2 – Test Data.....</b>	<b>10</b>
2.1 Test Data by Run .....	12
2.2 Sample Analysis & Tares.....	34
<b>Section 3 –Laboratory Quality Assurance.....</b>	<b>44</b>
3.1 Quality Assurance/Quality Control.....	45
3.2 Calibration Data .....	46
3.3 Example Calculations .....	63
<b>Appendix A - Labeling &amp; Owner’s/Installation Manual</b>	
<b>Appendix B – Revision History</b>	

# **Section 1**

## **Appliance, Testing, & Results**

- 1.1 - Appliance Description
- 1.2 – Procedures and Results Summary
- 1.3 - Summary Tables

## 1.1 - Appliance Description

**Appliance Manufacturer:** Hearth & Home Technologies, Inc.

**Pellet Stove Model:** Absolute43-C

**Type:** Freestanding, air-circulating type, pellet-fired room heater.

The Absolute43-C's principle elements include a fuel hopper, grey cast iron firebox chamber, ductile iron burn pot, and electrical fuel feed, combustion air, and convection air supply systems. The frame of the unit is constructed of mild steel, as is the outer fascia and door.

Combustion products are routed out of the firebox chamber via a baffle-type heat exchanger through a 3 inch diameter flue outlet located on the rear of the unit.

Fuel is supplied from the hopper to the burn pot via a screw-type auger. Fuel supply rate is varied by cycling the auger motor as needed.

Ashes fall through the burn pot into a removable ash drawer located at the bottom of the unit. The drawer is accessed through the front firebox door, which also features a 10" x 12" glass panel.

The electrical systems are regulated by a user-operated touch screen located on the hopper door to achieve desired heat output. The unit can also be controlled by an external thermostat system.

More detailed information is shown in the manufacturer's design drawings, Appendix C of this report. This information is considered confidential business information (CBI) by the manufacturer and is not included in the non-CBI version of this report.

**Appliance Photographs**

**Absolute43-C**

**Test Date: 2/20/2018**



**Absolute43-C Front**



**Absolute43-C Back**



**Absolute43-C Left**



**Absolute43-C Right**

## 1.2 - Procedures and Results Summary

### INTRODUCTION

Hearth & Home Technologies, Inc. retained OMNI-Test Laboratories, Inc. (*OMNI*) to perform U.S. Environmental Protection Agency (EPA) certification testing on the Absolute43-C. The Absolute43-C is a freestanding or insert style pellet-burning residential heating appliance.

The testing was performed at *OMNI's* testing facility in Portland, Oregon. The altitude of the laboratory is 30 feet above sea level. The unit was received in good condition and logged in at the *OMNI's* testing facility on February 19, 2018. It was assigned and labeled with *OMNI* ID #2269. *OMNI* representative Aaron Kravitz conducted the certification testing and completed all testing by February 20, 2018.

This report is organized in accordance with the EPA-recommended outline and is summarized in the Table of Contents immediately preceding this section. The results in this report are limited to the item(s) submitted.

### SUMMARY OF RESULTS

The average particulate emission rate over the complete, integrated test run was measured to be 0.99 g/hr.

The average particulate emission factor for the complete, integrated test run was measured to be 0.91 g/dry kg of fuel.

The average thermal efficiency for the complete, integrated test run was measured to be 77.0%.

The particulate emission rate calculated from the one-hour filter was 1.44 g/hr.

The proportionality results and sample train agreement for the test run was acceptable. Quality check results for each test run are presented in Section 3 of this report.

No sampling anomalies occurred during this test series, raw data, certification documents, and results were found to be valid and appropriate for certification to ASTM E2779.

## TESTING PROCEDURE


The Absolute43-C was tested in accordance with the U.S. EPA 40 CFR Part 60, Subpart AAA – Standards of Performance for New Residential Wood Heaters using ASTM E2515 and ASTM E2779. The fuel used for certification testing was Lignetics brand densified wood pellet fuel; this fuel was graded as Premium by the Pellet Fuels Institute and was produced at registered mill # 03434. Particulate emissions were measured using dual sampling trains consisting of two sets of filters (front and back).

The unit was installed and adjusted in accordance with the manufacturer's instructions.

The results of the integrated test run indicate an average particulate emission rate of 0.99 g/hr. The Absolute43-C results are within the emission limit of 2.0 g/hr for affected appliances manufactured on or after May 15, 2020 or sold at retail after December 31, 2020.

The model Absolute43-C was tested for thermal efficiency and carbon monoxide (CO) emissions in accordance with CSA B415.1-10. The heater has a demonstrated an average thermal efficiency of 77.0%. The calculated CO emission rate was 0.10 g/min.

Upon completion of emissions certification testing, the sample unit was sealed and will be stored by the manufacturer in accordance with the requirements of the CFR.





### 1.3 - Summary Tables

**Table 1 – Pellet Stove Results Summary**

Run #	Date	Setting	Burn Rate (dry kg/h)	Time (min)	Heat Output (Btu/hr)	1 <sup>st</sup> Hour PM (g/hr)	Total PM (g/hr)	CO Emissions (g/min)	Overall CO (g/min)	Heating Efficiency (% HHV)	Overall Heating Efficiency (% HHV)
1	Feb 21, 2018	H	2.30	61	44,183	*1.44	*0.99	0.22	0.10	79.2%	77.0%
		M	1.00	120	19,132			0.08		76.5%	
		L	0.74	180	14,141	**1.44	**0.99	0.07		74.9%	
		OA	1.09	361	20,876			0.10		77.0%	

H= High burn rate, M= Medium burn rate, L= low burn rate, OA= overall burn rate.

\*Corrected refers to gravimetric analysis that takes negative filter weights as a negative value in cases where filter residue was transferred to (stuck to) O-ring gaskets to account for the mass transfer.

\*\*Uncorrected refers to gravimetric analysis where negative filter weights are taken as zero, thus reporting a higher value by over-reporting of transferred filter material. The uncorrected values were added to this report in response to a request by the US EPA.

**Table 2 – Test Facility Conditions**

	Initial	Middle	Final
Room Temperature (°F)	72	71	70
Barometric Pressure (in Hg)	30.25	30.26	30.26
Air Velocity (ft/min)	< 50	< 50	< 50
Induced Draft (in H <sub>2</sub> O)	0	0	0

**Table 3 – Fuel Measurement Summary**

Segment	Time (min)	Burn Rate (dry kg/hr)	Consumed Fuel Weight (lbs)	Fuel Moisture Content (dry basis - %)
Pretest	90	2.17	7.5	4.84
Maximum	61	2.30	5.4	4.84
Medium	120	1.00	4.6	4.84
Minimum	180	0.74	5.1	4.84
Integrated Total	361	1.09	15.1	4.84

**Table 4 – Dilution Tunnel and Flue Gas Measurements**

Segment	Average Flue Draft (in H <sub>2</sub> O)	Average Dilution Tunnel Gas Measurements		
		Velocity (ft/sec)	Flow Rate (dscf/min)	Temperature (°F)
Integrated Total	-0.042	13.56	152.0	89.5

**Table 5 – Heater Configuration**

	Pretest	Burn Rate Segment		
		Maximum	Medium	Minimum
Const. Burn Setting	7.0 (max)	7.0 (max)	4.0	1.0 (min)
Feed Limit	83%	83%	37%	25%


# **Section 2**

## **Test Data**

2.1 Test Data by Run

2.2 Sample Analysis & Tares

### Example of ASTM E2515-11 Dilution Tunnel



Prior to testing, sample point and travers point locations are verified to ensure placement is within specifications. Collection hood, tunnel diameter, and mixing section length are also verified to be within specifications.

## **2.1 - Test Data by Run**

### Run 1 Notes & Results

## Pellet Heater Conditioning Data - ASTM E2779

Manufacturer: HHT Halifax  
 Model: Absolute 43-C  
 Tracking No.: 2269  
 Project No.: 0135PS039E  
 Test Date: January, 2018  
 Operation Category: Medium

Elapsed Time (hours)	Scale Reading (lbs)	Stack (°F)
0	17.8	434
1	12.4	432
2	9.3	302
3	6.6	300
4	5.2	270
5	3.9	259
6	2.8	267
7	50.5	437
8	44.6	377
9	42.0	308
10	39.4	309
11	37.5	252
12	35.5	249
13	33.8	248
14	60.0	437
15	54.4	438
16	51.3	308
17	48.8	297
18	47.0	244
19	45.0	245
20	43.3	252
21	48.6	447
22	43.1	445
23	40.1	316
24	37.4	315
25	35.3	264
26	33.4	255
27	31.5	256
28	46.1	446
29	40.7	438
30	37.7	311
31	35.1	314
32	33.2	262
33	31.6	261
34	29.7	260
35	65.7	448
36	60.5	455
37	57.6	342
38	54.9	339
39	53.0	289
40	51.0	302
41	49.1	295
42	58.2	449
43	53.1	450
44	49.8	351
45	47.3	345
46	44.8	293
47	42.9	297
48	41.1	287
49	54.3	452
50	49.1	455

## **Sturm, Neil (HHT)**

---

**From:** Sturm, Neil (HHT)  
**Sent:** Friday, February 02, 2018 12:25 PM  
**To:** Bud Fongellaz (HHT) (FongellazB@hearthnhome.com)  
**Subject:** ABSOLUTE 43-C

OK here we go. We are going to try to use as many existing programmed parameters as possible to keep the software rewrite as little as possible.

Prior to any test the inside heat exchanger surfaces should be clean. It will not be necessary to clean the combustion fan blade except for any 6 hour test for average effy. and emissions.

**High burn;** Mod. # 999043 (dealers section)

**Combustion RPM High** - 2800 (dealers section)

**Combustion RPM Low** - 2000 (dealers section)

**Wisper Adjust** - 10% (dealers section)

**Screen Brightness** - Both @ 100% ( Main Menu )

**Home Screen Options** - Dashboard ( Main Menu )

this will allow you to see RPM and ESP temp. on Home Screen

**Set Feed Limit @75%** ( Main Menu )

**Burn Mode - Constant** ( Main Menu )

**Set Burn on scale to #7** (Home Screen)

**Distribution Blower - Auto** ( Main Menu )

Start unit and allow it to stabilize at (about 440 deg) then jump to 81% until stable 455-460 deg.

83% will be as high as you can probably go without exceeding **468 deg.( + 0 / - 1 )** At 470 deg the control will start to reduce the feed

So you will need to watch closely when you get in the 466-468 deg range ( it may be that the unit you have 83% may be too much or not enough to keep a steady 468 or so deg temp without spiking and reducing the feed rate during a test.

The object of this test is to burn a minimum of 5.1 lbs. per hr. at the best efficiency. (lignetic fuel) (83% in the unit we have gives us 5.1 #/hr) I'm not sure what the fuel you have will do in any of these scenarios.

Achieving best effy. during High Burn; The only thing that can be adjusted during this test is the combustion RPM.

If you increase the RPM by let's say 100 RPMs you may get a better effy. # but you will then exceed the 470 deg and reduce the #/hr.

If you decrease the RPM by 100 RPM ( we never tried this so I don't know) does the effy. go up or down? The nice thing about this RPM reduction is that the ESP temp goes down allowing a higher feed rate %, but I'm not sure whether that helps us or hurts us. You will need to test this out during testing.

The best effy. may be with a dirtier burn so when it comes to the 6 hour test you need to understand we are no going for the cleanest burn (such as we achieved when we were there of 0.70 gph ) as long as it is about 1.0gph. ( I have no idea where this is) The customer only knows Effy.#s therefore we are going for these to be the best we can achieve.

Once you have a stable feed %, RPM, and ESP temp., we would like 2 or3 repeated tests to be sure these settings give us the results we want.

Send a picture of the test result for the NPD files.

**Medium Burn;** Set Feed Limit @<sup>37%</sup>~~39%~~ ( Main Menu )  
Set Burn on scale to #4 (Home Screen)

This is the part of the 6 hour test burn that we need to get our highest effy. #s.

You can change the feed limit up or down, probably only down because we need to stay below 50% of high burn with our #/hr. The combustion RPMs

Will self-adjust up or down automatically with changes in ESP temp.

At the 39% setting we see ESP temp. of about 330 deg. And RPMs of about 2190, and our usage at 2.4 #/hr. So you will need to play with the feed

adjust a couple of % at the most to find the ideal effy. #s.

**Low Burn;** Set Feed Limit @25% ( Main Menu )  
Set Burn on scale to #1 (Home Screen)

### Pellet Heater Certification Run Sheets

Client: HHT Halifax Project Number: 0135 RBA A 5039E Run Number: 1  
 Model: Absolute 43-C Tracking Number: 2269 Date: 2/20/18  
 Test Crew: A. Kravitz  
 OMNI Equipment ID numbers: 335, 336

#### ASTM E2779 Run Notes

##### Air Control Settings

High Burn Rate Target: 100%

Settings: Const. Burn 7.0  
Feed Limit 83%

Medium Burn Rate Target: <50%

Settings: Const. Burn 4.0  
Feed Limit 37%

Low Burn Rate Target: Minimum

Settings: Const. Burn 1.0  
Feed Limit 25%

Additional Settings  
 Notes:  
 Comb. Fan Max: 2800  
 Min: 2000  
 Wisper Adj.: 10%

Pellet Moisture Content: TBD

Pellet Specifications: Lignetics Gold Mill # 03434


Pellet Analysis Notes: TBD

##### Preburn Notes

Time	Notes
<u>60:00</u>	<u>- None -</u>

##### Test Notes

Time	Notes
<u>60:00</u>	<u>Changed Filter A</u>
<u>61:00</u>	<u>Changed settings to Med</u>
<u>181:00</u>	<u>Changed settings to low</u>
<u>361:00</u>	<u>Test End</u>

Technician Signature: 

Date: 2/20/18



### Pellet Heater Certification Run Sheets

Client: Hill Haligan Project Number: 0135 P503AE Run Number: 1  
 Model: Absolute 45C Tracking Number: 2269 Date: 2/20/18  
 Test Crew: A. Kowalski  
 OMNI Equipment ID numbers: 132, 410, 494, 185, 285A 204, 559

#### ASTM E2515 Sampling Information

Test Location: E1 Test Start Time: 07:43

Span Gas Concentrations: CO<sub>2</sub>: 16.03 CO %: 5.000 CO ppm: 901

Test Run Validation Checks	Pre Test	Post Test
Zero Stack Gas Leakage	✓	✓
Zero Pitot Line Leakage	✓	✓
Zero Induced Draft	✓	
100% Smoke Capture	✓	

Test Run Validation Measurements	Pre Test		Post Test	
Scale Audit (lbs)	10.0		10.0	
CO <sub>2</sub> % (Zero/Span)	0.00	16.03	<del>0.00</del> 15.11	<del>15.91</del> 14.897
CO % (Zero/Span)	0.000	4.996	0.001	4.997
CO ppm (Zero/Span)	0	901	17	913
Sample A Leakage (cfm@"Hg)	0 @ -12		0 @ -13	
Sample B Leakage (cfm@"Hg)	0 @ -9		0 @ -12	
Room Air Velocity (ft/min)	< 50		< 50	
Barometric Pressure (" Hg)	30.25		30.26	
Relative Humidity (%)	21.7		19.1	

#### Last Cleaning Dates

Flue Pipe	2/19/18
Dilution Tunnel	2/19/18
Sample Dryers	2/9/18

#### Dilution Tunnel Traverse

Traverse Point	1	2	Center	3	4	5	6	Center	7	8
Δp (" H <sub>2</sub> O)	6.030	6.048	0.052	0.048	6.034	0.036	0.048	0.051	0.046	0.030
T (°F)	603									

Technician Signature: 

Date: 2/20/18

# Pellet Heater Preburn Data - ASTM E2779



Manufacturer: HHT Halifax  
 Model: Absolute 43-C  
 Tracking No.: 2269  
 Project No.: 0135PS039E  
 Test Date: 2/21/2018

PB Length: 90 min  
 Recording Interval: 1 min

Averages:			387	69	-0.05	N/A	N/A
Elapsed Time (min)	Scale Reading	Weight Change	Stack (F)	Ambient (F)	Draft ("H2O)	CO2 (%)	CO (%)
0	39.2	-	295	68	-0.04	7.60	0.02
1	39.1	-0.1	304	68	-0.04	9.65	0.07
2	39.0	-0.1	313	69	-0.04	9.52	0.04
3	38.9	-0.1	320	68	-0.05	8.67	0.03
4	38.9	0	327	68	-0.05	8.20	0.01
5	38.8	-0.1	335	68	-0.05	10.00	0.05
6	38.7	-0.1	341	68	-0.05	8.71	0.01
7	38.6	-0.1	344	69	-0.05	8.23	0.02
8	38.5	-0.1	348	69	-0.05	8.82	0.02
9	38.5	0	351	68	-0.05	8.39	0.01
10	38.4	-0.1	356	68	-0.05	8.66	0.01
11	38.3	-0.1	359	68	-0.05	8.91	0.03
12	38.2	-0.1	360	68	-0.05	8.33	0.02
13	38.1	-0.1	364	68	-0.05	8.73	0.01
14	38.1	0	366	69	-0.05	8.51	0.02
15	38.0	-0.1	367	69	-0.05	7.89	0.02
16	37.9	-0.1	372	69	-0.05	8.12	0.01
17	37.8	-0.1	374	68	-0.05	8.87	0.03
18	37.8	0	374	68	-0.05	7.60	0.02
19	37.9	0.1	377	69	-0.05	8.09	0.01
20	37.6	-0.3	378	69	-0.05	8.39	0.02
21	37.5	-0.1	377	68	-0.05	7.56	0.03
22	37.1	-0.4	377	69	-0.05	0.56	0.00
23	37.0	-0.1	377	69	-0.05	0.07	0.00
24	36.9	-0.1	379	69	-0.05	0.06	0.00
25	36.8	-0.1	381	69	-0.05	0.03	0.00
26	36.8	0	383	69	-0.05	0.01	0.00
27	36.7	-0.1	384	69	-0.05	0.00	0.00
28	36.6	-0.1	384	69	-0.05	0.00	0.00
29	36.5	-0.1	386	69	-0.05	0.00	0.00
30	36.4	-0.1	386	69	-0.05	0.00	0.00
31	36.3	-0.1	386	69	-0.05	0.00	0.00
32	36.3	0	387	69	-0.05	0.00	0.00
33	36.2	-0.1	387	69	-0.05	0.00	0.00
34	36.1	-0.1	388	69	-0.05	0.83	0.08
35	36.0	-0.1	388	69	-0.05	0.95	0.09
36	35.9	-0.1	389	69	-0.05	12.84	4.12
37	35.8	-0.1	391	69	-0.05	15.77	4.97
38	36.2	0.4	390	69	-0.05	15.41	4.76
39	36.1	-0.1	394	69	-0.05	9.45	0.03
40	36.0	-0.1	395	69	-0.05	8.74	0.02
41	35.9	-0.1	394	69	-0.05	8.21	0.02
42	35.9	0	393	69	-0.05	8.51	0.02
43	35.8	-0.1	395	69	-0.05	9.70	0.03
44	35.7	-0.1	395	69	-0.05	9.07	0.02
45	35.6	-0.1	395	69	-0.05	9.35	0.03

# Pellet Heater Preburn Data - ASTM E2779



Manufacturer: HHT Halifax  
 Model: Absolute 43-C  
 Tracking No.: 2269  
 Project No.: 0135PS039E  
 Test Date: 2/21/2018


PB Length: 90 min  
 Recording Interval: 1 min

Averages:			387	69	-0.05	N/A	N/A
Elapsed Time (min)	Scale Reading	Weight Change	Stack (F)	Ambient (F)	Draft ("H2O)	CO2 (%)	CO (%)
46	35.5	-0.1	398	69	-0.05	10.31	0.04
47	35.4	-0.1	398	69	-0.05	9.72	0.03
48	35.3	-0.1	399	69	-0.05	9.65	0.03
49	35.3	0	398	69	-0.05	9.56	0.03
50	35.2	-0.1	397	69	-0.05	8.96	0.01
51	35.1	-0.1	399	69	-0.05	9.83	0.02
52	35.0	-0.1	399	69	-0.05	9.51	0.02
53	34.9	-0.1	401	69	-0.05	9.47	0.01
54	34.8	-0.1	401	69	-0.05	9.60	0.02
55	34.7	-0.1	401	69	-0.05	9.11	0.02
56	34.7	0	400	69	-0.05	8.85	0.01
57	34.6	-0.1	399	69	-0.05	9.16	0.04
58	34.5	-0.1	402	69	-0.05	10.32	0.07
59	34.4	-0.1	404	69	-0.05	10.31	0.02
60	34.3	-0.1	404	69	-0.05	9.78	0.04
61	34.4	0.1	405	69	-0.05	10.05	0.04
62	34.1	-0.3	406	69	-0.05	9.92	0.04
63	34.0	-0.1	407	69	-0.05	10.35	0.03
64	33.9	-0.1	407	69	-0.05	9.69	0.03
65	33.8	-0.1	407	69	-0.05	9.63	0.01
66	33.8	0	405	69	-0.05	8.71	0.02
67	33.7	-0.1	405	69	-0.05	9.49	0.01
68	41.6	7.9	412	69	-0.05	9.55	0.02
69	41.4	-0.2	406	69	-0.05	8.02	0.01
70	41.3	-0.1	405	69	-0.05	9.45	0.02
71	41.2	-0.1	403	69	-0.05	9.05	0.02
72	41.2	0	403	69	-0.05	9.26	0.01
73	41.1	-0.1	403	69	-0.05	9.21	0.02
74	41.0	-0.1	405	69	-0.05	9.19	0.01
75	41.0	0	406	69	-0.06	10.35	0.05
76	40.9	-0.1	405	69	-0.05	9.52	0.04
77	40.8	-0.1	405	69	-0.06	9.73	0.04
78	40.7	-0.1	406	69	-0.06	10.26	0.06
79	40.6	-0.1	406	69	-0.05	9.52	0.02
80	40.5	-0.1	407	69	-0.05	10.09	0.06
81	40.4	-0.1	408	69	-0.05	10.63	0.08
82	40.3	-0.1	409	69	-0.06	10.21	0.03
83	40.2	-0.1	409	69	-0.06	9.36	0.06
84	40.1	-0.1	408	69	-0.06	9.00	0.03
85	40.0	-0.1	410	69	-0.06	11.64	0.08
86	40.0	0	410	69	-0.06	10.02	0.05
87	39.9	-0.1	410	69	-0.06	9.85	0.02
88	39.8	-0.1	409	69	-0.06	9.14	0.01
89	39.7	-0.1	408	69	-0.06	10.09	0.03
90	39.6	-0.1	408	70	-0.06	10.37	0.03

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1  
 Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet  
 Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)  
 Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg  
 OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99

  
 Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F


V<sub>straw</sub> 13.76 ft/sec V<sub>scint</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data											Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps				
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H₂O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H₂O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H₂O)	CO₂ (%)	CO (%)	Drier A	Drier B
0	0.000	0.000			0.87	73	1.6	0.36	73	0.8	103	0.052			15.1		408	68	68	70	-0.056	10.15	0.030	70	71
1	0.154	0.162	0.15	0.16	1.35	73	2.01	1.17	73	1.2	103	0.052	96	102	15.0	-0.1	409	69	69	69	-0.055	10.53	0.036	71	71
2	0.318	0.328	0.16	0.17	1.35	73	2.02	1.17	73	1.2	103	0.051	104	106	14.9	-0.1	409	69	69	69	-0.056	10.26	0.039	71	71
3	0.481	0.494	0.16	0.17	1.35	73	2.02	1.16	73	1.2	103	0.050	104	107	14.8	-0.1	410	70	70	69	-0.056	10.94	0.160	71	71
4	0.644	0.659	0.16	0.17	1.35	73	2.02	1.11	73	1.2	103	0.050	104	106	14.7	-0.1	410	70	70	69	-0.056	9.73	0.051	72	71
5	0.806	0.821	0.16	0.16	1.35	73	2.02	1.10	73	1.2	103	0.051	102	103	14.6	-0.1	409	70	70	69	-0.056	9.59	0.039	72	71
6	0.970	0.982	0.16	0.16	1.35	73	2.02	1.10	73	1.2	104	0.050	105	104	14.6	0	411	70	70	69	-0.056	10.92	0.043	72	72
7	1.133	1.144	0.16	0.16	1.35	73	2.01	1.10	73	1.2	104	0.051	103	103	14.5	-0.1	414	71	70	69	-0.056	10.85	0.070	72	72
8	1.297	1.307	0.16	0.16	1.35	73	2.01	1.10	74	1.2	104	0.050	105	105	14.4	-0.1	413	71	71	69	-0.056	10.34	0.052	72	72
9	1.459	1.469	0.16	0.16	1.34	74	2.01	1.10	74	1.2	104	0.051	102	103	14.3	-0.1	411	71	71	69	-0.055	9.40	0.032	72	72
10	1.622	1.631	0.16	0.16	1.33	74	2.01	1.10	74	1.2	104	0.051	103	103	14.2	-0.1	411	71	71	69	-0.055	9.66	0.045	72	72
11	1.784	1.793	0.16	0.16	1.34	74	2	1.10	74	1.2	104	0.050	103	104	14.1	-0.1	410	71	71	69	-0.055	10.11	0.032	73	72
12	1.947	1.955	0.16	0.16	1.34	74	2.01	1.10	74	1.2	104	0.049	105	105	14.0	-0.1	409	72	71	69	-0.055	9.24	0.017	73	73
13	2.110	2.117	0.16	0.16	1.34	74	2.01	1.09	74	1.2	104	0.050	104	104	13.9	-0.1	410	72	72	70	-0.056	10.86	0.049	73	73
14	2.272	2.278	0.16	0.16	1.34	74	2.01	1.09	74	1.2	104	0.050	103	104	13.9	0	410	72	72	70	-0.056	10.36	0.038	73	73
15	2.436	2.440	0.16	0.16	1.33	74	2.01	1.09	74	1.2	104	0.050	105	104	13.8	-0.1	409	72	72	70	-0.055	9.66	0.022	73	73
16	2.598	2.602	0.16	0.16	1.33	74	2	1.09	74	1.2	104	0.050	103	104	13.7	-0.1	409	72	72	69	-0.055	10.16	0.049	73	73
17	2.761	2.763	0.16	0.16	1.33	75	2	1.09	75	1.2	104	0.050	104	103	13.6	-0.1	408	72	72	69	-0.055	8.96	0.020	74	73
18	2.923	2.924	0.16	0.16	1.33	75	2.01	1.09	75	1.2	104	0.053	100	100	13.5	-0.1	408	72	72	69	-0.055	10.67	0.047	74	73
19	3.085	3.086	0.16	0.16	1.34	75	2	1.09	75	1.2	103	0.053	100	101	13.4	-0.1	408	73	72	69	-0.055	10.36	0.060	74	73
20	3.247	3.248	0.16	0.16	1.33	75	2.01	1.09	75	1.2	104	0.048	105	106	13.3	-0.1	411	73	72	69	-0.056	11.10	0.051	74	73
21	3.411	3.409	0.16	0.16	1.34	75	2.01	1.09	75	1.2	104	0.050	104	103	13.2	-0.1	412	73	72	69	-0.055	10.44	0.050	74	74
22	3.574	3.571	0.16	0.16	1.33	75	2.01	1.09	75	1.2	104	0.051	103	103	13.2	0	411	73	72	69	-0.056	9.76	0.026	74	74
23	3.736	3.732	0.16	0.16	1.33	75	2	1.09	75	1.2	104	0.052	101	101	13.1	-0.1	410	73	73	69	-0.055	10.10	0.056	74	74
24	3.898	3.894	0.16	0.16	1.33	76	2.01	1.09	76	1.2	104	0.050	103	104	13.0	-0.1	411	73	73	69	-0.055	10.67	0.044	74	74
25	4.061	4.055	0.16	0.16	1.33	76	2.01	1.08	76	1.2	103	0.052	101	101	12.9	-0.1	411	73	73	69	-0.055	9.45	0.021	75	74
26	4.223	4.216	0.16	0.16	1.33	76	2.01	1.09	76	1.2	104	0.051	102	102	12.8	-0.1	412	73	73	69	-0.056	10.33	0.032	75	74
27	4.386	4.378	0.16	0.16	1.33	76	2.01	1.08	76	1.2	104	0.049	105	105	12.7	-0.1	413	73	73	69	-0.056	10.06	0.047	75	74
28	4.549	4.540	0.16	0.16	1.33	76	2.01	1.09	76	1.2	104	0.049	105	105	12.6	-0.1	412	73	73	70	-0.056	10.31	0.048	75	74
29	4.712	4.701	0.16	0.16	1.33	76	2.01	1.08	76	1.2	104	0.050	104	103	12.5	-0.1	412	73	73	69	-0.056	9.94	0.035	75	74
30	4.874	4.862	0.16	0.16	1.32	77	2.01	1.08	77	1.2	104	0.051	102	102	12.4	-0.1	412	74	73	69	-0.055	9.92	0.053	75	74
31	5.040	5.026	0.17	0.16	1.32	77	2.01	1.09	77	1.2	104	0.052	103	103	12.4	0	412	74	73	69	-0.055	10.26	0.027	75	74
32	5.202	5.189	0.16	0.16	1.32	77	2.01	1.09	77	1.2	104	0.050	103	104	12.3	-0.1	411	74	73	69	-0.056	10.14	0.034	75	74
33	5.364	5.349	0.16	0.16	1.33	77	2.01	1.08	77	1.2	104	0.051	102	101	12.2	-0.1	414	74	73	70	-0.056	11.38	0.070	75	74
34	5.527	5.511	0.16	0.16	1.33	77	2.01	1.09	77	1.2	103	0.051	102	103	12.1	-0.1	414	74	73	69	-0.056	10.17	0.043	75	75
35	5.690	5.672	0.16	0.16	1.32	77	2.01	1.08	77	1.2	104	0.051	102	102	12.0	-0.1	415	74	73	69	-0.056	10.59	0.047	76	75
36	5.854	5.834	0.16	0.16	1.33	77	2.01	1.08	77	1.2	103	0.051	103	103	11.9	-0.1	414	74	73	69	-0.056	9.46	0.032	76	75
37	6.016	5.995	0.16	0.16	1.32	77	2.01	1.08	78	1.2	104	0.052	101	101	11.8	-0.1	414	74	73	69	-0.056	10.06	0.020	76	75
38	6.179	6.157	0.16	0.16	1.32	78	2.02	1.08	78	1.2	104	0.049	104	105	11.8	0	414	74	74	69	-0.056	9.45	0.021	76	75
39	6.341	6.319	0.16	0.16	1.33	78	2.02	1.08	78	1.2	104	0.053	100	101	11.7	-0.1	415	74	74	69	-0.056	10.70	0.025	76	75
40	6.504	6.480	0.16	0.16	1.33	78	2.02	1.08	78	1.2	104	0.052	101	101	11.6	-0.1	414	74	74	69	-0.056	10.59	0.078	76	75
41	6.667	6.641	0.16	0.16	1.33	78	2.02	1.08	78	1.2	104	0.053	100	100	11.5	-0.1	414	74	74	69	-0.056	9.94	0.015	76	75

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1  
 Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet  
 Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)  
 Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg  
 OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99

  
 Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H2O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H2O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H2O)	CO2 (%)	CO (%)	Drier A	Drier B
42	6.830	6.803	0.16	0.16	1.33	78	2.02	1.08	78	1.2	104	0.052	101	101	11.4	-0.1	414	74	74	69	-0.056	10.19	0.030	76	75
43	6.993	6.965	0.16	0.16	1.32	78	2.02	1.08	78	1.2	104	0.051	102	102	11.3	-0.1	413	74	74	69	-0.055	9.78	0.047	76	75
44	7.156	7.126	0.16	0.16	1.32	78	2.03	1.08	78	1.2	104	0.050	103	103	11.2	-0.1	412	74	74	69	-0.056	9.89	0.036	76	75
45	7.319	7.288	0.16	0.16	1.32	78	2.02	1.09	78	1.2	104	0.051	102	102	11.1	-0.1	411	74	74	69	-0.056	9.94	0.039	76	75
46	7.482	7.449	0.16	0.16	1.33	78	2.03	1.08	78	1.2	104	0.049	104	104	11.1	0	412	74	74	69	-0.056	10.65	0.087	76	75
47	7.644	7.611	0.16	0.16	1.32	79	2.03	1.08	79	1.2	104	0.050	102	103	11.0	-0.1	412	74	74	70	-0.055	10.43	0.130	76	75
48	7.807	7.772	0.16	0.16	1.33	79	2.03	1.08	79	1.2	104	0.051	102	102	10.9	-0.1	409	74	74	70	-0.056	8.85	0.029	77	75
49	7.970	7.934	0.16	0.16	1.33	79	2.03	1.08	79	1.2	103	0.051	102	102	10.8	-0.1	408	74	74	70	-0.055	9.01	0.026	77	75
50	8.134	8.095	0.16	0.16	1.32	79	2.02	1.08	79	1.2	104	0.049	105	104	10.7	-0.1	409	74	74	70	-0.055	10.32	0.069	77	75
51	8.297	8.257	0.16	0.16	1.32	79	2.03	1.08	79	1.2	104	0.049	104	104	10.6	-0.1	410	74	74	70	-0.056	9.79	0.019	77	75
52	8.460	8.418	0.16	0.16	1.32	79	2.03	1.07	79	1.2	103	0.050	103	103	10.5	-0.1	409	74	74	71	-0.056	9.75	0.027	77	75
53	8.622	8.580	0.16	0.16	1.32	79	2.03	1.08	79	1.2	104	0.049	103	104	10.5	0	411	75	74	71	-0.055	9.71	0.035	77	75
54	8.785	8.741	0.16	0.16	1.32	79	2.04	1.08	79	1.2	103	0.051	102	102	10.4	-0.1	410	75	74	71	-0.055	10.17	0.038	77	75
55	8.948	8.903	0.16	0.16	1.33	79	2.04	1.07	79	1.2	103	0.051	102	102	10.3	-0.1	410	75	74	71	-0.056	10.01	0.058	77	75
56	9.111	9.064	0.16	0.16	1.32	79	2.04	1.08	79	1.2	104	0.049	104	104	10.2	-0.1	412	75	74	71	-0.055	11.52	0.150	77	75
57	9.274	9.225	0.16	0.16	1.32	80	2.04	1.08	80	1.2	104	0.050	103	102	10.1	-0.1	412	75	74	71	-0.056	10.73	0.085	77	75
58	9.437	9.387	0.16	0.16	1.32	80	2.03	1.07	80	1.2	104	0.051	102	102	10.0	-0.1	413	75	74	71	-0.056	10.71	0.066	77	76
59	9.600	9.548	0.16	0.16	1.32	80	2.04	1.07	80	1.2	104	0.053	100	100	9.9	-0.1	412	75	74	71	-0.056	10.82	0.065	77	76
60	9.766	9.709	0.17	0.16	1.34	80	1.99	1.07	80	1.2	103	0.050	105	102	9.8	-0.1	411	75	74	71	-0.056	9.63	0.036	77	76
61	9.929	9.870	0.16	0.16	1.32	80	2.03	1.08	80	1.2	104	0.051	102	101	9.7	-0.1	411	75	74	71	-0.056	10.28	0.200	77	76
62	10.092	10.032	0.16	0.16	1.32	80	2.02	1.08	80	1.2	103	0.053	100	100	9.7	0	407	76	74	71	-0.055	7.47	0.018	77	76
63	10.255	10.193	0.16	0.16	1.33	80	2.02	1.08	80	1.2	102	0.051	102	101	9.6	-0.1	398	76	74	71	-0.054	5.03	0.041	77	76
64	10.418	10.355	0.16	0.16	1.33	80	2.02	1.08	80	1.2	101	0.050	103	103	9.6	0	387	76	74	71	-0.053	4.19	0.021	77	76
65	10.582	10.516	0.16	0.16	1.33	80	2.02	1.07	80	1.2	100	0.051	102	101	9.6	0	376	76	74	71	-0.052	3.80	0.025	77	76
66	10.745	10.678	0.16	0.16	1.33	80	2.02	1.07	80	1.2	99	0.053	99	100	9.6	0	366	76	74	71	-0.051	3.83	0.017	77	76
67	10.910	10.839	0.17	0.16	1.32	80	2.02	1.08	80	1.2	98	0.052	101	100	9.5	-0.1	357	75	74	71	-0.049	3.73	0.022	77	75
68	11.073	11.000	0.16	0.16	1.33	80	2.01	1.08	81	1.2	98	0.052	100	100	9.5	0	347	75	74	71	-0.048	3.32	0.018	77	75
69	11.237	11.162	0.16	0.16	1.32	81	2.01	1.07	81	1.2	97	0.050	103	102	9.5	0	339	75	74	71	-0.047	3.58	0.019	77	75
70	11.400	11.323	0.16	0.16	1.32	81	2.02	1.07	81	1.2	95	0.053	99	99	9.5	0	331	75	74	71	-0.047	3.90	0.020	77	75
71	11.564	11.485	0.16	0.16	1.33	81	2.02	1.08	81	1.2	95	0.051	101	101	9.4	-0.1	322	75	74	71	-0.045	2.74	0.027	76	75
72	11.727	11.646	0.16	0.16	1.32	81	2.02	1.07	81	1.3	94	0.051	101	100	9.4	0	317	75	74	71	-0.045	4.51	0.022	76	75
73	11.891	11.808	0.16	0.16	1.33	81	2.01	1.07	81	1.2	93	0.050	102	102	9.4	0	311	75	74	71	-0.044	3.49	0.022	76	75
74	12.055	11.969	0.16	0.16	1.33	81	2.01	1.07	81	1.2	93	0.051	101	100	9.4	0	304	75	74	71	-0.044	3.71	0.027	76	74
75	12.218	12.130	0.16	0.16	1.33	81	2.01	1.07	81	1.2	92	0.049	103	102	9.3	-0.1	301	75	74	71	-0.043	4.07	0.024	76	74
76	12.383	12.292	0.16	0.16	1.34	81	2.01	1.07	81	1.3	91	0.051	102	101	9.3	0	300	75	74	71	-0.043	5.38	0.020	76	74
77	12.547	12.453	0.16	0.16	1.33	81	2.02	1.08	81	1.3	91	0.049	103	102	9.2	-0.1	298	75	74	71	-0.042	4.48	0.020	76	74
78	12.711	12.614	0.16	0.16	1.33	81	2.02	1.07	81	1.2	91	0.049	103	102	9.2	0	296	75	74	71	-0.043	5.02	0.039	76	74
79	12.874	12.776	0.16	0.16	1.33	81	2.01	1.08	81	1.3	91	0.051	100	101	9.1	-0.1	297	75	74	71	-0.043	6.07	0.017	76	74
80	13.038	12.938	0.16	0.16	1.33	81	2.02	1.07	81	1.3	91	0.051	101	101	9.1	0	294	75	74	71	-0.042	4.28	0.022	76	74
81	13.201	13.099	0.16	0.16	1.33	81	2.01	1.07	81	1.3	90	0.049	102	102	9.1	0	293	75	74	71	-0.042	5.25	0.026	76	74
82	13.365	13.260	0.16	0.16	1.33	81	2.01	1.07	81	1.3	90	0.052	100	99	9.0	-0.1	291	74	74	71	-0.042	4.56	0.027	76	74
83	13.529	13.422	0.16	0.16	1.33	81	2.01	1.07	81	1.3	90	0.050	102	102	9.0	0	289	74	74	71	-0.042	4.83	0.027	76	74

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99



Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H2O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H2O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H2O)	CO2 (%)	CO (%)	Drier A	Drier B
84	13.693	13.584	0.16	0.16	1.33	81	2.02	1.07	81	1.2	90	0.052	100	100	9.0	0	289	74	74	71	-0.042	4.94	0.022	76	74
85	13.856	13.745	0.16	0.16	1.33	81	2.02	1.07	81	1.3	90	0.051	100	100	8.9	-0.1	290	74	74	71	-0.042	6.00	0.014	76	73
86	14.021	13.906	0.17	0.16	1.33	81	2.02	1.07	81	1.2	90	0.052	101	99	8.9	0	289	74	74	71	-0.042	5.48	0.025	76	73
87	14.185	14.067	0.16	0.16	1.33	81	2.02	1.07	81	1.3	90	0.050	102	101	8.9	0	288	74	74	71	-0.042	5.16	0.030	76	73
88	14.349	14.229	0.16	0.16	1.33	82	2.02	1.07	81	1.3	89	0.053	99	99	8.8	-0.1	288	74	74	71	-0.042	5.73	0.024	76	73
89	14.513	14.390	0.16	0.16	1.32	81	2.02	1.07	81	1.3	89	0.051	101	100	8.8	0	288	74	74	71	-0.043	5.58	0.022	75	73
90	14.677	14.551	0.16	0.16	1.32	82	2.02	1.07	82	1.3	89	0.051	101	100	8.7	-0.1	289	74	74	71	-0.042	5.76	0.023	75	73
91	14.840	14.713	0.16	0.16	1.32	82	2.03	1.07	82	1.3	89	0.051	100	100	8.7	0	289	74	73	71	-0.042	5.49	0.018	75	73
92	15.004	14.874	0.16	0.16	1.33	82	2.02	1.07	82	1.3	89	0.050	102	101	8.6	-0.1	288	74	73	71	-0.042	4.74	0.032	75	73
93	15.167	15.035	0.16	0.16	1.33	82	2.03	1.07	82	1.3	89	0.051	100	100	8.6	0	289	74	74	71	-0.042	5.90	0.014	75	73
94	15.331	15.196	0.16	0.16	1.33	82	2.02	1.07	82	1.3	89	0.048	104	103	8.6	0	289	74	73	71	-0.042	5.25	0.026	75	73
95	15.495	15.358	0.16	0.16	1.33	82	2.03	1.07	82	1.3	89	0.052	100	99	8.5	-0.1	288	74	73	71	-0.042	4.68	0.030	75	73
96	15.659	15.518	0.16	0.16	1.33	82	2.03	1.06	82	1.3	89	0.052	100	98	8.5	0	288	74	73	71	-0.042	5.32	0.018	75	73
97	15.823	15.679	0.16	0.16	1.33	82	2.03	1.07	82	1.3	89	0.049	103	102	8.4	-0.1	289	74	73	71	-0.042	5.92	0.016	75	73
98	15.987	15.841	0.16	0.16	1.33	82	2.03	1.07	82	1.3	89	0.051	101	100	8.4	0	287	74	73	71	-0.042	4.56	0.034	75	73
99	16.151	16.002	0.16	0.16	1.32	82	2.03	1.07	82	1.3	89	0.051	101	100	8.4	0	285	74	73	71	-0.041	4.36	0.028	75	73
100	16.314	16.162	0.16	0.16	1.32	82	2.02	1.07	82	1.3	89	0.051	100	99	8.3	-0.1	284	74	73	71	-0.042	4.74	0.034	75	73
101	16.478	16.324	0.16	0.16	1.32	82	2.03	1.07	82	1.3	89	0.051	101	100	8.3	0	283	74	73	71	-0.041	4.67	0.020	75	72
102	16.641	16.486	0.16	0.16	1.32	82	2.03	1.06	82	1.3	89	0.052	99	99	8.3	0	282	73	73	71	-0.041	5.37	0.015	75	72
103	16.805	16.646	0.16	0.16	1.33	82	2.04	1.06	82	1.3	88	0.051	101	99	8.2	-0.1	282	73	73	70	-0.041	5.18	0.017	74	72
104	16.969	16.807	0.16	0.16	1.32	82	2.03	1.06	82	1.3	88	0.052	100	99	8.2	0	283	73	73	70	-0.042	5.73	0.022	74	72
105	17.132	16.968	0.16	0.16	1.32	82	2.04	1.07	82	1.3	88	0.051	100	100	8.1	-0.1	284	73	73	71	-0.042	5.75	0.015	74	72
106	17.297	17.129	0.16	0.16	1.33	82	2.04	1.06	82	1.3	88	0.050	102	101	8.1	0	285	73	73	70	-0.042	5.77	0.016	74	72
107	17.461	17.290	0.16	0.16	1.32	82	2.03	1.06	82	1.3	88	0.051	101	100	8.1	0	285	73	73	70	-0.042	5.40	0.016	74	72
108	17.625	17.451	0.16	0.16	1.32	82	2.03	1.06	82	1.3	88	0.051	101	100	8.0	-0.1	284	73	73	70	-0.042	5.20	0.020	74	72
109	17.788	17.612	0.16	0.16	1.33	82	2.04	1.07	82	1.3	88	0.053	98	98	8.0	0	284	73	73	71	-0.042	5.34	0.014	74	72
110	17.952	17.773	0.16	0.16	1.32	82	2.04	1.06	82	1.3	88	0.051	101	100	7.9	-0.1	283	73	73	71	-0.041	5.11	0.023	74	72
111	18.115	17.933	0.16	0.16	1.32	82	2.04	1.06	82	1.3	88	0.051	100	99	7.9	0	282	73	73	71	-0.041	4.87	0.023	74	72
112	18.279	18.094	0.16	0.16	1.32	82	2.04	1.07	82	1.3	88	0.050	102	101	7.9	0	282	73	73	71	-0.041	5.32	0.013	74	72
113	18.442	18.255	0.16	0.16	1.32	82	2.04	1.06	82	1.3	88	0.052	99	99	7.8	-0.1	282	73	73	71	-0.042	4.87	0.032	74	72
114	18.606	18.416	0.16	0.16	1.33	82	2.04	1.06	82	1.3	88	0.052	100	99	7.8	0	281	73	73	71	-0.041	4.87	0.022	74	72
115	18.770	18.576	0.16	0.16	1.33	82	2.04	1.06	82	1.3	88	0.052	100	98	7.8	0	282	73	73	70	-0.042	6.19	0.015	74	72
116	18.934	18.738	0.16	0.16	1.33	82	2.04	1.06	82	1.3	88	0.050	102	101	7.7	-0.1	282	73	73	71	-0.041	5.20	0.020	74	72
117	19.098	18.898	0.16	0.16	1.32	82	2.04	1.06	82	1.3	88	0.051	101	99	7.7	0	281	73	73	71	-0.041	5.28	0.019	74	72
118	19.261	19.058	0.16	0.16	1.32	82	2.04	1.06	82	1.3	88	0.050	101	100	7.6	-0.1	281	73	73	71	-0.041	5.16	0.024	74	72
119	19.425	19.220	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.054	98	97	7.6	0	283	73	73	71	-0.041	5.83	0.013	74	72
120	19.588	19.380	0.16	0.16	1.32	82	2.05	1.05	82	1.3	88	0.051	100	99	7.6	0	283	73	73	70	-0.042	5.35	0.014	74	72
121	19.752	19.540	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.050	102	100	7.5	-0.1	285	73	73	71	-0.042	5.67	0.011	74	72
122	19.915	19.701	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.052	99	99	7.5	0	286	73	73	71	-0.042	6.03	0.017	74	72
123	20.078	19.862	0.16	0.16	1.32	82	2.05	1.05	82	1.3	88	0.052	99	99	7.4	-0.1	286	73	73	71	-0.042	5.64	0.029	74	72
124	20.242	20.022	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.050	102	100	7.4	0	285	73	73	70	-0.042	5.34	0.023	74	72
125	20.406	20.182	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.053	99	97	7.4	0	286	73	73	71	-0.042	5.38	0.018	74	72

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99



Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O °F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H2O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H2O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H2O)	CO2 (%)	CO (%)	Drier A	Drier B
126	20.570	20.344	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.052	100	99	7.3	-0.1	286	73	73	71	-0.042	5.54	0.011	74	72
127	20.733	20.503	0.16	0.16	1.32	82	2.05	1.06	82	1.3	89	0.050	101	99	7.3	0	287	73	73	71	-0.042	5.61	0.013	74	72
128	20.897	20.664	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.051	101	100	7.2	-0.1	287	73	73	71	-0.042	6.19	0.015	74	72
129	21.060	20.825	0.16	0.16	1.31	82	2.06	1.05	82	1.3	89	0.051	100	100	7.2	0	287	73	73	70	-0.042	5.52	0.019	74	72
130	21.223	20.985	0.16	0.16	1.32	82	2.05	1.05	82	1.3	88	0.051	100	99	7.2	0	286	73	73	71	-0.042	5.25	0.025	74	72
131	21.387	21.145	0.16	0.16	1.32	82	2.05	1.06	82	1.3	88	0.051	101	99	7.1	-0.1	286	73	73	71	-0.042	5.29	0.013	74	72
132	21.550	21.306	0.16	0.16	1.32	82	2.05	1.05	82	1.3	88	0.052	99	99	7.1	0	286	73	73	70	-0.042	5.36	0.013	74	72
133	21.713	21.466	0.16	0.16	1.32	82	2.06	1.05	82	1.3	88	0.053	98	97	7.0	-0.1	285	73	73	70	-0.042	4.43	0.024	74	72
134	21.877	21.626	0.16	0.16	1.32	82	2.06	1.06	82	1.3	88	0.051	101	99	7.0	0	285	73	73	70	-0.042	4.82	0.023	74	72
135	22.041	21.787	0.16	0.16	1.32	82	2.06	1.05	82	1.3	88	0.051	101	100	7.0	0	285	73	73	70	-0.042	5.62	0.017	74	72
136	22.205	21.947	0.16	0.16	1.32	82	2.06	1.05	82	1.3	88	0.051	101	99	6.9	-0.1	287	73	73	70	-0.042	5.92	0.017	74	72
137	22.368	22.106	0.16	0.16	1.31	82	2.06	1.06	82	1.3	88	0.050	101	99	6.9	0	289	73	73	70	-0.042	6.14	0.013	74	72
138	22.531	22.267	0.16	0.16	1.32	82	2.06	1.06	82	1.3	88	0.052	99	99	6.8	-0.1	289	73	73	71	-0.043	5.70	0.018	74	72
139	22.694	22.427	0.16	0.16	1.32	82	2.06	1.05	82	1.3	88	0.051	100	99	6.8	0	289	73	73	70	-0.043	5.57	0.025	74	72
140	22.857	22.587	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.051	100	99	6.8	0	289	73	73	70	-0.042	5.01	0.025	74	72
141	23.021	22.747	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.050	102	100	6.7	-0.1	288	73	73	70	-0.042	5.20	0.018	74	72
142	23.184	22.907	0.16	0.16	1.32	82	2.07	1.04	82	1.3	88	0.053	98	97	6.7	0	287	73	73	70	-0.042	4.92	0.023	74	72
143	23.348	23.067	0.16	0.16	1.31	82	2.06	1.05	82	1.3	88	0.051	101	99	6.6	-0.1	287	73	73	71	-0.042	4.92	0.018	74	72
144	23.511	23.227	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.051	100	99	6.6	0	287	73	73	71	-0.042	4.97	0.031	74	72
145	23.675	23.387	0.16	0.16	1.31	82	2.07	1.05	82	1.3	88	0.050	102	100	6.6	0	287	73	73	70	-0.042	5.79	0.012	74	72
146	23.838	23.547	0.16	0.16	1.31	82	2.07	1.05	82	1.3	88	0.050	101	100	6.5	-0.1	288	73	73	70	-0.043	5.88	0.016	74	72
147	24.000	23.706	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.050	100	99	6.5	0	289	73	73	70	-0.043	5.84	0.016	73	72
148	24.163	23.867	0.16	0.16	1.31	82	2.07	1.05	82	1.3	88	0.050	101	101	6.4	-0.1	287	73	73	70	-0.042	4.99	0.022	73	72
149	24.327	24.026	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.050	102	99	6.4	0	287	73	73	71	-0.042	5.42	0.026	73	72
150	24.490	24.186	0.16	0.16	1.32	82	2.07	1.05	82	1.3	88	0.051	100	99	6.4	0	286	73	73	70	-0.042	5.36	0.016	73	72
151	24.653	24.346	0.16	0.16	1.32	82	2.08	1.04	82	1.3	88	0.051	100	99	6.3	-0.1	287	73	73	70	-0.042	5.52	0.026	73	72
152	24.817	24.505	0.16	0.16	1.31	82	2.08	1.05	82	1.3	88	0.051	101	98	6.3	0	287	73	73	70	-0.042	5.29	0.011	73	72
153	24.980	24.665	0.16	0.16	1.32	82	2.08	1.05	82	1.3	88	0.051	100	99	6.2	-0.1	287	73	73	71	-0.042	5.42	0.013	74	72
154	25.143	24.827	0.16	0.16	1.30	82	2.08	1.10	82	1.4	88	0.053	98	98	6.2	0	287	73	73	70	-0.042	5.40	0.023	73	72
155	25.305	24.991	0.16	0.16	1.31	82	2.07	1.09	82	1.4	88	0.051	99	101	6.2	0	287	73	73	70	-0.042	5.32	0.016	73	72
156	25.468	25.154	0.16	0.16	1.31	82	2.08	1.10	82	1.4	88	0.049	102	103	6.1	-0.1	288	73	73	70	-0.042	6.05	0.013	73	72
157	25.631	25.318	0.16	0.16	1.31	82	2.08	1.11	82	1.4	88	0.050	101	103	6.1	0	288	73	73	71	-0.042	4.94	0.022	73	72
158	25.794	25.481	0.16	0.16	1.31	82	2.09	1.10	82	1.4	88	0.051	100	101	6.0	-0.1	289	73	73	70	-0.042	5.64	0.012	74	72
159	25.958	25.646	0.16	0.16	1.32	82	2.08	1.10	82	1.4	88	0.053	99	100	6.0	0	289	73	73	71	-0.042	5.88	0.017	73	72
160	26.121	25.809	0.16	0.16	1.31	82	2.08	1.09	82	1.4	88	0.051	100	101	6.0	0	287	73	73	71	-0.042	4.43	0.019	73	72
161	26.284	25.972	0.16	0.16	1.30	82	2.08	1.10	82	1.4	88	0.050	101	102	5.9	-0.1	287	73	73	71	-0.042	5.33	0.017	73	72
162	26.446	26.135	0.16	0.16	1.31	82	2.08	1.10	82	1.4	88	0.052	98	100	5.9	0	287	73	73	71	-0.042	5.18	0.029	73	72
163	26.609	26.299	0.16	0.16	1.31	82	2.08	1.09	82	1.4	88	0.050	101	103	5.8	-0.1	285	73	73	71	-0.042	4.72	0.025	73	72
164	26.772	26.463	0.16	0.16	1.31	82	2.08	1.10	82	1.4	88	0.051	100	101	5.8	0	284	73	73	71	-0.042	4.83	0.020	73	72
165	26.934	26.626	0.16	0.16	1.31	82	2.08	1.10	82	1.4	88	0.051	99	101	5.8	0	285	73	73	71	-0.042	5.40	0.021	73	72
166	27.098	26.789	0.16	0.16	1.31	82	2.09	1.09	82	1.4	88	0.050	102	102	5.7	-0.1	286	73	73	71	-0.042	5.59	0.015	73	72
167	27.261	26.952	0.16	0.16	1.31	82	2.09	1.10	82	1.4	88	0.052	99	100	5.7	0	286	73	73	71	-0.042	5.40	0.022	73	72

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99



Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O °F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H₂O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H₂O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H₂O)	CO₂ (%)	CO (%)	Drier A	Drier B
168	27.424	27.115	0.16	0.16	1.30	82	2.09	1.09	82	1.4	88	0.052	99	100	5.6	-0.1	286	73	73	71	-0.042	5.62	0.011	73	72
169	27.586	27.279	0.16	0.16	1.31	82	2.09	1.09	82	1.4	89	0.051	99	102	5.6	0	287	73	73	71	-0.042	5.94	0.015	73	72
170	27.749	27.442	0.16	0.16	1.31	82	2.09	1.09	82	1.4	88	0.052	99	100	5.5	-0.1	287	73	73	71	-0.042	5.99	0.022	73	72
171	27.911	27.605	0.16	0.16	1.31	82	2.09	1.09	82	1.4	89	0.051	99	101	5.5	0	288	73	73	71	-0.042	5.97	0.012	73	72
172	28.073	27.768	0.16	0.16	1.31	82	2.09	1.09	82	1.4	89	0.050	100	102	5.5	0	288	73	73	71	-0.043	5.48	0.024	73	72
173	28.237	27.930	0.16	0.16	1.31	82	2.1	1.09	82	1.4	89	0.050	102	101	5.4	-0.1	289	73	73	71	-0.043	5.75	0.017	73	72
174	28.400	28.094	0.16	0.16	1.31	82	2.09	1.09	82	1.4	89	0.050	101	103	5.4	0	290	73	73	71	-0.042	5.79	0.019	73	72
175	28.562	28.257	0.16	0.16	1.30	82	2.1	1.09	82	1.4	89	0.051	99	101	5.4	0	289	73	73	70	-0.042	4.65	0.016	73	72
176	28.724	28.419	0.16	0.16	1.30	82	2.1	1.09	82	1.4	89	0.048	103	103	5.3	-0.1	289	73	73	70	-0.042	5.22	0.015	73	72
177	28.887	28.582	0.16	0.16	1.31	82	2.1	1.09	82	1.4	89	0.051	100	101	5.3	0	291	73	73	71	-0.043	6.22	0.013	73	72
178	29.049	28.745	0.16	0.16	1.31	82	2.09	1.09	82	1.4	89	0.050	100	102	5.2	-0.1	289	73	73	70	-0.043	4.62	0.018	73	72
179	29.212	28.908	0.16	0.16	1.30	82	2.1	1.08	82	1.4	89	0.050	101	102	5.2	0	289	73	73	71	-0.043	5.64	0.011	73	72
180	29.375	29.071	0.16	0.16	1.30	82	2.1	1.09	82	1.4	89	0.051	100	101	5.1	-0.1	289	73	73	71	-0.043	5.51	0.017	73	72
181	29.537	29.233	0.16	0.16	1.30	82	2.11	1.09	82	1.4	88	0.050	100	101	5.1	0	288	73	73	70	-0.042	5.43	0.012	73	72
182	29.699	29.395	0.16	0.16	1.30	82	2.11	1.09	82	1.4	89	0.051	99	100	5.1	0	288	73	73	71	-0.043	5.44	0.021	73	72
183	29.862	29.558	0.16	0.16	1.30	82	2.1	1.08	82	1.4	88	0.049	102	103	5.0	-0.1	286	73	73	70	-0.042	4.60	0.012	73	72
184	30.024	29.721	0.16	0.16	1.30	82	2.11	1.08	82	1.4	88	0.052	98	100	5.0	0	284	73	73	70	-0.042	4.09	0.034	73	72
185	30.186	29.883	0.16	0.16	1.31	82	2.11	1.08	82	1.4	88	0.051	99	100	5.0	0	281	73	73	70	-0.041	4.21	0.017	73	72
186	30.349	30.045	0.16	0.16	1.30	82	2.1	1.08	82	1.4	88	0.051	100	100	4.9	-0.1	278	73	73	70	-0.041	3.68	0.021	73	72
187	30.512	30.208	0.16	0.16	1.30	82	2.11	1.08	82	1.4	87	0.052	99	100	4.9	0	273	73	73	70	-0.040	2.72	0.020	73	72
188	30.674	30.371	0.16	0.16	1.29	82	2.1	1.08	82	1.4	87	0.051	99	101	4.9	0	267	73	73	71	-0.039	2.46	0.019	73	72
189	30.836	30.533	0.16	0.16	1.30	82	2.11	1.08	82	1.4	87	0.051	99	100	4.9	0	263	73	73	71	-0.038	2.52	0.035	73	71
190	30.998	30.695	0.16	0.16	1.31	82	2.11	1.08	82	1.4	86	0.051	99	100	4.9	0	257	73	73	71	-0.038	2.19	0.034	73	71
191	31.161	30.857	0.16	0.16	1.30	82	2.11	1.09	82	1.4	86	0.050	101	101	4.9	0	254	73	73	70	-0.037	2.38	0.025	73	71
192	31.323	31.020	0.16	0.16	1.30	82	2.11	1.08	82	1.4	86	0.051	99	101	4.9	0	249	73	73	71	-0.036	2.14	0.038	73	71
193	31.486	31.183	0.16	0.16	1.30	82	2.11	1.08	82	1.4	86	0.051	100	101	4.8	-0.1	247	73	73	70	-0.036	2.83	0.021	73	71
194	31.649	31.344	0.16	0.16	1.29	82	2.11	1.08	82	1.4	86	0.050	101	100	4.8	0	246	73	73	70	-0.036	2.72	0.017	73	71
195	31.810	31.506	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.053	97	98	4.8	0	244	73	73	70	-0.035	2.63	0.020	73	71
196	31.973	31.669	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.051	100	101	4.8	0	243	73	73	70	-0.035	2.67	0.021	73	71
197	32.135	31.832	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.050	100	102	4.8	0	241	73	72	70	-0.035	2.64	0.021	73	71
198	32.297	31.994	0.16	0.16	1.30	82	2.12	1.07	82	1.4	85	0.052	98	99	4.7	-0.1	241	73	72	71	-0.035	3.07	0.026	73	71
199	32.460	32.155	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.050	101	100	4.7	0	242	72	72	71	-0.035	3.61	0.027	73	71
200	32.622	32.318	0.16	0.16	1.29	82	2.12	1.08	82	1.4	85	0.052	98	100	4.7	0	244	72	72	70	-0.036	3.72	0.020	73	71
201	32.784	32.480	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.053	97	98	4.6	-0.1	244	72	72	70	-0.035	3.84	0.022	73	71
202	32.946	32.642	0.16	0.16	1.30	82	2.12	1.08	82	1.4	85	0.050	100	101	4.6	0	245	72	72	70	-0.036	3.76	0.023	73	71
203	33.108	32.804	0.16	0.16	1.30	82	2.11	1.08	82	1.4	85	0.053	97	98	4.6	0	246	72	72	70	-0.036	3.86	0.019	73	71
204	33.271	32.966	0.16	0.16	1.30	82	2.12	1.08	82	1.4	85	0.050	101	101	4.6	0	246	72	72	70	-0.036	3.53	0.019	73	71
205	33.434	33.128	0.16	0.16	1.30	82	2.12	1.07	82	1.4	85	0.050	101	101	4.5	-0.1	245	72	72	70	-0.036	3.53	0.018	73	71
206	33.596	33.290	0.16	0.16	1.29	82	2.12	1.07	82	1.4	85	0.053	97	98	4.5	0	245	72	72	70	-0.036	3.52	0.022	73	71
207	33.757	33.452	0.16	0.16	1.30	82	2.12	1.08	82	1.4	85	0.050	99	101	4.5	0	245	72	72	70	-0.036	3.77	0.020	73	71
208	33.920	33.614	0.16	0.16	1.30	82	2.12	1.08	82	1.4	85	0.052	99	99	4.4	-0.1	244	72	72	70	-0.036	3.09	0.023	73	71
209	34.081	33.776	0.16	0.16	1.30	82	2.12	1.07	82	1.4	85	0.051	98	100	4.4	0	244	72	72	70	-0.036	3.53	0.019	73	71



### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99

  
 Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H <sub>2</sub> O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H <sub>2</sub> O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H <sub>2</sub> O)	CO <sub>2</sub> (%)	CO (%)	Drier A	Drier B
210	34.244	33.938	0.16	0.16	1.30	82	2.13	1.08	82	1.4	85	0.050	101	101	4.4	0	244	72	72	70	-0.036	3.32	0.021	73	71
211	34.407	34.099	0.16	0.16	1.30	82	2.12	1.07	82	1.4	85	0.052	99	98	4.3	-0.1	244	72	72	70	-0.036	3.81	0.014	73	71
212	34.569	34.261	0.16	0.16	1.29	82	2.13	1.07	82	1.4	85	0.047	103	104	4.3	0	244	72	72	70	-0.036	3.28	0.020	73	71
213	34.730	34.424	0.16	0.16	1.30	82	2.12	1.07	82	1.4	85	0.051	98	101	4.3	0	243	72	72	70	-0.036	3.36	0.027	73	71
214	34.892	34.585	0.16	0.16	1.30	82	2.13	1.07	82	1.4	85	0.051	99	99	4.3	0	243	72	72	70	-0.035	3.36	0.018	73	71
215	35.054	34.746	0.16	0.16	1.30	82	2.13	1.07	82	1.4	85	0.052	98	98	4.2	-0.1	243	72	72	70	-0.036	3.40	0.020	73	71
216	35.216	34.908	0.16	0.16	1.30	82	2.13	1.07	82	1.4	85	0.053	97	98	4.2	0	244	72	72	70	-0.036	3.61	0.019	73	71
217	35.379	35.071	0.16	0.16	1.30	82	2.13	1.07	82	1.4	85	0.051	100	101	4.2	0	245	72	72	70	-0.036	3.80	0.012	73	71
218	35.541	35.232	0.16	0.16	1.28	82	2.14	1.07	82	1.4	85	0.052	98	98	4.1	-0.1	245	72	72	70	-0.036	3.95	0.019	73	71
219	35.702	35.393	0.16	0.16	1.29	82	2.13	1.07	82	1.4	85	0.051	98	99	4.1	0	244	72	72	70	-0.036	3.64	0.035	73	71
220	35.864	35.554	0.16	0.16	1.29	82	2.14	1.07	82	1.4	84	0.054	96	96	4.1	0	243	72	72	70	-0.036	3.32	0.015	73	71
221	36.026	35.717	0.16	0.16	1.29	82	2.14	1.07	82	1.4	85	0.052	98	100	4.1	0	243	72	72	70	-0.036	3.31	0.023	73	71
222	36.189	35.878	0.16	0.16	1.30	82	2.13	1.07	82	1.4	85	0.052	99	98	4.0	-0.1	245	72	72	70	-0.036	3.85	0.011	73	71
223	36.351	36.039	0.16	0.16	1.29	82	2.13	1.07	82	1.4	84	0.051	99	99	4.0	0	245	72	72	70	-0.036	3.65	0.018	73	71
224	36.513	36.200	0.16	0.16	1.28	82	2.14	1.07	82	1.4	85	0.052	98	98	4.0	0	246	72	72	70	-0.036	3.71	0.012	73	71
225	36.674	36.362	0.16	0.16	1.29	82	2.14	1.07	82	1.5	85	0.051	98	100	4.0	0	246	72	72	70	-0.036	3.70	0.018	73	71
226	36.836	36.523	0.16	0.16	1.29	82	2.14	1.06	82	1.5	85	0.050	100	100	3.9	-0.1	246	72	72	70	-0.036	3.69	0.019	73	71
227	36.998	36.684	0.16	0.16	1.29	82	2.14	1.07	82	1.5	85	0.050	100	100	3.9	0	247	72	72	70	-0.036	3.88	0.030	73	71
228	37.161	36.846	0.16	0.16	1.29	82	2.14	1.06	82	1.4	84	0.053	98	98	3.9	0	246	72	72	70	-0.036	3.18	0.038	73	71
229	37.322	37.007	0.16	0.16	1.29	82	2.14	1.06	82	1.5	84	0.053	97	97	3.8	-0.1	246	72	72	70	-0.037	3.77	0.014	73	71
230	37.483	37.168	0.16	0.16	1.29	82	2.14	1.07	82	1.4	85	0.051	98	99	3.8	0	246	72	72	70	-0.036	3.53	0.014	73	71
231	37.645	37.329	0.16	0.16	1.29	82	2.14	1.07	82	1.4	85	0.051	99	99	3.8	0	246	72	72	70	-0.036	3.53	0.025	73	71
232	37.807	37.491	0.16	0.16	1.29	82	2.15	1.06	82	1.4	85	0.051	99	100	3.8	0	245	72	72	70	-0.036	3.49	0.015	73	71
233	37.969	37.652	0.16	0.16	1.29	82	2.15	1.06	82	1.4	85	0.052	98	98	3.7	-0.1	246	72	72	71	-0.036	4.10	0.014	73	71
234	38.131	37.813	0.16	0.16	1.29	82	2.15	1.07	82	1.5	85	0.051	99	99	3.7	0	247	72	72	70	-0.036	3.67	0.017	73	71
235	38.292	37.974	0.16	0.16	1.28	82	2.15	1.06	82	1.5	85	0.049	100	101	3.7	0	247	72	72	70	-0.036	3.72	0.025	72	71
236	38.454	38.135	0.16	0.16	1.29	82	2.15	1.06	82	1.5	85	0.052	98	98	3.6	-0.1	247	72	72	70	-0.036	3.73	0.015	72	71
237	38.615	38.296	0.16	0.16	1.29	82	2.14	1.06	82	1.5	85	0.050	99	100	3.6	0	248	72	72	70	-0.037	3.90	0.026	72	71
238	38.777	38.457	0.16	0.16	1.29	82	2.14	1.06	82	1.5	85	0.052	98	98	3.6	0	247	72	72	70	-0.036	4.02	0.014	72	71
239	38.940	38.618	0.16	0.16	1.29	82	2.15	1.06	82	1.5	85	0.053	98	97	3.6	0	247	72	72	70	-0.037	3.38	0.022	72	71
240	39.101	38.779	0.16	0.16	1.28	82	2.15	1.06	82	1.5	85	0.052	98	98	3.5	-0.1	247	72	72	70	-0.036	3.38	0.016	72	71
241	39.262	38.939	0.16	0.16	1.29	82	2.15	1.06	82	1.5	85	0.051	98	99	3.5	0	247	72	72	70	-0.037	3.91	0.021	72	71
242	39.423	39.100	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.053	97	97	3.5	0	249	72	72	70	-0.037	4.45	0.009	72	71
243	39.585	39.261	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.049	101	101	3.4	-0.1	248	72	72	70	-0.037	3.53	0.015	72	71
244	39.747	39.421	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.053	97	97	3.4	0	248	72	72	70	-0.037	3.47	0.017	72	71
245	39.909	39.582	0.16	0.16	1.28	82	2.16	1.06	82	1.5	85	0.052	98	98	3.4	0	247	72	72	70	-0.036	3.36	0.018	72	71
246	40.070	39.743	0.16	0.16	1.29	82	2.15	1.06	82	1.5	85	0.052	98	98	3.3	-0.1	247	72	72	70	-0.037	3.39	0.020	72	71
247	40.231	39.904	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.053	97	97	3.3	0	247	72	72	70	-0.037	3.88	0.011	72	71
248	40.392	40.064	0.16	0.16	1.28	82	2.15	1.06	82	1.5	85	0.051	98	99	3.3	0	248	72	72	70	-0.037	3.91	0.014	72	71
249	40.555	40.225	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.051	100	99	3.3	0	248	72	72	70	-0.037	3.71	0.011	72	70
250	40.716	40.385	0.16	0.16	1.28	82	2.16	1.05	82	1.5	85	0.052	98	98	3.2	-0.1	246	72	72	70	-0.036	3.34	0.024	72	71
251	40.877	40.546	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.051	98	99	3.2	0	246	72	72	70	-0.037	3.51	0.017	72	70

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99



Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O °F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H <sub>2</sub> O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H <sub>2</sub> O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (*F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H <sub>2</sub> O)	CO <sub>2</sub> (%)	CO (%)	Drier A	Drier B
252	41.038	40.707	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.051	98	99	3.2	0	246	72	72	70	-0.036	3.45	0.017	72	71
253	41.199	40.867	0.16	0.16	1.29	82	2.16	1.05	82	1.5	85	0.051	98	99	3.2	0	245	72	72	70	-0.036	3.32	0.016	72	70
254	41.362	41.027	0.16	0.16	1.29	82	2.16	1.06	82	1.5	85	0.050	101	100	3.1	-0.1	245	72	72	70	-0.036	3.42	0.014	72	71
255	41.523	41.187	0.16	0.16	1.28	82	2.16	1.06	82	1.5	84	0.052	97	98	3.1	0	244	72	72	70	-0.035	3.05	0.013	72	71
256	41.684	41.348	0.16	0.16	1.28	82	2.17	1.05	82	1.5	85	0.052	98	98	3.1	0	244	72	72	70	-0.037	3.46	0.035	72	70
257	41.845	41.508	0.16	0.16	1.29	82	2.16	1.05	82	1.5	85	0.050	99	100	3.0	-0.1	245	72	72	70	-0.036	3.67	0.010	72	70
258	42.006	41.668	0.16	0.16	1.29	82	2.16	1.06	82	1.5	84	0.052	97	98	3.0	0	244	72	72	70	-0.036	3.08	0.023	72	70
259	42.169	41.829	0.16	0.16	1.28	82	2.16	1.06	82	1.5	84	0.054	97	96	3.0	0	243	72	72	70	-0.036	3.17	0.015	72	70
260	42.330	41.989	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.051	98	99	3.0	0	243	72	72	70	-0.036	3.52	0.020	72	70
261	42.490	42.149	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.055	94	95	2.9	-0.1	244	72	72	70	-0.037	3.65	0.015	72	70
262	42.651	42.310	0.16	0.16	1.29	82	2.17	1.05	82	1.5	84	0.052	97	98	2.9	0	245	72	72	70	-0.036	3.65	0.013	72	70
263	42.813	42.469	0.16	0.16	1.29	82	2.17	1.05	82	1.5	85	0.053	97	96	2.9	0	245	72	72	70	-0.036	3.68	0.019	72	70
264	42.975	42.630	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.053	97	97	2.9	0	245	72	72	70	-0.036	3.38	0.022	72	70
265	43.136	42.790	0.16	0.16	1.27	82	2.17	1.05	82	1.5	84	0.050	99	100	2.8	-0.1	245	72	72	69	-0.036	3.80	0.015	72	70
266	43.296	42.950	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.051	98	99	2.8	0	245	72	72	70	-0.036	3.68	0.013	72	70
267	43.457	43.110	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.051	98	99	2.8	0	246	72	72	70	-0.036	3.82	0.016	72	70
268	43.619	43.271	0.16	0.16	1.28	82	2.18	1.05	82	1.5	84	0.053	97	97	2.7	-0.1	246	72	72	70	-0.037	3.60	0.020	72	70
269	43.780	43.430	0.16	0.16	1.28	82	2.17	1.05	82	1.5	84	0.051	98	98	2.7	0	246	72	72	70	-0.037	3.73	0.008	72	70
270	43.942	43.590	0.16	0.16	1.27	82	2.17	1.05	82	1.5	84	0.053	97	97	2.7	0	247	72	72	70	-0.037	3.93	0.016	72	70
271	44.102	43.751	0.16	0.16	1.27	82	2.18	1.05	82	1.5	84	0.053	96	97	2.7	0	247	72	72	70	-0.037	3.84	0.020	72	70
272	44.263	43.910	0.16	0.16	1.29	82	2.18	1.05	81	1.5	84	0.054	96	95	2.6	-0.1	247	72	72	70	-0.037	3.69	0.014	72	70
273	44.425	44.070	0.16	0.16	1.32	82	2.24	1.08	82	1.5	84	0.052	98	98	2.6	0	247	72	72	70	-0.036	3.91	0.010	72	70
274	44.589	44.232	0.16	0.16	1.32	82	2.24	1.08	81	1.5	84	0.052	99	99	2.6	0	246	72	72	70	-0.036	3.75	0.021	72	70
275	44.753	44.394	0.16	0.16	1.32	82	2.24	1.07	81	1.5	84	0.052	99	99	2.5	-0.1	246	72	72	70	-0.037	3.52	0.018	72	70
276	44.917	44.556	0.16	0.16	1.31	82	2.25	1.08	81	1.5	84	0.054	97	97	2.5	0	245	72	72	70	-0.036	3.49	0.018	72	70
277	45.080	44.718	0.16	0.16	1.31	82	2.25	1.08	81	1.5	84	0.050	101	101	2.5	0	247	72	72	70	-0.037	4.25	0.011	72	70
278	45.243	44.880	0.16	0.16	1.32	82	2.25	1.08	81	1.5	84	0.053	98	98	2.4	-0.1	247	72	72	70	-0.037	4.02	0.009	72	70
279	45.407	45.042	0.16	0.16	1.32	82	2.25	1.08	81	1.5	84	0.051	100	100	2.4	0	248	72	72	70	-0.037	3.90	0.015	72	70
280	45.570	45.203	0.16	0.16	1.32	82	2.25	1.07	81	1.5	84	0.053	98	98	2.4	0	247	72	72	70	-0.037	3.64	0.020	72	70
281	45.734	45.365	0.16	0.16	1.32	82	2.25	1.07	81	1.5	84	0.051	100	100	2.3	-0.1	248	72	72	70	-0.037	4.18	0.010	72	70
282	45.897	45.527	0.16	0.16	1.33	82	2.25	1.07	81	1.5	84	0.052	99	99	2.3	0	248	72	72	70	-0.037	3.74	0.016	72	70
283	46.062	45.689	0.16	0.16	1.32	82	2.25	1.07	81	1.5	84	0.053	99	98	2.3	0	247	72	72	70	-0.037	3.71	0.020	72	70
284	46.225	45.850	0.16	0.16	1.32	82	2.25	1.07	81	1.5	84	0.051	100	99	2.3	0	247	72	72	70	-0.037	3.45	0.018	72	70
285	46.388	46.012	0.16	0.16	1.31	82	2.26	1.07	81	1.5	84	0.051	100	100	2.2	-0.1	246	72	72	70	-0.037	3.40	0.021	72	70
286	46.551	46.174	0.16	0.16	1.32	82	2.26	1.07	81	1.5	84	0.050	101	101	2.2	0	247	72	72	70	-0.037	3.96	0.014	72	70
287	46.715	46.335	0.16	0.16	1.31	82	2.25	1.07	81	1.5	84	0.052	99	98	2.2	0	247	72	72	70	-0.037	3.77	0.014	72	70
288	46.878	46.496	0.16	0.16	1.32	82	2.26	1.07	81	1.5	84	0.051	100	99	2.2	0	247	72	72	70	-0.037	3.84	0.011	72	70
289	47.041	46.657	0.16	0.16	1.32	82	2.26	1.07	81	1.5	84	0.052	99	98	2.1	-0.1	246	72	72	70	-0.037	3.53	0.020	72	70
290	47.204	46.819	0.16	0.16	1.32	82	2.26	1.07	81	1.5	84	0.051	100	100	2.1	0	246	72	72	70	-0.036	3.93	0.015	72	70
291	47.368	46.980	0.16	0.16	1.32	82	2.27	1.07	81	1.5	84	0.051	100	99	2.1	0	247	72	72	70	-0.036	4.03	0.009	72	70
292	47.531	47.141	0.16	0.16	1.31	82	2.27	1.07	81	1.6	84	0.050	101	100	2.0	-0.1	248	72	72	70	-0.037	4.05	0.011	72	70
293	47.695	47.302	0.16	0.16	1.31	82	2.26	1.07	81	1.5	84	0.051	100	99	2.0	0	246	72	72	70	-0.036	3.27	0.027	72	70

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1


Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99

  
 Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F

V<sub>straw</sub> 13.76 ft/sec V<sub>scant</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data											Fuel Weight (lb)				Temperature Data (°F)				Stack Gas Data			Dryer Temps		
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H2O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H2O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H2O)	CO2 (%)	CO (%)	Drier A	Drier B
294	47.857	47.464	0.16	0.16	1.31	82	2.26	1.07	81	1.5	84	0.050	100	101	2.0	0	245	72	72	70	-0.036	3.05	0.016	72	70
295	48.020	47.625	0.16	0.16	1.31	82	2.26	1.07	81	1.6	84	0.052	99	98	2.0	0	244	72	72	70	-0.036	3.40	0.016	72	70
296	48.183	47.786	0.16	0.16	1.31	82	2.27	1.06	81	1.6	84	0.052	99	98	1.9	-0.1	244	72	72	70	-0.036	3.34	0.016	72	70
297	48.346	47.947	0.16	0.16	1.32	82	2.27	1.06	81	1.6	84	0.051	100	99	1.9	0	245	72	72	70	-0.036	4.47	0.006	72	70
298	48.509	48.108	0.16	0.16	1.31	82	2.27	1.06	81	1.6	84	0.054	97	97	1.9	0	246	72	72	70	-0.037	4.21	0.017	72	70
299	48.673	48.268	0.16	0.16	1.31	82	2.27	1.06	81	1.6	84	0.052	99	98	1.8	-0.1	246	72	72	70	-0.036	3.93	0.007	72	70
300	48.836	48.430	0.16	0.16	1.31	82	2.28	1.06	81	1.6	84	0.051	100	100	1.8	0	246	72	72	70	-0.037	4.15	0.008	72	70
301	48.999	48.591	0.16	0.16	1.30	82	2.27	1.06	81	1.6	84	0.049	102	101	1.8	0	246	72	72	70	-0.036	3.41	0.010	72	70
302	49.161	48.751	0.16	0.16	1.30	82	2.27	1.06	81	1.6	84	0.050	100	100	1.7	-0.1	246	72	71	70	-0.037	4.34	0.017	72	70
303	49.324	48.911	0.16	0.16	1.30	82	2.28	1.06	81	1.6	84	0.051	100	99	1.7	0	247	71	71	70	-0.037	4.02	0.013	72	70
304	49.486	49.073	0.16	0.16	1.31	82	2.28	1.06	81	1.6	84	0.051	99	100	1.7	0	247	72	71	70	-0.037	3.75	0.020	72	70
305	49.649	49.233	0.16	0.16	1.31	82	2.28	1.05	81	1.6	84	0.053	98	97	1.6	-0.1	247	72	71	70	-0.037	4.10	0.012	72	70
306	49.813	49.393	0.16	0.16	1.30	82	2.29	1.06	81	1.6	84	0.054	97	96	1.6	0	247	72	71	70	-0.036	3.83	0.026	72	70
307	49.975	49.555	0.16	0.16	1.31	81	2.29	1.06	81	1.6	84	0.052	98	99	1.6	0	246	72	71	70	-0.037	3.51	0.032	72	70
308	50.138	49.715	0.16	0.16	1.30	82	2.28	1.05	81	1.6	84	0.051	100	99	1.6	0	245	71	71	70	-0.037	3.53	0.034	72	70
309	50.300	49.874	0.16	0.16	1.30	81	2.28	1.06	81	1.6	84	0.052	98	97	1.5	-0.1	245	72	71	70	-0.036	3.56	0.013	72	70
310	50.463	50.035	0.16	0.16	1.30	81	2.29	1.06	81	1.6	84	0.049	102	101	1.5	0	244	71	71	70	-0.036	3.36	0.016	72	70
311	50.625	50.196	0.16	0.16	1.31	82	2.29	1.04	81	1.6	84	0.055	95	96	1.5	0	244	71	71	70	-0.036	3.78	0.013	72	70
312	50.788	50.356	0.16	0.16	1.31	81	2.29	1.06	81	1.6	84	0.051	100	99	1.4	-0.1	244	71	71	70	-0.036	3.57	0.012	72	70
313	50.951	50.516	0.16	0.16	1.30	81	2.29	1.05	81	1.6	84	0.050	101	100	1.4	0	244	71	71	70	-0.037	3.40	0.020	72	70
314	51.114	50.677	0.16	0.16	1.30	82	2.29	1.05	81	1.6	84	0.053	98	98	1.4	0	245	71	71	70	-0.036	4.40	0.019	72	70
315	51.276	50.836	0.16	0.16	1.30	81	2.29	1.05	81	1.6	84	0.052	98	97	1.3	-0.1	244	71	71	70	-0.036	3.75	0.020	72	70
316	51.438	50.997	0.16	0.16	1.30	81	2.29	1.06	81	1.6	84	0.051	99	99	1.3	0	244	71	71	70	-0.036	3.18	0.013	72	70
317	51.600	51.157	0.16	0.16	1.30	81	2.29	1.05	81	1.6	84	0.054	96	96	1.3	0	244	71	71	70	-0.036	3.73	0.019	72	70
318	51.763	51.317	0.16	0.16	1.30	81	2.29	1.05	81	1.6	84	0.052	99	98	1.3	0	245	71	71	70	-0.036	3.51	0.019	72	70
319	51.925	51.477	0.16	0.16	1.30	82	2.29	1.05	81	1.6	84	0.050	100	100	1.2	-0.1	244	71	71	70	-0.036	3.41	0.018	72	70
320	52.088	51.637	0.16	0.16	1.30	82	2.29	1.05	81	1.6	84	0.053	98	97	1.2	0	244	71	71	70	-0.037	3.17	0.021	72	70
321	52.251	51.797	0.16	0.16	1.30	82	2.29	1.05	81	1.6	84	0.050	101	100	1.2	0	244	71	71	70	-0.036	3.71	0.011	72	70
322	52.412	51.956	0.16	0.16	1.30	82	2.29	1.05	81	1.6	84	0.051	98	98	1.2	0	244	71	71	70	-0.036	3.52	0.012	72	70
323	52.575	52.117	0.16	0.16	1.30	81	2.3	1.05	81	1.6	84	0.052	99	98	1.1	-0.1	245	71	71	70	-0.036	3.80	0.016	72	70
324	52.737	52.276	0.16	0.16	1.30	81	2.3	1.05	81	1.6	84	0.051	99	98	1.1	0	244	71	71	70	-0.036	3.80	0.016	72	70
325	52.899	52.436	0.16	0.16	1.30	82	2.3	1.05	81	1.6	84	0.051	99	99	1.1	0	245	71	71	70	-0.036	4.15	0.009	72	70
326	53.062	52.596	0.16	0.16	1.30	82	2.31	1.05	81	1.6	84	0.052	99	98	1.0	-0.1	246	71	71	70	-0.037	4.09	0.012	72	70
327	53.224	52.756	0.16	0.16	1.29	82	2.31	1.04	81	1.6	84	0.051	99	99	1.0	0	245	71	71	70	-0.037	3.27	0.024	72	70
328	53.383	52.913	0.16	0.16	1.30	82	2.31	1.05	81	1.6	84	0.053	95	95	1.0	0	245	71	71	70	-0.036	3.86	0.011	72	70
329	53.545	53.072	0.16	0.16	1.30	82	2.3	1.04	81	1.6	84	0.052	98	97	1.0	0	245	71	71	70	-0.037	3.49	0.009	72	70
330	53.707	53.232	0.16	0.16	1.30	81	2.3	1.14	81	1.7	84	0.051	99	99	0.9	-0.1	245	71	71	70	-0.036	3.68	0.008	72	70
331	53.871	53.394	0.16	0.16	1.34	82	2.36	1.08	81	1.6	84	0.051	100	100	0.9	0	245	71	71	70	-0.036	3.65	0.014	72	70
332	54.036	53.557	0.16	0.16	1.33	82	2.36	1.08	81	1.6	84	0.051	101	101	0.9	0	246	71	71	70	-0.037	4.43	0.020	72	70
333	54.201	53.718	0.16	0.16	1.33	82	2.37	1.07	81	1.6	84	0.050	102	100	0.8	-0.1	248	71	71	70	-0.037	4.51	0.014	72	70
334	54.365	53.880	0.16	0.16	1.33	82	2.36	1.08	81	1.6	84	0.051	100	100	0.8	0	249	71	71	70	-0.037	4.26	0.013	72	70
335	54.529	54.042	0.16	0.16	1.32	82	2.36	1.08	81	1.6	84	0.053	98	98	0.8	0	248	71	71	70	-0.037	3.93	0.012	72	70

### Pellet Heater Test Data - ASTM E2779 / ASTM E2515

Run: 1

Manufacturer: HHT Halifax High Burn End Time: 61  
 Model: Absolute 43-C Medium Burn End Time: 181  
 Tracking No.: 2269 Total Sampling Time: 361 min  
 Project No.: 0135PS039E Recording Interval: 1 min  
 Test Date: 21-Feb-18  
 Beginning Clock Time: 07:43 Background Sample Volume: 0 cubic feet

Meter Box Y Factor: 0.977 (1) 0.979 (2) 0 (Amb)

Barometric Pressure: Begin Middle End Average  
30.25 30.26 30.26 30.26 \*Hg

OMNI Equipment Numbers: 132, 185, 209, 335, 336, 410, 494, 559

PM Control Modules: 335/336  
 Dilution Tunnel MW(dry): 29.00 lb/lb-mole  
 Dilution Tunnel MW(wet): 28.78 lb/lb-mole  
 Dilution Tunnel H2O: 2.00 percent  
 Dilution Tunnel Static: -0.160 \*H2O  
 Tunnel Area: 0.19635 ft2  
 Pitot Tube Cp: 0.99

Avg. Tunnel Velocity: 13.56 ft/sec.  
 Initial Tunnel Flow: 148.3 scfm  
 Average Tunnel Flow: 152.0 scfm  
 Post-Test Leak Check (1): 0.000 cfm @ -13 in. Hg  
 Post-Test Leak Check (2): 0.000 cfm @ -12 in. Hg  
 Fuel Moisture: 4.84 Dry Basis %

Velocity Traverse Data									
	Pt.1	Pt.2	Pt.3	Pt.4	Pt.5	Pt.6	Pt.7	Pt.8	Center
Initial dP	0.030	0.048	0.048	0.034	0.036	0.048	0.046	0.030	0.052
Temp:	103	103	103	103	103	103	103	103	103

\*H2O  
\*F

V<sub>straw</sub> 13.76 ft/sec V<sub>scint</sub> 15.45 ft/sec F<sub>p</sub> 0.891

Elapsed Time (min)	Particulate Sampling Data												Fuel Weight (lb)		Temperature Data (°F)				Stack Gas Data			Dryer Temps			
	Gas Meter 1 (ft³)	Gas Meter 2 (ft³)	Sample Rate 1 (cfm)	Sample Rate 2 (cfm)	Orifice dH 1 (*H <sub>2</sub> O)	Meter Temp 1 (°F)	Meter Vacuum 1 (*Hg)	Orifice dH 2 (*H <sub>2</sub> O)	Meter Temp 2 (°F)	Meter Vacuum 2 (*Hg)	Dilution Tunnel (°F)	Dilution Tunnel Center dP	Pro. Rate 1	Pro. Rate 2	Scale Reading	Weight Change	Stack	Filter 1	Filter 2	Ambient	Draft (*H <sub>2</sub> O)	CO <sub>2</sub> (%)	CO (%)	Drier A	Drier B
336	54.693	54.204	0.16	0.16	1.32	82	2.36	1.07	81	1.6	84	0.055	96	96	0.7	-0.1	248	71	71	70	-0.037	3.62	0.013	72	70
337	54.857	54.365	0.16	0.16	1.32	82	2.36	1.07	81	1.6	84	0.051	100	99	0.7	0	247	71	71	70	-0.038	3.90	0.013	72	70
338	55.021	54.527	0.16	0.16	1.33	82	2.36	1.08	81	1.6	84	0.055	96	96	0.7	0	247	71	71	70	-0.037	3.78	0.017	72	70
339	55.184	54.689	0.16	0.16	1.33	82	2.36	1.07	81	1.6	84	0.054	97	97	0.6	-0.1	247	71	71	70	-0.037	3.76	0.013	72	70
340	55.349	54.851	0.16	0.16	1.33	82	2.37	1.07	81	1.6	84	0.052	100	99	0.6	0	248	71	71	70	-0.037	4.22	0.014	72	70
341	55.513	55.012	0.16	0.16	1.33	82	2.37	1.07	81	1.6	84	0.049	102	101	0.6	0	248	71	71	70	-0.037	3.72	0.015	72	70
342	55.677	55.174	0.16	0.16	1.33	82	2.37	1.07	81	1.6	84	0.056	96	96	0.6	0	249	71	71	70	-0.037	4.12	0.009	72	70
343	55.841	55.336	0.16	0.16	1.33	82	2.38	1.07	81	1.6	84	0.050	101	101	0.5	-0.1	248	71	71	70	-0.037	3.49	0.018	72	70
344	56.006	55.498	0.16	0.16	1.33	81	2.37	1.07	81	1.6	84	0.054	98	97	0.5	0	248	71	71	70	-0.037	3.67	0.015	72	70
345	56.170	55.659	0.16	0.16	1.32	82	2.38	1.07	81	1.6	84	0.053	98	98	0.5	0	246	71	71	70	-0.036	3.02	0.021	72	70
346	56.334	55.820	0.16	0.16	1.32	82	2.38	1.07	81	1.6	84	0.053	98	98	0.5	0	244	71	71	70	-0.036	2.94	0.012	72	70
347	56.498	55.982	0.16	0.16	1.32	81	2.37	1.07	81	1.6	84	0.050	101	101	0.4	-0.1	243	71	71	70	-0.036	3.07	0.022	72	70
348	56.661	56.144	0.16	0.16	1.32	82	2.38	1.07	81	1.6	84	0.050	101	101	0.4	0	244	71	71	70	-0.037	3.93	0.015	72	70
349	56.825	56.305	0.16	0.16	1.32	82	2.38	1.07	81	1.7	84	0.054	97	97	0.4	0	245	71	71	70	-0.037	3.93	0.012	72	70
350	56.989	56.466	0.16	0.16	1.32	82	2.37	1.07	81	1.6	84	0.052	99	98	0.3	-0.1	245	71	71	70	-0.037	3.58	0.019	72	70
351	57.152	56.628	0.16	0.16	1.33	82	2.38	1.07	81	1.6	84	0.052	99	99	0.3	0	244	71	71	70	-0.036	3.77	0.021	72	70
352	57.316	56.789	0.16	0.16	1.32	82	2.38	1.06	81	1.7	84	0.050	101	100	0.3	0	246	71	71	70	-0.038	4.08	0.008	72	70
353	57.480	56.949	0.16	0.16	1.33	82	2.38	1.07	81	1.7	84	0.050	101	100	0.2	-0.1	247	71	71	70	-0.037	4.71	0.014	72	70
354	57.644	57.111	0.16	0.16	1.32	82	2.39	1.07	81	1.7	84	0.052	99	99	0.2	0	249	71	71	70	-0.037	4.73	0.022	72	70
355	57.808	57.272	0.16	0.16	1.32	82	2.38	1.07	81	1.7	84	0.051	100	99	0.2	0	250	71	71	70	-0.037	4.45	0.009	72	70
356	57.971	57.433	0.16	0.16	1.32	82	2.39	1.07	81	1.7	84	0.053	98	98	0.1	-0.1	250	71	71	70	-0.037	3.95	0.018	72	70
357	58.136	57.596	0.17	0.16	1.32	82	2.39	1.06	81	1.7	84	0.053	99	99	0.1	0	249	71	71	70	-0.037	4.00	0.013	72	70
358	58.298	57.756	0.16	0.16	1.32	82	2.39	1.06	81	1.7	84	0.052	98	98	0.1	0	250	71	71	70	-0.038	3.86	0.010	72	70
359	58.462	57.917	0.16	0.16	1.32	82	2.39	1.05	81	1.7	84	0.051	100	99	0.1	0	250	71	71	70	-0.039	3.91	0.011	72	70
360	58.625	58.077	0.16	0.16	1.32	81	2.4	1.06	81	1.7	84	0.053	98	97	0.0	-0.1	250	71	71	70	-0.037	3.87	0.021	72	70
361	58.789	58.238	0.16	0.16	1.32	81	2.4	1.06	81	1.7	84	0.052	99	98	0.0	0	250	71	71	70	-0.038	4.07	0.012	72	70
Avg/Tot	58.789	58.238	0.16	0.16	1.31	81	2.13	1.07	81	1.39	89	0.05	100	100			291	73	72	70	-0.042	5.28	0.02	77	76

## Pellet Heater Test Results - ASTM E2779 / ASTM E2515

Manufacturer: HHT Halifax  
 Model: Absolute 43-C  
 Project No.: 0135PS039E  
 Tracking No.: 2269  
 Run: 1  
 Test Date: 02/21/18

Burn Rate (Composite)	<b>1.09 kg/hr dry</b>
Average Tunnel Temperature	89 degrees F
Average Gas Velocity in Dilution Tunnel - vs	13.56 feet/second
Average Gas Flow Rate in Dilution Tunnel - Qsd	9120.6 dscf/hour
Average Delta p	0.051 inches H2O
Average Delta H	1.31 inches H2O
Total Time of Test	361 minutes

<b>Burn Rate (High)</b>	<b>2.30 kg/hr dry</b>
<b>Burn Rate (Med)</b>	<b>1.00 kg/hr dry</b> 43.3% of High
<b>Burn Rate (Low)</b>	<b>0.74 kg/hr dry</b> 32.0% of High

	AMBIENT	SAMPLE TRAIN 1	SAMPLE TRAIN 2	1 <sup>st</sup> HR FILTER (TRAIN 1)
Total Sample Volume - Vm	0.000 cubic feet	58.789 cubic feet	58.238 cubic feet	9.766 cubic feet
Average Gas Meter Temperature	70 degrees F	81 degrees F	81 degrees F	76 degrees F
Total Sample Volume (Standard Conditions) - Vmstd	0.000 dscf	56.855 dscf	56.425 dscf	9.525 dscf
Total Particulates - m <sub>n</sub>	0 mg	6 mg	6.3 mg	1.5 mg
Particulate Concentration (dry-standard) - C <sub>i</sub> /C <sub>s</sub>	0.000000 grams/dscf	0.00011 grams/dscf	0.00011 grams/dscf	0.00016 grams/dscf
Total Particulate Emissions - E <sub>T</sub>	0.00 grams	5.79 grams	6.13 grams	1.44 grams
Particulate Emission Rate	0.00 grams/hour	0.96 grams/hour	1.02 grams/hour	1.44 grams/hour
Emissions Factor		0.89 g/kg	0.94 g/kg	0.63 g/kg
Difference from Average Total Particulate Emissions		0.17 grams	0.17 grams	
<b>Dual Train Comparison Results Are Acceptable</b>				

### FINAL AVERAGE RESULTS

<b>Integrated Test Run</b>	
Total Particulate Emissions - E <sub>T</sub>	5.96 grams
Particulate Emission Rate	<b>0.99 grams/hour</b>
Emissions Factor	0.91 grams/kg
<b>First Hour Emissions</b>	
Total Particulate Emissions - E <sub>T</sub>	1.44 grams
Particulate Emission Rate	1.44 grams/hour
Emissions Factor	0.63 grams/kg


### QUALITY CHECKS

<b>Filter Temps &lt; 90 °F</b>	OK
<b>Filter Face Velocity (47 mm)</b>	OK
<b>Leakage Rate</b>	OK
<b>Ambient Temp (55-90°F)</b>	OK
<b>Negative Probe Weight Eval.</b>	OK
<b>Pro-Rate Variation</b>	OK
<b>Medium Burn Rate &lt; 50%</b>	OK
<b>Train Precision 7.5%</b>	2.82
<b>Train Precision 0.5g/kg</b>	0.06

# OMNI-Test Laboratories

**Manufacturer:** HHT Halifax  
**Model:** Absolute 43-C  
**Date:** 02/21/18  
**Run:** 1  
**Control #:** 0135PS039E  
**Test Duration:** 361  
**Output Category:** Integrated

**Technicians:** Aaron Kravitz



**Test Results in Accordance with CSA B415.1-09**

	HHV Basis	LHV Basis
Overall Efficiency	77.0%	82.3%
Combustion Efficiency	99.5%	99.5%
Heat Transfer Efficiency	77%	82.8%

Output Rate (kJ/h)	16,951	16,080	(Btu/h)
Burn Rate (kg/h)	1.09	2.39	(lb/h)
Input (kJ/h)	22,007	20,876	(Btu/h)

Test Load Weight (dry kg)	6.53	14.40	dry lb
MC wet (%)	4.62		
MC dry (%)	4.84		
Particulate (g)	5.96		
CO (g)	35		
Test Duration (h)	6.02		

Emissions	Particulate	CO
g/MJ Output	0.06	0.34
g/kg Dry Fuel	0.91	5.33
g/h	0.99	5.79
lb/MM Btu Output	0.14	0.79

Air/Fuel Ratio (A/F)	23.09
----------------------	-------

VERSION:


2.2

12/14/2009

# OMNI-Test Laboratories

**Manufacturer:** HHT Halifax  
**Model:** Absolute 43-C  
**Date:** 02/21/18  
**Run:** 1  
**Control #:** 0135PS039E  
**Test Duration:** 61  
**Output Category:** Maximum

**Technicians:** Aaron Kravitz



## Test Results in Accordance with CSA B415.1-09

	HHV Basis	LHV Basis
Overall Efficiency	79.2%	84.6%
Combustion Efficiency	99.5%	99.5%
Heat Transfer Efficiency	80%	85.1%

Output Rate (kJ/h)	36,872	34,977	(Btu/h)
Burn Rate (kg/h)	2.30	5.07	(lb/h)
Input (kJ/h)	46,576	44,183	(Btu/h)

Test Load Weight (dry kg)	2.34	5.15	dry lb
MC wet (%)	4.62		
MC dry (%)	4.84		
Particulate (g)	0		
CO (g)	13		
Test Duration (h)	1.02		

Emissions	Particulate	CO
g/MJ Output	0.00	0.36
g/kg Dry Fuel	0.00	5.73
g/h	0.00	13.16
lb/MM Btu Output	0.00	0.83

Air/Fuel Ratio (A/F)	12.00
----------------------	-------

VERSION:

2.2

12/14/2009

# OMNI-Test Laboratories

**Manufacturer:** HHT Halifax  
**Model:** Absolute 43-C  
**Date:** 02/21/18  
**Run:** 1  
**Control #:** 0135PS039E  
**Test Duration:** 120  
**Output Category:** Medium

**Technicians:** Aaron Kravitz



**Test Results in Accordance with CSA B415.1-09**

	HHV Basis	LHV Basis
Overall Efficiency	76.5%	81.8%
Combustion Efficiency	99.5%	99.5%
Heat Transfer Efficiency	77%	82.2%

Output Rate (kJ/h)	15,436	14,642	(Btu/h)
Burn Rate (kg/h)	1.00	2.19	(lb/h)
Input (kJ/h)	20,169	19,132	(Btu/h)

Test Load Weight (dry kg)	1.99	4.39	dry lb
MC wet (%)	4.62		
MC dry (%)	4.84		
Particulate (g)	0		
CO (g)	9		
Test Duration (h)	2.00		

Emissions	Particulate	CO
g/MJ Output	0.00	0.30
g/kg Dry Fuel	0.00	4.64
g/h	0.00	4.62
lb/MM Btu Output	0.00	0.70

Air/Fuel Ratio (A/F)	23.25
----------------------	-------

VERSION:

2.2


12/14/2009



# OMNI-Test Laboratories

**Manufacturer:** HHT Halifax  
**Model:** Absolute 43-C  
**Date:** 02/21/18  
**Run:** 1  
**Control #:** 0135PS039E  
**Test Duration:** 180  
**Output Category:** Minimum

**Technicians:** Aaron Kravitz


---

**Test Results in Accordance with CSA B415.1-09**

	HHV Basis	LHV Basis
Overall Efficiency	74.9%	80.1%
Combustion Efficiency	99.5%	99.5%
Heat Transfer Efficiency	75%	80.5%

Output Rate (kJ/h)	11,163	10,589	(Btu/h)
Burn Rate (kg/h)	0.74	1.62	(lb/h)
Input (kJ/h)	14,907	14,141	(Btu/h)

Test Load Weight (dry kg)	2.21	4.86	dry lb
MC wet (%)	4.62		
MC dry (%)	4.84		
Particulate (g)	0		
CO (g)	12		
Test Duration (h)	3.00		

Emissions	Particulate	CO
g/MJ Output	0.00	0.37
g/kg Dry Fuel	0.00	5.62
g/h	0.00	4.13
lb/MM Btu Output	0.00	0.86

Air/Fuel Ratio (A/F)	33.30
----------------------	-------

VERSION:

2.2

12/14/2009

## **2.2 - Sample Analysis & Tares**

Analysis Worksheets  
Tared Filter, Probe, and O-Ring Data  
Pellet Fuel Label  
Pellet Fuel Analysis Report

### Pellet Heater Certification Run Sheets

Client: HHT Halifax Project Number: 6135 PS039E Run Number: 1  
 Model: Absolute 43°C Tracking Number: 2269 Date: 2/20/18  
 Test Crew: A. Kravitz  
 OMNI Equipment ID numbers: 637, 592, 283A

#### ASTM E2515 Lab Sheet

Assembled By:

A. Kravitz


Date/Time in Dessicator:

2/21/18

Weighing #1	Weighing #2	Weighing #3	Weighing #4	Weighing #5
Date: <u>2/24/18</u>	Date: <u>2/27/18</u>	Date:	Date:	Date:
Time: <u>13:00</u>	Time: <u>13:00</u>	Time:	Time:	Time:
R/H %: <u>12.4</u>	R/H %: <u>10.2</u>	R/H %:	R/H %:	R/H %:
Temp (F): <u>71.7</u>	Temp (F): <u>71.9</u>	Temp (F):	Temp (F):	Temp (F):
Audit 1: <u>199.9</u>	Audit 1: <u>199.9</u>	Audit 1:	Audit 1:	Audit 1:
Audit 2: <u>199.8</u>	Audit 2: <u>199.9</u>	Audit 2:	Audit 2:	Audit 2:
Audit 3: <u>9997.9</u>	Audit 3: <u>9997.8</u>	Audit 3:	Audit 3:	Audit 3:
Initials: <u>A</u>	Initials: <u>A</u>	Initials:	Initials:	Initials:

Train	Item	ID #	Tare (mg)	Weight (mg)	Weight (mg)	Weight (mg)	Weight (mg)	Weight (mg)
A	Front Filter (60 min)	<u>0391</u>	<u>110.6</u>	<u>112.1</u>	<u>112.1</u>			
A	Front Filter (Remainder)	<u>0417</u>	<u>237.7</u>	<u>241.3</u>	<u>241.1</u>			
A	Rear Filter	<u>0418</u> ↗	-	-	-			
A	Probe	<u>2</u>	<u>115014.5</u>	<u>115014.4</u>	<u>115014.5</u>			
A	O-Ring Set	<u>R573</u>	<u>4136.6</u>	<u>4137.9</u>	<u>4132.7</u> <del>4137.8</del>			
B	Front Filter	<u>D414</u>	<u>237.9</u>	<u>243.8</u>	<u>243.6</u> <del>243.6</del>			
B	Rear Filter	<u>D420</u> ↗	-	-	-			
B	Probe	<u>3</u>	<u>116008.6</u>	<u>116008.5</u>	<u>116008.6</u>			
B	O-Ring Set	<u>R576</u>	<u>3367.5</u>	<u>3368.3</u>	<u>3368.1</u>			
BG	Filter							

Technician Signature: \_\_\_\_\_



Date: \_\_\_\_\_

2/27/17

## Pellet Heater Lab Data - ASTM E2779 / ASTM E2515

Manufacturer: HHT Halifax                      Equipment Numbers: 632, 283A, 592  
 Model: Absolute 43-C  
 Tracking No.: 2269  
 Project No.: 0135PS039E  
 Run #: 1  
 Date: 2/21/18



**TRAIN 1 (First Hour emissions)**

Sample Component	Reagent	Filter, Probe or Dish #	Weights		
			Final, mg	Tare, mg	Particulate, mg
A. Front filter catch	Filter	D391	112.1	110.6	1.5
B. Rear filter catch	Filter				0.0
C. Probe catch*	Probe				0.0
D. Filter seals catch*	Seals				0.0

Sub-Total 

Total Particulate, mg:	1.5
------------------------	-----

**TRAIN 1 (Remainder of Test)**

Sample Component	Reagent	Filter, Probe or Dish #	Weights		
			Final, mg	Tare, mg	Particulate, mg
A. Front filter catch	Filter	D417	241.1	237.7	3.4
B. Rear filter catch	Filter	D418			0.0
C. Probe catch*	Probe	2	115014.5	115014.5	0.0
D. Filter seals catch*	Seals	R573	4137.7	4136.6	1.1

Sub-Total 

Total Particulate, mg:	4.5
------------------------	-----

Train 1 Aggregate 

Total Particulate, mg:	6.0
------------------------	-----

**TRAIN 2**

Sample Component	Reagent	Filter, Probe or Dish #	Weights		
			Final, mg	Tare, mg	Particulate, mg
A. Front filter catch	Filter	D419	243.6	237.9	5.7
B. Rear filter catch	Filter	D420			0.0
C. Probe catch*	Probe	3	116008.6	116008.6	0.0
D. Filter seals catch*	Seals	R576	3368.1	3367.5	0.6

Total Particulate, mg:	6.3
------------------------	-----

**AMBIENT**

Sample Component	Reagent	Filter # or Probe #	Weights		
			Final, mg	Tare, mg	Particulate, mg
A. Front filter catch*	Filter				0.0

Total Particulate, mg:	0.0
------------------------	-----

\*Particulate catch that results in a negative number, is assumed to be zero for probes and seals, negative numbers for filters are assumed to be part of the seal

Component	Equations:
A. Front filter catch	Final (mg) - Tare (mg) = Particulate, mg
B. Rear filter catch	Final (mg) - Tare (mg) = Particulate, mg
C. Probe catch	Final (mg) - Tare (mg) = Particulate, mg





Tare Sheet: Probes \_\_\_ 47mm Filters  100mm Filters \_\_\_ O-Ring Pair \_\_\_

Date/time Placed in Dessicator: 1/4/18 1410

Thermohyrometer ID #: OMNI-00592

Prepared By: B Davis

Analytical Balance ID #: OMNI-00637

Audit Weight ID #/Mass: OMNI-00283A / 200 mg

ID #	Date: 1/5/18 Time: 1425 RH %: 19.8 T (°F): 71.2 Audit: 0.2001	Date: 1/8/18 Time: 10:20 RH %: 14.6 T (°F): 74.4 Audit: 0.2000	Date: 1/9/18 Time: 0820 RH %: 8.6 T (°F): 77 Audit: 0.2000	Date: Time: RH %: T (°F): Audit:	Date Used	Project Number	Run No.
D391	110.4	119.6			2/20/18		1

Initials: Bd Initials: Bd Initials: Bd Initials: \_\_\_\_\_

Final Technician Signature: [Signature]  
Control No. P-SFDP-0001.xls, Effective date: 9/9/2015

Date: 1/10/18  
39 of 133

Evaluator signature: [Signature]

Tare Sheet: (check one)

Probes \_\_\_\_\_

47mm Filters \_\_\_\_\_

100mm Filters \_\_\_\_\_

O-Ring Pair

Prepared By:

Balance ID #:

Thermohygrometer ID #:

Audit Weight ID #/Mass: /

Placed in Dessicator: Date: <u>2/13/18</u> Time: <u>1130</u>	Date: <u>4/12/18</u> Time: <u>13:00</u> RH %: <u>8.0</u> T (°F): <u>71.7</u> Audit: <u>1999.7</u>	Date: <u>2/20/18</u> Time: <u>0600</u> RH %: <u>6.9</u> T (°F): <u>68.1</u> Audit: <u>1999.8</u>	Date: <u>3/14/18</u> Time: <u>1430</u> RH %: <u>7.7</u> T (°F): <u>73.4</u> Audit: <u>1999.8</u>	Date: _____ Time: _____ RH %: _____ T (°F): _____ Audit: _____	Date Used	Project Number	Run No.
<u>R573</u>	<u>4136.4</u>	<u>4136.6</u>	<u>-</u>	<input checked="" type="checkbox"/>	<u>2/20/18</u>	<u>0135PS039E</u>	<u>1</u>
<u>R576</u>	<u>3867.3</u>	<u>3867.5</u>	<u>-</u>	<input checked="" type="checkbox"/>	<u>2/20/18</u>	<u>0135PS039C</u>	<u>1</u>

Initials: A Initials: A Initials: A Initials: \_\_\_\_\_

Final Technician Signature: [Signature]  
Control No. P-SFDP-0002.xls, Effective date: 2/1/2017

Date: 3/14/18

Evaluator signature: [Signature]







Twin Ports Testing, Inc.  
 1301 North 3rd Street  
 Superior, WI 54880  
 p: 715-392-7114  
 p: 800-373-2562  
 f: 715-392-7163  
 www.twinportstesting.com

**Report No:** USR:W218-0204-01  
**Issue No:** 1

# Analytical Test Report

**Client:** OMNI-TEST LABORATORIES INC.  
 13327 NE Airport Way  
 Portland, OR 97230  
**Attention:** Finance Department  
**PO No:** 180166

Signed: *Stephen Sundeen*  
 Stephen Sundeen  
 Chemistry Laboratory Manager  
 Date of Issue: 3/6/2018  
THIS DOCUMENT SHALL NOT BE REPRODUCED EXCEPT IN FULL

**Sample Details**  
**Sample Log No:** W218-0204-01      **Sample Date:**  
**Sample Designation:** 04415-2018      **Sample Time:**  
**Sample Recognized As:** Wood Pellets      **Arrival Date:** 2/28/2018

## Test Results

	METHOD	UNITS	MOISTURE FREE	AS RECEIVED
Moisture Total	ASTM E871	wt. %		4.62
Ash	ASTM D1102	wt. %	0.50	0.47
Volatile Matter	ASTM D3175	wt. %		
Fixed Carbon by Difference	ASTM D3172	wt. %		
Sulfur	ASTM D4239	wt. %	0.009	0.008
SO <sub>2</sub>	Calculated	lb/mmbtu		0.020
Net Cal. Value at Const. Pressure	ISO 1928	GJ/tonne	18.94	17.95
Net Cal. Value at Const. Pressure	ISO 1928	J/g	18940	17953
Gross Cal. Value at Const. Vol.	ASTM E711	J/g	20263	19327
Gross Cal. Value at Const. Vol.	ASTM E711	Btu/lb	8712	8309

Carbon	ASTM D5373	wt. %	50.40	48.07
Hydrogen*	ASTM D5373	wt. %	6.07	5.79
Nitrogen	ASTM D5373	wt. %	< 0.20	< 0.19
Oxygen*	ASTM D3176	wt. %	> 42.82	> 40.84

\*Note: As received values do not include hydrogen and oxygen in the total moisture.

Chlorine	ASTM D6721	mg/kg		
Fluorine	ASTM D3761	mg/kg		
Mercury	ASTM D6722	mg/kg		

Bulk Density	ASTM E873	lbs/ft <sup>3</sup>		
Fines (Less than 1/8")	TPT CH-P-06	wt. %		
Durability Index	Kansas State	PDI		
Sample Above 1.50"	TPT CH-P-06	wt. %		
Maximum Length (Single Pellet)	TPT CH-P-06	inch		
Diameter, Range	TPT CH-P-05	inch		to
Diameter, Average	TPT CH-P-05	inch		
Stated Bag Weight	TPT CH-P-01	lbs		
Actual Bag Weight	TPT CH-P-01	lbs		

**Comments**



PFI Densified Fuel Grade: Premium  
Mill Registration # 03434

Grade Requirements:

Bulk Density:	40-46 lbs/ft <sup>3</sup>
Diameter:	230-285 in/5.84-7.25 mm
Durability:	≥98.5
Fines:	≤0.50%
Ash Content (as received):	≤1%
Length:	≤1.5 in.
Moisture:	≤8.0%
Chloride:	≤300 ppm

Manufacturers Guaranteed Analysis:

Type of Material:	Hardwood/Softwood Blend
Additives:	None
Minimum Higher Heating Value (as received):	8000 BTU/lb.
Other Manufacturers Guarantees:	



For more information, please visit the PFI website at [www.pfiwest.com](http://www.pfiwest.com)

LIGNETICS OF WEST VIRGINIA, INC.  
GLENNVILLE, WV  
26035

Lignetics® Fuel  
designed to be  
responsible for  
improper burn

California  
W

Handling and combust  
exposure to carbon diox  
chemicals known to the S  
and birth defects or other

NET WT. 40

U.S. Patent N

USE OF THIS AND OTHER  
RESTRICTED AT THE  
Please check 1-877-4NO-BURN  
<http://www.8774noburn.com>

LIGNETICS OF IDAHO  
SANDPOINT, ID  
83263-4

# **Section 3**

## **Laboratory Quality Assurance**

- 3.1 - Quality Assurance/Quality Control
- 3.2 - Calibration Data
- 3.3 - Example Calculations

### 3.1 - Quality Assurance/Quality Control

*OMNI* follows the guidelines of ISO/IEC 17025, “General Requirements for the Competence of Testing and Calibration Laboratories,” and the quality assurance/quality control (QA/QC) procedures found in *OMNI*'s Quality Assurance Manual.

*OMNI*'s scope of accreditation includes, but is not limited to, the following:

- ANSI (American National Standards Institute) for certification of product to safety standards.
- To perform product safety testing by the International Accreditation Service, Inc. (formerly ICBO ES) under accreditation as a testing laboratory designated TL-130.
- To perform product safety testing as a “Certification Organization” by the Standards Council of Canada (SCC).
- Serving as a testing laboratory for the certification of wood heaters by the U.S. Environmental Protection Agency.

This report is issued within the scope of *OMNI*'s accreditation. Accreditation certificates are available upon request.

The manufacturing facilities and quality control system for the production of the Absolute43-C at Hearth & Home Technologies, Inc. were evaluated to determine if sufficient to maintain conformance with *OMNI*'s requirements for product certification. *OMNI* has concluded that the manufacturing facilities, processes, and quality control system are adequate to produce the appliance congruous with the standards and model codes to which it was evaluated.

This report shall not be reproduced, except in full, without the written approval of *OMNI*-Test Laboratories, Inc.

## 3.2 - Calibration Data

Equipment for ASTM E2515, ASTM E2779, & EPA Method 28R

<b>ID #</b>	<b>Lab Name/Purpose</b>	<b>Log Name</b>	<b>Attachment Type</b>
132	10 lb Weight	Weight Standard, 10 lb.	Calibration Certificate
185	Platform Scale	Weight Indicator, Model WI-127	Calibration Certificate
209	Barometer	Barometer – Princo	Equipment Record
283A	Audit Weights	Troemner 21pc Msas Set	Calibration Certificate
335	Sample Box / Dry Gas Meter	Apex Automated Emissions Sampling Box	Calibration Log
336	Sample Box / Dry Gas Meter	Apex Automated Emissions Sampling Box	Calibration Log
410	Microtector	Dwyer Microtector	Calibration Certificate
559	Vaneometer	Dwyer Vaneometer	Equipment Record
592	Thermohygrometer	Omega Digital Thermohygrometer	Calibration Log
594	Combustion Gas Analyzer	CAI Gas Analyzer	See Run Sheet
637	Milligram Balance	Analytical Balance - Mettler - Toledo	Calibration Certificate

# SCALE WEIGHT CALIBRATION DATA SHEET

Weight to be calibrated: 132

ID Number: 132

Standard Calibration Weight: 274

ID Number: 274

Scale Used: 785 K 288

ID Number: 785 K 288

Date: 2-07-08

By: K. Morgan

Standard Weight (A) (Lb.)	Weight Verified (B) (Lb.)	Difference (A - B)	% Error
10.0	10.0	0	0

\*Acceptable tolerance is 1%.

*This calibration is traceable to NIST using calibrated standard weights.*

Technician signature: K. Morgan Date: 2-07-08

## SCALE WEIGHT CALIBRATION DATA SHEET

Weight to be calibrated: 10 pounds

ID Number: OMNI-00132

Standard Calibration Weight: 10 pounds

ID Number: OMNI-00255

Scale Used: MTW-150K

ID Number: OMNI-00353

Date: 2/23/2018 By: B. Davis

Standard Weight (A) (Lb.)	Weight Verified (B) (Lb.)	Difference (A - B)	% Error
10.0	10.0	0.0	0

\*Acceptable tolerance is 1%.

*This calibration is traceable to NIST using calibrated standard weights.*

Technician signature:  Date: 2/23/18





# QUALITY CONTROL SERVICES

LABORATORY EQUIPMENT • SALES • SERVICE • CALIBRATION • REPAIRS  
2340 SE 11<sup>TH</sup> Ave. Portland, Oregon 97214 • Box 14831 Portland, Oregon 97293  
(503) 236-2712 • FAX (503) 235-2535 • www.qc-services.com



OMNI-Test Laboratories, Inc.  
13327 NE Airport Way  
Portland, OR 97230

Report Number: OMNE0321676171004

## A2LA ACCREDITED CERTIFICATE OF CALIBRATION WITH DATA

### INSTRUMENT INFORMATION

Item	Make	Model	Serial Number	Customer ID	Location
Scale	Weigh-Tronix	WI-127 1000x0.1lb	21676	185	Lab
Units	Readability	SOP	Cal Date	Last Cal Date	Cal Due Date
lbs	0.1	QC033	10/4/17	10/11/16	10/2018

### FUNCTIONAL CHECKS

SHIFT TEST		LINEARITY		REPEATABILITY		ENVIRONMENTAL CONDITIONS
Test Wt:	Tol:	Test Wt:	Tol:	Test Wt:	Tol:	<input type="checkbox"/> Good <input checked="" type="checkbox"/> Fair <input type="checkbox"/> Poor  Temperature: 21.0°C
500	0.5	HB44	HB44	200	0.2	
As-Found:		As-Found:		As-Found:		
Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	
As-Left:		As-Left:		As-Left:		
Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	Pass: <input checked="" type="checkbox"/>	Fail: <input type="checkbox"/>	

### CALIBRATION DATA

Standard	As-Found	As-Left	Expanded Uncertainty
1000	1000.0	1000.0	0.12
700	700.0	700.0	0.12
500	500.0	500.0	0.08
200	200.0	200.0	0.08
100	100.0	100.0	0.05
50	50.0	50.0	0.05

### CALIBRATION STANDARDS

Item	Make	Model	Serial Number	Cal Date	Cal Due Date	NIST ID
Avoirdupois Cast W	Rice Lake	25 and 50lb	PWO990-CA	11/4/15	11/2017	20152112

Permanent Information Concerning this Equipment:

Comments/Information Concerning this Calibration

Report prepared/reviewed by: ①

Date: 10-4-17

Technician: D. Oudeans

Signature: [Signature]

THIS CERTIFICATE SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE APPROVAL OF QUALITY CONTROL SERVICES, INC.

The uncertainty is calculated according to the ISO Guide to the Expression of Uncertainty in Measurement and includes the uncertainty of standards used combined with the observed standard deviation of the unit under test. The uncertainty is expanded with a k factor of 2 for an approximate 95% level of confidence. Instruments listed above were calibrated using standards traceable to the National Institute of Standards and Technology (NIST). Calibration data reflect results at the time and location of calibration. Calibration data should be reviewed to insure that the instrument is performing to its required accuracy.

OMNI 00209

# Instruction Booklet

for use with

# PRINCO

Fortin type mercurial

## Barometers

*Manufactured by*

**PRINCO INSTRUMENTS, INC.**

1020 Industrial Blvd.

Southampton, Pa. 18966-4095


U.S.A.

Phone: 215 355-1500

Fax: 215 355-7766



453  
National  
Weather  
Service  
Type



463  
NOVA™  
Economy  
Model



# Thermal Metering System Calibration Y Factor

Manufacturer: APEX  
 Model: XC-60-EP  
 Serial Number: 606001  
 OMNI Tracking No.: OMNI-00335  
 Calibrated Orifice:  Yes

Date	7/18/2017	Acceptable Deviation (5%)	Deviation
y Factor	0.981	0.04905	0.004
Acceptance	<b>Acceptable</b>		

<b>Average Gas Meter y Factor</b>
<b>0.977</b>

<b>Orifice Meter dH@</b>
<b>N/A</b>

Calibration Date: 01/17/18  
 Calibrated by: B. Davis  
 Calibration Frequency: Six months  
 Next Calibration Due: 7/18/2018  
 Instrument Range: 1.000 cfm  
 Standard Temp.: 68 oF  
 Standard Press.: 29.92 "Hg  
 Barometric Press., Pb: 29.94 "Hg  
 Signature/Date: *B. Davis* 1/18/2018

Acceptable y Deviation	0.020
Maximum y Deviation	0.005
Acceptable dH@ Deviation	N/A
Maximum dH@ Deviation	N/A
Acceptance	<b>Acceptable</b>

Reference Standard *		
Standard	Model	Standard Test Meter
Calibrator	S/N	<u>OMNI-00001</u>
	Calib. Date	<u>30-Oct-17</u>
	Calib. Value	<u>0.9977</u> y factor (ref)

1/19/2018

Calibration Parameters	Run 1	Run 2	Run 3
Reference Meter Pressure ("H2O), Pr	0.00	0.00	0.00
DGM Pressure ("H2O), Pd	2.30	1.38	1.00
Initial Reference Meter	198.1	203.7	214.2
Final Reference Meter	203.602	208.8	222.5
Initial DGM	0	0	0
Final DGM	5.65	5.298	8.67
Temp. Ref. Meter (°F), Tr	68.1	68.1	68.0
Temperature DGM (°F), Td	77.0	78.0	80.0
Time (min)	26.5	31.8	43.5
Net Volume Ref. Meter, Vr	5.502	5.100	8.300
Net Volume DGM, Vd	5.65	5.298	8.67
<b>Gas Meter y Factor =</b>	<b>0.982</b>	<b>0.975</b>	<b>0.974</b>
<b>Gas Meter y Factor Deviation (from avg.)</b>	0.005	0.002	0.003
<b>Orifice dH@</b>	N/A	N/A	N/A
<b>Orifice dH@ Deviation (from avg.)</b>	N/A	N/A	N/A

where:

1. Deviation = |Average value for all runs - current run value|
- \*\* 2.  $y = [Vr \times (y \text{ factor (ref)}) \times (Pb + (Pr / 13.6)) \times (Td + 460)] / [Vd \times (Pb + (Pd / 13.6)) \times (Tr + 460)]$
- \*\* 3.  $dH@ = 0.0317 \times Pd / (Pb (Td + 460)) \times [(Tr + 460) \times \text{time}] / Vr]^2$

\* Reference calibration is traceable to NIST through NIST Test # 40674, Kimble ASTM E1272, or NIST traceable laboratory

\*\* Equations come from EPA Method 5

The uncertainty of measurement is  $\pm 0.14 \text{ ft}^3/\text{min}$ . This is based on the reference standard having a TAR (Test Accuracy Ratio) of at least 4:1.

## DIFFERENTIAL PRESSURE GAUGE CALIBRATION DATA SHEET

Instrument to be calibrated: Pressure Transducer

Maximum Range: 0-2" WC ID Number: OMNI-00335

Calibration Instrument: Digital Manometer ID Number: OMNI-00395

Date: 1/17/2018 By: B. Davis

**This form is to be used only in conjunction with Standard Procedure C-SPC.**

Range of Calibration Point ("WC)	Digital Manometer Input ("WC)	Pressure Gauge Response ("WC)	Difference (Input - Response)	% Error of Full Span*
0-20% Max. Range 0 - 0.4	0.08	0.067	0.013	0.65
20-40% Max. Range 0.4 - 0.8	0.64	0.638	0.002	0.10
40-60% Max. Range 0.8 - 1.2	1.00	1.012	0.012	0.60
60-80% Max. Range 1.2 - 1.6	1.40	1.432	0.032	1.6
80-100% Max. Range 1.6 - 2.0	1.85	1.895	0.045	2.25

\*Acceptable tolerance is 4%.

The uncertainty of measurement is  $\pm 0.4$ " WC. This is based on the reference standard having a TAR (Test Accuracy Ratio) of at least 4:1.

Technician signature:  Date: 1/18/2018

Reviewed by:  Date: 1/19/2018

Temperature Calibration EPA Method 28R, ASTM 2515							
BOOTH:		TEMPERATURE MONITOR TYPE:			EQUIPMENT NUMBER:		
E1		National Instruments Logger			00335, 00336		
REFERENCE METER EQUIPMENT NUMBER: 00373				Calibration Due Date: <del>7</del> /17/18			
CALIBRATION PERFORMED BY:		DATE:		AMBIENT TEMPERATURE:		BAROMETRIC PRESSURE:	
B. Davis		1/17/2018		68		29.87	
Input Temperature (F)	Ambient	Meter A					FB Interior
			Meter B	Filter A	Filter B	Tunnel	
0	1	0	0	1	0	0	0
100	101	100	100	100	100	100	100
300	300	300	300	300	300	300	299
500	500	500	500	500	500	500	499
700	700	700	700	700	700	700	699
1000	1000	1000	1000	1000	1000	1000	1000

Input (F)	FB Top	FB Bottom	FB Back	FB Left	FB Right	Imp A	Imp B	Cat	Stack
0	0	0	0	-1	-1	0	0	0	0
100	100	100	100	99	99	100	100	100	100
300	300	299	299	299	299	300	300	300	299
500	499	499	499	499	499	500	500	500	500
700	699	699	699	699	699	700	700	700	700
1000	1000	999	1000	1000	999	1000	1000	1000	1000

1500  
2000

1500  
1999

Technician signature: BD Date: 1/17/2018


Reviewed By: [Signature] Date: 1/19/2018

# Thermal Metering System Calibration Y Factor

Manufacturer: APEX  
 Model: XC-60-EP  
 Serial Number: 606002  
 OMNI Tracking No.: OMNI-00336  
 Calibrated Orifice:  Yes

<b>Average Gas Meter y Factor</b>
<b>0.979</b>

<b>Orifice Meter dH@</b>
<b>N/A</b>

Calibration Date: 01/17/18  
 Calibrated by: B. Davis  
 Calibration Frequency: Six months  
 Next Calibration Due: 1/18/2018  
 Instrument Range: 1.000 cfm  
 Standard Temp.: 68 oF  
 Standard Press.: 29.92 "Hg  
 Barometric Press., Pb: 29.94 "Hg  
 Signature/Date:  1/17/2018

1 / 19 / 2017

### Previous Calibration Comparison

Date	<u>7/18/2017</u>	Acceptable Deviation (5%)	Deviation
y Factor	<u>0.984</u>	0.0492	0.005
Acceptance	<b>Acceptable</b>		

### Current Calibration

Acceptable y Deviation	0.020
Maximum y Deviation	0.003
Acceptable dH@ Deviation	N/A
Maximum dH@ Deviation	N/A
Acceptance	<b>Acceptable</b>

### Reference Standard \*

Standard	Model	Standard Test Meter
Calibrator	S/N	<u>OMNI-00001</u>
	Calib. Date	<u>30-Oct-17</u>
	Calib. Value	<u>0.9977</u> y factor (ref)

Calibration Parameters	Run 1	Run 2	Run 3
Reference Meter Pressure ("H2O), Pr	0.00	0.00	0.00
DGM Pressure ("H2O), Pd	1.95	1.20	0.80
Initial Reference Meter	223.4	231.9	238
Final Reference Meter	231.7	237.9	243.503
Initial DGM	0	0	0
Final DGM	8.517	6.215	5.713
Temp. Ref. Meter (°F), Tr	68.0	69.1	68.6
Temperature DGM (°F), Td	76.0	78.0	79.0
Time (min)	39.8	36.5	37.0
Net Volume Ref. Meter, Vr	8.300	6.000	5.503
Net Volume DGM, Vd	8.517	6.215	5.713
<b>Gas Meter y Factor =</b>	<b>0.982</b>	<b>0.977</b>	<b>0.978</b>
<b>Gas Meter y Factor Deviation (from avg.)</b>	0.003	0.002	0.001
<b>Orifice dH@</b>	N/A	N/A	N/A
<b>Orifice dH@ Deviation (from avg.)</b>	N/A	N/A	N/A

where:

1. Deviation = |Average value for all runs - current run value|
- \*\* 2.  $y = [Vr \times (y \text{ factor (ref)}) \times (Pb + (Pr / 13.6)) \times (Td + 460)] / [Vd \times (Pb + (Pd / 13.6)) \times (Tr + 460)]$
- \*\* 3.  $dH@ = 0.0317 \times Pd / (Pb (Td + 460)) \times [(Tr + 460) \times \text{time}] / Vr]^2$

\* Reference calibration is traceable to NIST through NIST Test # 40674, Kimble ASTM E1272, or NIST traceable laboratory

\*\* Equations come from EPA Method 5

The uncertainty of measurement is  $\pm 0.14 \text{ ft}^3/\text{min}$ . This is based on the reference standard having a TAR (Test Accuracy Ratio) of at least 4:1.

## DIFFERENTIAL PRESSURE GAUGE CALIBRATION DATA SHEET

Instrument to be calibrated: Pressure Transducer

Maximum Range: 0-2" WC ID Number: OMNI-00336

Calibration Instrument: Digital Manometer ID Number: OMNI-00395

Date: 1/17/2018 By: B. Davis

**This form is to be used only in conjunction with Standard Procedure C-SPC.**

Range of Calibration Point ("WC)	Digital Manometer Input ("WC)	Pressure Gauge Response ("WC)	Difference (Input - Response)	% Error of Full Span*
0-20% Max. Range 0 - 0.4	0.35	0.362	0.012	0.6
20-40% Max. Range 0.4 - 0.8	0.65	0.672	0.022	1.1
40-60% Max. Range 0.8 - 1.2	1.00	1.024	0.024	1.2
60-80% Max. Range 1.2 - 1.6	1.30	1.340	0.040	2.0
80-100% Max. Range 1.6 - 2.0	1.70	1.749	0.049	2.45

\*Acceptable tolerance is 4%.

The uncertainty of measurement is  $\pm 0.4$ " WC. This is based on the reference standard having a TAR (Test Accuracy Ratio) of at least 4:1.

Technician signature:  Date: 1/18/2018

Reviewed by:  Date: 1/19/2018



Temperature Calibration EPA Method 28R, ASTM 2515							
BOOTH:		TEMPERATURE MONITOR TYPE:			EQUIPMENT NUMBER:		
E1		National Instruments Logger			00335, 00336		
REFERENCE METER EQUIPMENT NUMBER: 00373				Calibration Due Date: <del>7</del> /17/18			
CALIBRATION PERFORMED BY:		DATE:	AMBIENT TEMPERATURE:		BAROMETRIC PRESSURE:		
B. Davis		1/17/2018	68		29.87		
Input Temperature (F)	Ambient	Meter A					FB Interior
			Meter B	Filter A	Filter B	Tunnel	
0	1	0	0	1	0	0	0
100	101	100	100	100	100	100	100
300	300	300	300	300	300	300	299
500	500	500	500	500	500	500	499
700	700	700	700	700	700	700	699
1000	1000	1000	1000	1000	1000	1000	1000

Input (F)	FB Top	FB Bottom	FB Back	FB Left	FB Right	Imp A	Imp B	Cat	Stack
0	0	0	0	-1	-1	0	0	0	0
100	100	100	100	99	99	100	100	100	100
300	300	299	299	299	299	300	300	300	299
500	499	499	499	499	499	500	500	500	500
700	699	699	699	699	699	700	700	700	700
1000	1000	999	1000	1000	999	1000	1000	1000	1000

1500  
2000

1500  
1999

Technician signature: BD Date: 1/17/2018

Reviewed By: [Signature] Date: 1/19/2018

# Certificate of Calibration

Certificate Number: **659360**



**JJ Calibrations, Inc.**

7007 SE Lake Rd  
Portland, OR 97267-2105  
Phone 503.786.3005  
FAX 503.786.2994

**Omni-Test Laboratories**  
13327 NE Airport Way  
Portland, OR 97230

PO: **170149**  
Order Date: **09/22/2017**  
Authorized By: **N/A**



Property #: **OMNI-00410**  
User: **N/A**  
Department: **N/A**  
Make: **Dwyer**  
Model: **1430**  
Serial #: **OMNI-00410**  
Description: **Microtector**  
Procedure: **SEND TO VENDOR**  
Accuracy: **±0.00025" WC**

Calibrated on: **10/11/2017**  
\*Recommended Due: **10/11/2018**  
Environment: **19 °C 52 % RH**  
\* As Received: **Limited**  
\* As Returned: **Limited**  
Action Taken: **Calibrated**  
Technician: **34**

Remarks: \* Many factors may cause the unit to drift out of calibration before the recommended due date. Any reported error is the absolute value between the reference and the unit. Uncertainties include the effects of the unit.

**Limited Calibration (est.2016) - Calibrated micrometer head only.**

## Standards Used

Std ID	Manufacturer	Model	Nomenclature	Due Date	Trace ID
541A	Select	E8FED2	8 Piece Gage Block Set	12/14/2017	635720
103A	Brown & Sharpe	598-81-14	Gage Block Set, 81 pc.	03/16/2019	643452
368A	Rutland	2225-7081	81 Piece Gage Block Set	06/01/2018	649394

## Parameter

## Measurement Data

Measurement Description	Range	Unit	Reference	Min	Max	Error	UUT	Uncertainty
<b>Before/After Length</b>								Accredited = ✓
	Inch		0.1300	0.129	0.131	0.000	0.130 Inch	1.1E-03 ✓
	Inch		0.3850	0.384	0.386	0.000	0.385 Inch	1.1E-03 ✓
	Inch		0.6150	0.614	0.616	0.000	0.615 Inch	1.1E-03 ✓
	Inch		0.8700	0.869	0.871	0.000	0.870 Inch	1.1E-03 ✓
	Inch		1.0000	0.999	1.001	0.000	1.000 Inch	1.1E-03 ✓

JJ Calibrations, Inc. certifies that this instrument has been calibrated in accordance with the JJ Calibrations Quality Assurance Manual with the stated procedure using standards that are traceable to the National Institute of Standards and Technology (NIST), or other National Measurement Institutes (NMI's), or by using natural physical constants, intrinsic standards or ratio calibration techniques. The quality system and this certificate are in compliance with ANSI/NCCL Z540-1-1994, ISO/IEC 17025-2005, ISO 10012-1, the ISO 9000 family and QS 9000. The expanded uncertainties of measurements for this calibration are based upon 95% (2 sigma) confidence limits. Unless otherwise stated, a test accuracy ratio (TAR) of 4:1, if achievable, is maintained. The results reported herein apply only to the calibration of the item described above. This report may not be reproduced, except in full, without prior written consent of JJ Calibrations, Inc. JJ Calibrations, Inc. quality system has been assessed and accredited to ISO/IEC 17025:2005.

  
Reviewer

3 Issued 10/13/2017 Rev # 15

  
Inspector



OMNI Track #	OMNI-00594			
Equipment Name/Description	CAI ZRE-4 Gas Analyzer			
Equipment S/N:	N5F0112			
Comments	CO2, O2, and dual range CO gas analyzer.			
Status	Active, calibrate prior to use.			
Part #	ZRE-4			
Reference Standard:	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> X	<input type="checkbox"/> NO	(Check 'X' for answer)
Location of Equipment:	Portable gas cart.			
Calibration Vendor	OMNI in house			
Type of Calibration	Calibrate Prior to use.			
Calibration Period (Months)	N/A			
Date of Last Calibration	N/A			
Date of Next Calibration	N/A			

Do the following:

- 1) Complete Calibration documentation
- 2) Complete top half of this form
- 3) Attach appropriate calibration forms and save in following location  
    \\omni-serv\Test Equipment\Equipment\OMNI-XXXXX - Equipment Name
- 4) Repopulate database with updated information
- 5) Print, laminate and adhere calibration tag to equipment

<p>Verify before use  OMNI-00594  Gas Analyzer</p>
--

<p>Verify before use  OMNI-00594  Gas Analyzer</p>
--

# Certificate of Calibration

Certificate Number: **655889**



**JJ Calibrations, Inc.**

7007 SE Lake Rd  
Portland, OR 97267-2105  
Phone 503.786.3005  
FAX 503.786.2994

**Omni-Test Laboratories**  
13327 NE Airport Way  
Portland, OR 97230

OnSite

PO: 170142

Order Date: 08/07/2017

Authorized By: N/A



0723.01  
Calibration

Property #: **OMNI-00637**

User: **N/A**

Department: **N/A**

Make: **Mettler Toledo**

Model: **MS104TS/00**

Serial #: **B729400181**

Description: **Scale, Analytical, 120g**

Procedure: **DCN 500887**

Accuracy: **±0.0005g**

Calibrated on: **08/07/2017**

\*Recommended Due: **02/07/2018**

Environment: **22 °C 45 % RH**

\* As Received: **Within Tolerance**

\* As Returned: **Within Tolerance**

Action Taken: **Calibrated**

Technician: **34**

Remarks: \* Many factors may cause the unit to drift out of calibration before the recommended due date. Any reported error is the absolute value between the reference and the unit. Uncertainties include the effects of the unit.

## Standards Used

Std ID	Manufacturer	Model	Nomenclature	Due Date	Trace ID
256A	Rice Lake	W0133K	Mass Set	10/28/2017	616126

## Measurement Data

Parameter	Measurement Description	Range	Unit	Reference	Min	Max	*Error	UUT	Uncertainty
<b>Before/After</b>									Accredited = ✓
<b>Force</b>									
			g	10.00000	9.9995	10.0005	0.0001	10.0001 g	5.7E-04 ✓
			g	30.00000	29.9995	30.0005	0.0001	30.0001 g	5.7E-04 ✓
			g	60.00000	59.9995	60.0005	0.0003	60.0003 g	5.7E-04 ✓
			g	90.00000	89.9995	90.0005	0.0002	90.0002 g	5.7E-04 ✓
			g	120.00000	119.9995	120.0005	0.0003	120.0003 g	5.7E-04 ✓

JJ Calibrations, Inc. certifies that this instrument has been calibrated in accordance with the JJ Calibrations Quality Assurance Manual with the stated procedure using standards that are traceable to the National Institute of Standards and Technology (NIST), or other National Measurement Institutes (NMI's), or by using natural physical constants, intrinsic standards or ratio calibration techniques. The quality system and this certificate are in compliance with ANSI/NCCL Z540-1-1994, ISO/IEC 17025-2005, ISO 10012-1, the ISO 9000 family and QS 9000. The expanded uncertainties of measurements for this calibration are based upon 95% (2 sigma) confidence limits. Unless otherwise stated, a test accuracy ratio (TAR) of 4:1, if achievable, is maintained. The results reported herein apply only to the calibration of the item described above. This report may not be reproduced, except in full, without prior written consent of JJ Calibrations, Inc. JJ Calibrations, Inc. quality system has been assessed and accredited to ISO/IEC 17025:2005.

Reviewer


3 Issued 08/14/2017

Rev # 15

Inspector

# Certificate of Calibration

Certificate Number: **668066**



**JJ Calibrations, Inc.**  
 7007 SE Lake Rd  
 Portland, OR 97267-2105  
 Phone 503.786.3005  
 FAX 503.786.2994

**Omni-Test Laboratories**  
 13327 NE Airport Way  
 Portland, OR 97230

OnSite

PO: **180161**  
 Order Date: **02/06/2018**  
 Authorized By: **N/A**



Calibrated on: **02/06/2018**  
 \*Recommended Due: **08/06/2018**  
 Environment: **20 °C 53 % RH**  
 \* As Received: **Within Tolerance**  
 \* As Returned: **Within Tolerance**  
 Action Taken: **Calibrated**  
 Technician: **111**

Property #: **OMNI-00637**  
 User: **N/A**  
 Department: **N/A**  
 Make: **Mettler Toledo**  
 Model: **MS104TS/00**  
 Serial #: **B729400181**  
 Description: **Analytical Scale, 120g**  
 Procedure: **DCN 500887**  
 Accuracy: **±0.0005g**

Remarks: \* Many factors may cause the unit to drift out of calibration before the recommended due date. Any reported error is the absolute value between the reference and the unit. Uncertainties include the effects of the unit.

## Standards Used

Std ID	Manufacturer	Model	Nomenclature	Due Date	Trace ID
503A	Rice Lake	1mg-200g (Class 0)	Mass Set,	04/20/2018	642578

## Measurement Data

Parameter	Measurement Description	Range Unit	Reference	Min	Max	*Error	UUT	Uncertainty
<b>Before/After</b>	<b>Force</b>							Accredited = ✓
		g	10.00000	9.9995	10.0005	0.0001	10.0001 g	5.7E-04 ✓
		g	30.00000	29.9995	30.0005	0.0003	30.0003 g	5.7E-04 ✓
		g	60.00000	59.9995	60.0005	0.0001	60.0001 g	5.7E-04 ✓
		g	90.00000	89.9995	90.0005	0.0001	89.9999 g	5.7E-04 ✓
		g	120.00000	119.9995	120.0005	0.0002	119.9998 g	5.7E-04 ✓

JJ Calibrations, Inc. certifies that this instrument has been calibrated in accordance with the JJ Calibrations Quality Assurance Manual with the stated procedure using standards that are traceable to the National Institute of Standards and Technology (NIST), or other National Measurement Institutes (NMI's), or by using natural physical constants, intrinsic standards or ratio calibration techniques. The quality system and this certificate are in compliance with ANSI/NCCL Z540-1-1994, ISO/IEC 17025-2005, ISO 10012-1, the ISO 9000 family and QS 9000. The expanded uncertainties of measurements for this calibration are based upon 95% (2 sigma) confidence limits. Unless otherwise stated, a test accuracy ratio (TAR) of 4:1, if achievable, is maintained. The results reported herein apply only to the calibration of the item described above. This report may not be reproduced, except in full, without prior written consent of JJ Calibrations, Inc.  
 JJ Calibrations, Inc. quality system has been assessed and accredited to ISO/IEC 17025:2005.

Reviewer

3 Issued

Rev # 15

Inspector

### **3.3 - Example Calculations**

## Equations and Sample Calculations – ASTM E2779 & E2515

Manufacturer: HHT Halifax  
Model: Absolute 43-C  
Run: 1  
Category: [Integrated]

Equations used to calculate the parameters listed below are described in this appendix. Sample calculations are provided for each equation. The raw data and printout results from a sample run are also provided for comparison to the sample calculations.

$M_{Bdb}$  – Weight of test fuel burned during test run, dry basis, kg

$M_{BSidb}$  – Weight of test fuel burned during test run segment  $i$ , dry basis, kg

BR – Average dry burn rate over full integrated test run, kg/hr

$BR_{Si}$  – Average dry burn rate over test run segment  $i$ , kg/hr

$V_s$  – Average gas velocity in the dilution tunnel, ft/sec

$Q_{sd}$  – Average gas flow rate in dilution tunnel, dscf/hr

$V_{m(std)}$  – Volume of Gas Sampled Corrected to Dry Standard Conditions, dscf

$m_n$  – Total Particulate Matter Collected, mg

$C_s$  - Concentration of particulate matter in tunnel gas, dry basis, corrected to standard conditions, g/dscf

$E_T$  – Total Particulate Emissions, g

PR - Proportional Rate Variation

$PM_R$  – Average particulate emissions for full integrated test run, g/hr

$PM_F$  – Average particulate emission factor for full integrated test run, g/dry kg of fuel burned



**M<sub>Bdb</sub> – Weight of test fuel burned during test run, dry basis, kg**  
ASTM E2779 equation (1)

$$M_{Bdb} = (M_{Swb} - M_{Ewb})(100/(100 + FM))$$

Where,

FM = average fuel moisture of test fuel, % dry basis

M<sub>Swb</sub> = weight of test fuel in hopper at start of test run, wet basis, kg

M<sub>Ewb</sub> = weight of test fuel in hopper at end of test run, wet basis, kg

Sample Calculation:

4.8 %

M<sub>Swb</sub> = 15.1 lbs

M<sub>Ewb</sub> = 0.0 lbs

0.4536 = Conversion factor from lbs to kg

$$M_{Bdb} = [(15.1 \times 0.4536) - (0.0 \times 0.4536)] (100/(100 + 4.844))$$

$$M_{Bdb} = \mathbf{6.5 \text{ kg}}$$

**$M_{BSidb}$  – Weight of test fuel burned during test run segment  $i$ , dry basis, kg**  
ASTM E2779 equation (2)

$$M_{BSidb} = (M_{S_{Siwb}} - M_{E_{Siwb}})(100/(100 + FM))$$

Where,

$M_{S_{Siwb}}$  = weight of test fuel in hopper at start of test run segment  $i$ , wet basis, kg

$M_{E_{Siwb}}$  = weight of test fuel in hopper at end of test run segment  $i$ , wet basis, kg

Sample Calculation (from medium burn rate segment):

$$FM = 4.8 \%$$

$$M_{S_{Siwb}} = 9.7 \text{ lbs}$$

$$M_{E_{Siwb}} = 5.1 \text{ lbs}$$

0.4536 = Conversion factor from lbs to kg

$$M_{BSidb} = [(9.7 \times 0.4536) - (5.1 \times 0.4536)] (100/(100 + 5))$$

$$M_{BSidb} = 2 \text{ kg}$$

**BR – Average dry burn rate over full integrated test run, kg/hr**  
ASTM E2779 equation (3)

$$BR = \frac{60 M_{Bdb}}{\theta}$$

Where,

$\theta$  = Total length of full intergrated test run, min

Sample Calculation:

$$M_{Bdb} = 6.53 \quad \text{kg}$$

$$\theta = 361 \quad \text{min}$$

$$BR = \frac{60 \times 6.53}{361}$$

$$BR = \mathbf{1.09} \quad \text{kg/hr}$$

**BR<sub>Si</sub> – Average dry burn rate over test run segment *i*, kg/hr**  
ASTM E2779 equation (4)

$$BR_{Si} = \frac{60 M_{BSidb}}{\theta_{Si}}$$

Where,

$$\theta_{Si} = \text{Total length of test run segment } i, \text{ min}$$

Sample Calculation (from medium burn rate segment):

$$M_{BSidb} = 1.99 \text{ kg}$$

$$\theta = 120 \text{ min}$$

$$BR = \frac{60 \times 1.99}{120}$$

$$BR = 1.00 \text{ kg/hr}$$

**V<sub>s</sub> – Average gas velocity in the dilution tunnel, ft/sec**

ASTM E2515 equations (9)

$$V_s = F_p \times K_p \times C_p \times (\sqrt{\Delta P})_{avg} \times \sqrt{\frac{T_s}{P_s \times M_s}}$$

Where:

- F<sub>p</sub> = Adjustment factor for center of tunnel pitot tube placement,  $F_p = \frac{V_{strav}}{V_{scent}}$ , ASTM E2515 Equation (1)
- V<sub>scent</sub> = Dilution tunnel velocity calculated after the multi-point pitot traverse at the center, ft/sec
- V<sub>strav</sub> = Dilution tunnel velocity calculated after the multi-point pitot traverse, ft/sec
- k<sub>p</sub> = Pitot tube constant, 85.49
- C<sub>p</sub> = Pitot tube coefficient: 0.99, unitless
- ΔP\* = Velocity pressure in the dilution tunnel, in H<sub>2</sub>O
- T<sub>s</sub> = Absolute average gas temperature in the dilution tunnel, °R; (°R = °F + 460)
- P<sub>s</sub> = Absolute average gas static pressure in dilution tunnel, = P<sub>bar</sub> + P<sub>g</sub>, in Hg
- P<sub>bar</sub> = Barometric pressure at test site, in. Hg
- P<sub>g</sub> = Static pressure of tunnel, in. H<sub>2</sub>O; (in Hg = in H<sub>2</sub>O/13.6)
- M<sub>s</sub> = \*\*The dilution tunnel wet molecular weight; M<sub>s</sub> = 28.78 assuming a dry weight of 29 lb/lb-mole

Sample calculation:

$$F_p = \frac{13.76}{15.45} = 0.891$$

$$V_s = 0.891 \times 85.49 \times 0.99 \times 0.226 \times \left( \frac{89.5 + 460}{\left( \frac{30.26}{13.6} + \frac{-0.16}{13.6} \right) \times 28.78} \right)^{1/2}$$

$$V_s = \mathbf{13.56 \text{ ft/s}}$$

\*The ASTM test standard mistakenly has the square root of the average delta p instead of the average of the square root of delta p. The current EPA Method 2 is also incorrect. This was verified by Mike Toney at EPA.

\*\*The ASTM test standard mistakenly identifies M<sub>s</sub> as the dry molecular weight. It should be the wet molecular weight as indicated in EPA Method 2.

**Q<sub>sd</sub> – Average gas flow rate in dilution tunnel, dscf/hr**

ASTM E2515 equation (3)

$$Q_{sd} = 3600 \times (1 - B_{ws}) \times v_s \times A \times \frac{T_{std}}{T_s} \times \frac{P_s}{P_{std}}$$

Where:

- 3600 = Conversion from seconds to hours (ASTM method uses 60 to convert in minutes)
- B<sub>ws</sub> = Water vapor in gas stream, proportion by volume; assume 2%
- A = Cross sectional area of dilution tunnel, ft<sup>2</sup>
- T<sub>std</sub> = Standard absolute temperature, 528 °R
- P<sub>s</sub> = Absolute average gas static pressure in dilution tunnel, = P<sub>bar</sub> + P<sub>g</sub>, in Hg
- T<sub>s</sub> = Absolute average gas temperature in the dilution tunnel, °R; (°R = °F + 460)
- P<sub>std</sub> = Standard absolute pressure, 29.92 in Hg

Sample calculation:

$$Q_{sd} = 3600 \times (1 - 0.02) \times 13.56 \times 0.196 \times \frac{528}{89.5 + 460} \times \frac{30.3 + \frac{-0.16}{13.6}}{29.92}$$

$$Q_{sd} = \mathbf{9120.6 \text{ dscf/hr}}$$

**$V_{m(std)}$  – Volume of Gas Sampled Corrected to Dry Standard Conditions, dscf**  
 ASTM E2515 equation (6)

$$V_{m(std)} = K_1 \times V_m \times Y \times \frac{P_{bar} + \left( \frac{\Delta H}{13.6} \right)}{T_m}$$

Where:

- $K_1$  = 17.64 °R/in. Hg
- $V_m$  = Volume of gas sample measured at the dry gas meter, dcf
- $Y$  = Dry gas meter calibration factor, dimensionless
- $P_{bar}$  = Barometric pressure at the testing site, in. Hg
- $\Delta H$  = Average pressure differential across the orifice meter, in. H<sub>2</sub>O
- $T_m$  = Absolute average dry gas meter temperature, °R

Sample Calculation:

Using equation for Train 1:

$$V_{m(std)} = 17.64 \times 58.789 \times 0.977 \times \frac{\left( 30.26 + \frac{1.31}{13.6} \right)}{\left( 80.9 + 460 \right)}$$

$$V_{m(std)} = \mathbf{56.855} \text{ dscf}$$

Using equation for Train 2:

$$V_{m(std)} = 17.64 \times 58.238 \times 0.979 \times \frac{\left( 30.26 + \frac{1.07}{13.6} \right)}{\left( 80.7 + 460 \right)}$$

$$V_{m(std)} = \mathbf{56.425} \text{ dscf}$$

Using equation for ambient train:

$$V_{m(std)} = 17.64 \times 0.00 \times 0 \times \frac{\left( 30.26 + \frac{0.00}{13.6} \right)}{\left( 70.2 + 460 \right)}$$

$$V_{m(std)} = \mathbf{0.000} \text{ dscf}$$

**$m_n$  – Total Particulate Matter Collected, mg**

ASTM E2515 Equation (12)

$$m_n = m_p + m_f + m_g$$

Where:

$m_p$  = mass of particulate matter from probe, mg

$m_f$  = mass of particulate matter from filters, mg

$m_g$  = mass of particulate matter from filter seals, mg

Sample Calculation:

Using equation for Train 1 (first hour):

$$m_n = 0.0 + 1.5 + 0.0$$

$$m_n = 1.5 \text{ mg}$$

Using equation for Train 1 (remainder):

$$m_n = 0.0 + 3.4 + 1.1$$

$$m_n = 4.5 \text{ mg}$$

Train 1 Aggregate = **6.0 mg**

Using equation for Train 2:

$$m_n = 0.0 + 5.7 + 0.6$$

$$m_n = \mathbf{6.3 \text{ mg}}$$



**C<sub>s</sub> - Concentration of particulate matter in tunnel gas, dry basis, corrected to standard conditions, g/dsc**  
ASTM E2515 equation (13)

$$C_s = K_2 \times \frac{m_n}{V_{m(std)}}$$

Where:

K<sub>2</sub> = Constant, 0.001 g/mg

m<sub>n</sub> = Total mass of particulate matter collected in the sampling train, mg

V<sub>m(std)</sub> = Volume of gas sampled corrected to dry standard conditions, dscf

Sample calculation:

For Train 1:

$$C_s = 0.001 \times \frac{6.0}{56.86}$$

$$C_s = \mathbf{0.00011} \text{ g/dscf}$$

For Train 2

$$C_s = 0.001 \times \frac{6.3}{56.42}$$

$$C_s = \mathbf{0.00011} \text{ g/dscf}$$

For Ambient Train

$$C_r = 0.001 \times \frac{0.0}{0.00}$$

$$C_r = \mathbf{0.000000} \text{ g/dscf}$$

**E<sub>T</sub> – Total Particulate Emissions, g**

ASTM E2515 equation (15)

$$E_T = (C_s - C_r) \times Q_{std} \times \theta$$

Where:

- C<sub>s</sub> = Concentration of particulate matter in tunnel gas, g/dscf
- C<sub>r</sub> = Concentration particulate matter room air, g/dscf
- Q<sub>std</sub> = Average dilution tunnel gas flow rate, dscf/hr
- θ = Total time of test run, minutes

Sample calculation:

For Train 1

$$E_T = ( \underline{0.000106} - 0.000000 ) \times \underline{9120.6} \times \underline{361} /60$$
$$E_T = \underline{5.79} \text{ g}$$

For Train 2

$$E_T = ( \underline{0.000112} - 0.000000 ) \times \underline{9120.6} \times \underline{361} /60$$
$$E_T = \underline{6.13} \text{ g}$$

Average

$$E = \underline{5.96} \text{ g}$$

Total emission values shall not differ by more than 7.5% from the total average emissions

$$7.5\% \text{ of the average} = \underline{0.45}$$

$$\text{Train 1 difference} = \underline{0.17}$$

$$\text{Train 2 difference} = \underline{0.17}$$

**PR - Proportional Rate Variation**

ASTM E2515 equation (16)

$$PR = \left[ \frac{\theta \times V_{mi} \times V_s \times T_m \times T_{si}}{\theta_i \times V_m \times V_{si} \times T_{mi} \times T_s} \right] \times 100$$

Where:

$\theta$  = Total sampling time, min

$\theta_i$  = Length of recording interval, min

$V_{mi}$  = Volume of gas sample measured by the dry gas meter during the "ith" time interval, dcf

$V_m$  = Volume of gas sample as measured by dry gas meter, dcf

$V_{si}$  = Average gas velocity in the dilution tunnel during the "ith" time interval, ft/sec

$V_s$  = Average gas velocity in the dilution tunnel, ft/sec

$T_{mi}$  = Absolute average dry gas meter temperature during the "ith" time interval, °R

$T_m$  = Absolute average dry gas meter temperature, °R

$T_{si}$  = Absolute average gas temperature in the dilution tunnel during the "ith" time interval, °R

$T_s$  = Absolute average gas temperature in the dilution tunnel, °R

Sample calculation (for the first 1 minute interval of Train 1):

$$PR = \left( \frac{361 \times 0.154 \times 13.56 \times (103.0 + 460) \times (80.9 + 460)}{1 \times 58.79 \times 13.83 \times (89.5 + 460) \times (73.0 + 460)} \right) \times 100$$

$$PR = \underline{96} \%$$

**PM<sub>R</sub> – Average particulate emissions for full integrated test run, g/hr**  
ASTM E2779 equation (5)

$$PM_R = 60 (E_T/\theta)$$

Where,

E<sub>T</sub> = Total particulate emissions, grams

θ = Total length of full integrated test run, min

Sample Calculation:

$$E_T (\text{Dual train average}) = 5.96 \text{ g}$$

$$\theta = 361 \text{ min}$$

$$PM_R = 60 \times ( 5.96 / 361 )$$

$$PM_R = 0.99 \text{ g/hr}$$

**PM<sub>F</sub> – Average particulate emission factor for full integrated test run, g/dry kg of fuel burned**  
ASTM E2779 equation (6)

$$PM_F = E_T / M_{Bdb}$$

Where,

$E_T$  = Total particulate emissions, grams

$M_{Bdb}$  = Weight of test fuel burned during test run, dry basis, kg

Sample Calculation:

$$E_T \text{ (Dual train average)} = 5.96 \text{ g}$$

$$M_{Bdb} = 6.53 \text{ kg}$$

$$PM_F = 5.96 / 6.53 )$$

$$PM_F = \mathbf{0.91} \text{ g/kg}$$

# **Appendix A**

## **Labeling & Owner's/Installation Manual**



**MODEL / MODÈLE: "Absolute43-C"**

Room Heater Pellet Fuel-Burning Type  
SUITABLE FOR MOBILE-HOME INSTALLATION

This pellet burning appliance has been tested and listed for use in Manufactured Homes in accordance with OAR 814-23-900 through 814-23-909

**Report / Rapport #0135PS039E, 0135PS032S**

Test /testé à ASTM E 1509-12, ULC-S627-00, ASTM E 2515-11, ASTM E 2779-10

Room Heater, Pellet Fuel-Burning Type, Also For Use In Mobile Homes. (UM) 84-HUD

**"PREVENT HOUSE FIRES"** Install and use only in accordance with manufactures installation and operation instructions.

Contact local building or fire officials about restrictions and installation inspection in your area.

**WARNING: FOR MANUFACTURED HOMES:**

Do not install appliance in a sleeping room. An outside combustion air inlet must be provided. The structural integrity of the manufactured home floor, ceiling and walls must be maintained.

Refer to manufacturer's instructions and local codes for precautions required for passing chimney through a combustible wall or ceiling. Inspect and clean exhaust venting system frequently in accordance with manufacturer's instructions. Use a 3" or 4" diameter type "L" or "PL" venting system.

Do not connect this unit to a chimney flue servicing another appliance.

Do not obstruct the space beneath the heater.

**FOR USE WITH PELLETTIZED WOOD FUEL ONLY.**

EPA Certified Emissions: .99 g/hr

**Input Rating Max:** 5.0 lb. fuel/hr

**Electrical Rating:** 240 VAC, 50 Hz, Start 1.75 AMPS, Run 1.25 AMPS

**U.S. Electrical Rating:** 115 VAC, 60 Hz, Start 3.5 AMPS, Run 2.5 AMPS

Fuel Type: Wood Pellet ONLY

**Route power cord away from unit.**

**MINIMUM CLEARANCES TO COMBUSTIBLES**

Back Wall to Appliance 2"  
Side Wall to Appliance 6"

**Corner Installation**  
Walls to Appliance 6.25"

Use a non-combustible floor protector extending under and to the sides, front and back of the unit as shown in floor protection diagram. Measure front distance from the surface of the glass door.

**Recommended: Non-combustible floor protection extended beneath the flue pipe when installed with horizontal venting.**

Floor Protection*	USA	CANADA
Sides (A)	6"	152 mm
Back (B)	1"	25 mm
Front (C)	6"	152 mm

**Alcove Installation**  
Min. Alcove Height 42" (1067mm)  
Max. Alcove Depth 24" (610mm)

**US ENVIRONMENTAL PROTECTION AGENCY**




The Absolute43-C is Certified to comply with 2020 particulate emission standards.

L'Absolute43-C est certifié conforme aux normes d'émission de particules de 2020.

This wood heater needs periodic inspection and repair for proper operation. Consult the owner's manual for further information. It is against federal regulations to operate this wood heater in a manner inconsistent with the operating instructions in the owner's manual.



3-90-7772\_R1



**THIS AREA MUST BE BLACK**

**Modèle: "Absolute43-C"**  
Appareil de chauffage à granulés de bois  
CONÇU POUR MAISONS MOBILES

Serial No. **HF**  
N° de série:

BARCODE LABEL

Test pour / tested à la norme ASTM E 1509-12, ULC-S627-00, EPA Method 28 & 5G

Chauffe-chambre, Pellet à combustibles Type, également pour les maisons mobiles. (UM) 84-HUD

**"Empêcher MAISON incendies"** Installer et utiliser uniquement en conformité avec les instructions du fabricant d'installation et d'exploitation.

Contactez le service des incendies à propos des restrictions et l'inspection d'installation dans votre région.

**AVERTISSEMENT: POUR maisons préfabriquées:** Ne pas installer l'appareil dans une chambre à coucher. Une entrée d'air de combustion à l'extérieur doit être fournie. L'intégrité structurale de la maison étage, plafond et murs fabriqués doit être maintenue. Reportez-vous aux instructions du fabricant et les codes locaux pour les précautions nécessaires pour faire passer la cheminée à travers un mur ou un plafond combustible. Inspectez et nettoyez système d'évacuation souvent en conformité avec les instructions du fabricant.

Utilisez un "ou 4" Type de diamètre «L» 3 ou le système de ventilation "PL".

Ne pas connecter cet appareil à un conduit de cheminée desservant un autre appareil.

**Ne pas obstruer l'espace sous le chauffe-eau.**

**À UTILISER AVEC LA GRANULE DE BOIS SEULEMENT.**

Émissions certifiées EPA: .99 g / h

**Entrée Max Note:** 5,0 carburant / h

**Note électrique:** 240 VAC, 50 Hz, Lancer 1,75 AMPS, Exécuter 1,25 AMPS

**US Note électrique:** 115 VAC, 60 Hz, 3,5 AMPS Démarrer, Exécuter 2,5 AMPS

Type de carburant: Bois Pellet SEULEMENT

**Route cordon électrique de l'appareil.**

**Fonctionner uniquement avec les portes fermées**

Ce poêle à bois a besoin d'une inspection et d'une réparation périodiques pour fonctionner correctement. Consultez le manuel du propriétaire pour plus d'informations. Il est contraire à la réglementation fédérale d'utiliser ce poêle à bois d'une manière non conforme aux instructions d'utilisation du manuel du propriétaire.

Date of Manufacture / Date de fabrication:

2018	2019	2020	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
■	■	■	■	■	■	■	■	■	■	■	■	■	■	■

Manufactured by / Fabriqué par: Hearth and Home Technologies 352 Mountain House Road, Halifax PA 17032

**LABEL TICKET**

<b>ECO:</b>	87270	<b>LABEL SIZE:</b>	5.75" H x 13.562" W
<b>PART # / REV:</b>	3-90-7772_R1	<b>ADHESIVE:</b>	
<b>ORIGINATOR:</b>	Spidlet	<b>MATERIAL:</b>	24 Gauge Aluminum
<b>DATE:</b>	01/23/18	<b>INK:</b>	Black Background
		352 Mountain House Road Halifax, PA 17032  (1) Holes = Ø.30 (5) Slotted Holes = .156 x .25 (4) Corners = R.062 Barcode label must have the serial number on it. The barcode label must be able to read Code 39 Full ASCII.	

# Installation Manual

## Installation and Appliance Setup

**INSTALLER:** Leave this manual with party responsible for use and operation.

**OWNER:** Retain this manual for future reference.


**NOTICE: SAVE THESE INSTRUCTIONS**

# HARMAN®

**BUILT TO A STANDARD, NOT A PRICE**

**Model(s):**

**Absolute43-C  
Freestanding Pellet Stove**



### CAUTION

Tested and approved for wood pellet fuel only. Burning of any other type of fuel voids your warranty.

Installation and service of this appliance should be performed by qualified personnel. Hearth & Home Technologies recommends HHT Factory Trained or NFI certified professionals.



### CAUTION

Check building codes prior to installation.

- Installation **MUST** comply with local, regional, state and national codes and regulations.
- Contact local building or fire officials about restrictions and installation inspection requirements in your area.

### WARNING



Please read this entire manual before installation and use of this pellet fuel-burning room heater.

**Failure to follow these instructions could result in property damage, bodily injury or even death.**

- Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
- Do not overfire - If any external part starts to glow, you are overfiring. Reduce feed rate. Overfiring will void your warranty.
- Comply with all minimum clearances to combustibles as specified. Failure to comply may cause house fire.

### WARNING



#### HOT SURFACES!

Glass and other surfaces are hot during operation AND cool down.

**Hot glass will cause burns.**

- Do not touch glass until it is cooled
  - **NEVER** allow children to touch glass
  - Keep children away
  - **CAREFULLY SUPERVISE** children in same room as stove.
  - Alert children and adults to hazards of high temperatures.
- High temperatures may ignite clothing or other flammable materials.**
- Keep clothing, furniture, draperies and other flammable materials away.

### NOTE

To obtain a French translation of this manual, please contact your dealer or visit [www.harmanstoves.com](http://www.harmanstoves.com)

Pour obtenir une traduction française de ce manuel, s'il vous plaît contacter votre revendeur ou visitez [www.harmanstoves.com](http://www.harmanstoves.com)



**⚠ Safety Alert Key:**

- **DANGER!** Indicates a hazardous situation which, if not avoided will result in death or serious injury.
- **WARNING!** Indicates a hazardous situation which, if not avoided could result in death or serious injury.
- **CAUTION!** Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
- **NOTICE:** Indicates practices which may cause damage to the stove or to property.

**TABLE OF CONTENTS**

→ **Installation Standard Work Checklist** . . . . . 3

**1 Product Specific and Important Safety Information**

A. Appliance Certification . . . . . 4

B. Glass Specifications . . . . . 4

C. Mobile Home Approvals . . . . . 4

D. BTU Specifications . . . . . 4

E. Electrical Codes . . . . . 4

F. California Safety Information . . . . . 4

**2 Getting Started**

A. Design and Installation Considerations . . . . . 5

B. Tools and Supplies Needed . . . . . 6

C. Inspect Appliance and Components . . . . . 6

**3 Framing and Clearances**

A. Appliance Dimension Diagram . . . . . 7

B. Non-Combustible Materials Specification . . . . . 8

C. Combustible Materials Specification . . . . . 8

D. Clearances to Combustibles . . . . . 8

E. Floor Protection . . . . . 9

F. Mobile Home Installation . . . . . 9

**4 Termination Location and Vent Information**

A. Vent Termination Minimum Clearances . . . . . 10

B. Chimney Diagram . . . . . 15

C. Venting & Use of Elbows . . . . . 16

D. Outside Air . . . . . 18

E. Locating Your Appliance and Chimney . . . . . 19

F. Draft . . . . . 19

G. Negative Pressure . . . . . 19

H. Avoiding Smoke & Odors . . . . . 20

I. Fire Safety . . . . . 21

J. Inspect Appliance & Components . . . . . 21

**5 Appliance Setup**

A. Unpacking . . . . . 22

B. Firebox Draft and Combustion Fan RPM . . . . . 22

C. Wireless Room Sensor . . . . . 23

D. Flame Guide . . . . . 23

**6 Reference Materials**

A. Safety Reminders . . . . . 24

B. Wiring Diagram . . . . . 25

→ = Contains updated information

# Installation Standard Work Checklist

## ATTENTION INSTALLER: Follow this Standard Work Checklist

This standard work checklist is to be used by the installer in conjunction with, not instead of, the instructions contained in this installation manual.

Customer: \_\_\_\_\_  
 Lot/Address: \_\_\_\_\_  
 \_\_\_\_\_  
 Model: \_\_\_\_\_

Date Installed: \_\_\_\_\_  
 Location of Stove: \_\_\_\_\_  
 Installer: \_\_\_\_\_  
 Dealer/Distributor Ph #: \_\_\_\_\_  
 Serial Number: \_\_\_\_\_

 **WARNING! Risk of Fire or Explosion! Failure to install appliance to these instructions can lead to a fire or explosion.**

### Appliance Install Section 3

Required non-combustible floor protection	YES	IF NO, WHY?
Verified clearances to combustible.	<input type="checkbox"/>	_____
Unit is Leveled and secured.	<input type="checkbox"/>	_____

### Venting/Chimney Section 4

Venting Configuration complies to vent diagrams.	YES	IF NO, WHY?
Venting installed, sealed and secured in place with proper clearances.	<input type="checkbox"/>	_____
Exterior wall/roof flashing installed and sealed	<input type="checkbox"/>	_____
Terminations installed and sealed.	<input type="checkbox"/>	_____

### Electrical Section 1

120 VAC unswitched power provided to the appliance.	YES	IF NO, WHY?
Check outlet with multi-meter for proper voltage. (115-120 VAC)	<input type="checkbox"/>	_____
Record voltage reading: _____	<input type="checkbox"/>	_____

### Appliance Setup Section 5

All packaging and protective materials are removed	YES	IF NO, WHY?
Accessories installed properly	<input type="checkbox"/>	_____
Manual bag and all it's contents are removed from inside the appliance and given to party responsible for use and operation	<input type="checkbox"/>	_____
Started appliance and verified that all motors and blowers operate as they should.	<input type="checkbox"/>	_____
Checked draft using a Manometer. Record readings: _____	<input type="checkbox"/>	_____
During operation, verify that the hopper lid switch (If applicable) and pressure switch are working properly by briefly opening the hopper lid and main door and verifying that the feed motor is interrupted.	<input type="checkbox"/>	_____

Hearth and Home Technologies recommends the following:  
 Photographing the installation and copying this checklist for your file.  
 This checklist remain visible at all times on the appliance until the installation is complete.

Comments: Further description of the issues, who is responsible (Installer/Builder/Other Trades, etc.) and corrective action needed \_\_\_\_\_

Comments communicated to party responsible \_\_\_\_\_ by \_\_\_\_\_ on \_\_\_\_\_  
 (Builder / Gen Contractor) (Installer) (Date)

# 1 Product Specific and Important Safety Information

## A. Appliance Certification

<b>MODEL:</b>	Absolute43-C Pellet Stove
<b>LABORATORY:</b>	OMNI Test Laboratories, Inc
<b>REPORT NO.</b>	0135PS039E, 0135PS032S
<b>TYPE:</b>	Pellet Fueled/Supplementary For Residential Use
<b>STANDARD(s):</b>	ASTM E 1509-12, ULC-S627-00, ASTM E 2515-11, ASTM E 2779-10
<b>ELECTRICAL RATING:</b>	115 VAC, 60 Hz, Start 4.0 Amps, Run 3.0 Amps
<b>GLASS SPECIFICATION:</b>	5mm mirrored ceramic glass

Harman® is a registered trademark of Hearth & Home Technologies.

The Absolute43-C is Certified to comply with 2020 particulate emission standards.



**NOTE:** This installation must conform with local codes. In the absence of local codes you must comply with the **ASTM E1509-2004, ULC S628-93, (UM) 84-HUD**

## B. Glass Specifications

This appliance is equipped with 5mm mirrored ceramic glass. Replace glass only with 5mm mirrored ceramic glass. Please contact your dealer for replacement glass.

## C. Mobile Home Approved

This appliance is approved for mobile home installations when not installed in a sleeping room and when an outside combustion air inlet is provided.

The structural integrity of the mobile home floor, ceiling, and walls must be maintained. The appliance must be properly grounded to the frame of the mobile home and use only listed pellet vent, Class "PL" connector pipe.

**A Harman® Outside Air Kit must be installed in a mobile home installation.**



### WARNING

**THE STRUCTURAL INTEGRITY OF THE MANUFACTURED HOME FLOOR, WALL, AND CEILING/ROOF MUST BE MAINTAINED.**

**DO NOT INSTALL IN SLEEPING ROOM.**

## D. BTU & Efficiency Specifications

<b>EPA Certification Number:</b>	126.18
<b>EPA Certified Emissions:</b>	.99 g/hr
<b>*LHV Tested Efficiency:</b>	82.3%
<b>**HHV Tested Efficiency:</b>	77%
<b>***EPA BTU Output:</b>	34,800 - 10,600
<b>****BTU Input</b>	44,200 - 14,100
<b>Vent Size:</b>	3 Inch
<b>Hopper Capacity:</b>	52 lbs
<b>Fuel</b>	Wood Pellet

\* Weighted average LHV efficiency using data collected during EPA emissions test.

\*\*Weighted average HHV efficiency using data collected during EPA emissions test.

\*\*\*A range of BTU outputs based on EPA Default Efficiency and the burn rates from the low and high EPA tests.

\*\*\*\*Based on the maximum feed rate per hour multiplied by approximately 8600 BTU's which is the average BTU's from a pound of pellets.

## E. Electrical Codes

115 VAC, 60 Hz, Start 4.0 Amps, Run 3.0 Amps

**Notice:** This appliance must be electrically wired and grounded in accordance with local codes or, in the absence of local codes, with **National Electric Code ANSI/NFPA 70-latest edition or the Canadian Electric Code CSA C22.1.**

**NOTE:** Some generator or battery back-up systems may not be compatible with the micro-processor electronics on this appliance. Please consult the power supply manufacturer for compatible systems.

**NOTE:** Hearth & Home Technologies, manufacturer of this appliance, reserves the right to alter its products, their specifications and/or price without notice.

## F. California Safety Information



### WARNING

This product and the fuels used to operate this product (wood), and the products of combustion of such fuels, can expose you to chemicals including lead and carbon black, which is known to the State of California to cause cancer, and carbon monoxide, which is know to the State of California to cause birth defects or other reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

# 2 Getting Started

## A. Design and Installation Considerations

### 1. Appliance Location

**NOTICE:** Check building codes prior to installation.

- Installation MUST comply with local, regional, state and national codes and regulations.
- Consult insurance carrier, local building inspector, fire officials or authorities having jurisdiction over restrictions, installation inspection and permits.

It is a good idea to plan your installation on paper, using exact measurements for clearances and floor protection, before actually beginning the installation

Consideration must be given to:

- Safety, convenience, traffic flow
- Placement of the chimney and chimney connector.
- If you are not using an existing chimney, place the appliance where there will be a clear passage for a factory-built listed chimney through the ceiling and roof.
- Installing an optional outside air kit would affect the location of the vent termination.

**NOTICE:** Locating the appliance in a location of considerable air movement can cause intermittent smoke spillage from appliance. Do not locate appliance near:

- Frequently open doors
- Central heat outlets or returns

Since pellet exhaust can contain ash, soot or sparks, you must consider the location of:

- Windows
- Air Intakes
- Air Conditioner
- Overhang, soffits, porch roofs, adjacent walls
- Landscaping, vegetation

When locating vent and venting termination, vent above roof line when possible.




Figure 2.1

## B. Tools And Supplies Needed

Tools and building supplies normally required for installation, unless installing into an existing masonry fireplace:

- Reciprocating Saw
  - Hammer
  - Phillips Screwdriver
  - Tape Measure
  - Level
  - Non-Combustible Sealant
  - Material
  - Gloves
  - Safety Glasses
  - Electric Drill & Bits
- May also need:**
- Vent Support Straps
  - Venting Paint

## C. Inspect Appliance and Components

- Carefully remove the appliance and components from the packaging.
- Report to your dealer any parts damaged in shipment, particularly the condition of the glass.
- **Read all of the instructions before starting the installation. Follow these instructions carefully during the installation to ensure maximum safety and benefit.**

### **DO NOT:**

- *Install or operate damaged appliance*
- *Modify appliance*
- *Install other than as instructed by Hearth & Home Technologies*
- *Operate the appliance without fully assembling all components*
- *Overfire*
- *Install any component not approved by Hearth & Home Technologies*
- *Install parts or components not Listed or approved.*
- *Disable safety switches*

*Improper installation, adjustment, alteration, service or maintenance can cause injury or property damage.*

*For assistance or additional information, consult a qualified installer, service agency or your dealer.*

This wood heater has a manufacturer-set minimum low burn rate that must not be altered. It is against federal regulations to alter this setting or otherwise operate this wood heater in a manner inconsistent with operating instructions in this manual.

This wood heater needs periodic inspection and repair for proper operation. It is against federal regulations to operate this wood heater in a manner inconsistent with operating instructions in this manual.



## WARNING



**RISK OF FIRE OR EXPLOSION!**

**DAMAGED PARTS COULD IMPAIR SAFE OPERATION. DO NOT install damaged, incomplete or substitute components. Keep appliance dry.**

Hearth & Home Technologies disclaims any responsibility for, and the warranty will be voided by the following actions:

- Installation and use of any damaged appliance or vent system component.
- Modification of the appliance or vent system.
- Installation other than as instructed by Hearth & Home Technologies.
- Installation and/or use of any component part not approved by Hearth & Home Technologies.

**Any such action may cause a fire hazard.**



## WARNING

**Risk of Fire, Explosion or Electric Shock! DO NOT use this appliance if any part has been under water. Call a qualified service technician to inspect the appliance and to replace any part of the control system which has been under water.**

# 3 Clearances

## A. Appliance Dimension Diagram

Dimensions are actual appliance dimensions. Use for reference only.




Figure 3.1

## B. Non-Combustible Materials Specification

Material which will not ignite and burn. Such materials are those consisting entirely of steel, iron, brick, tile, concrete, slate, glass or plasters, or any combination thereof.

Materials that are reported as passing **ASTM E 136, Standard Test Method for Behavior of Materials in a Vertical Tube Furnace at 750° C** and **UL763** shall be considered non-combustible materials.

## C. Combustible Materials Specification

Materials made of or surfaced with wood, compressed paper, plant fibers, plastics, or other material that can ignite and burn, whether flame proofed or not, or plastered or unplastered shall be considered combustible materials.

## D. Clearances to Combustibles

When selecting a location for the appliance it is important to consider the required clearances to walls (see Figure 3.2).



### WARNING


**RISK OF FIRE OR BURNS! Provide adequate clearance around air openings and for service access. Due to high temperatures, the appliance should be located out of traffic and away from furniture and draperies.**

**NOTICE:** Illustrations reflect typical installations and are FOR DESIGN PURPOSES ONLY. Actual installation may vary due to individual design preference.

Place the stove away from combustible walls at least as far as shown in Figure 3.2.

Note that the clearances shown are minimum for safety but do not leave much room for access when cleaning or servicing. Please take this into account when placing the stove.

When installing the unit into an alcove it is important to consider the required clearances listed below.



Min. Height = 42", Min. Width = 36, Max. Depth = 24"




Figure 3.2



### CAUTION

**THIS APPLIANCE MUST BE VENTED TO THE OUTSIDE.**

**NOTICE:** Clearances may only be reduced by means approved by the regulatory authority having jurisdiction.

Due to high temperatures, the stove should be placed away from traffic, furniture and draperies.

Children and adults should be alerted to the hazards of high surface temperatures and should stay away to avoid burns to skin and/or clothing.

Young children should be carefully supervised when they are in the same room as the stove.

Clothing and other flammable materials should not be placed on or near this unit.

## E. Floor Protection



### CAUTION

Hearth and Home Technologies does not recommend adhesive based vinyl flooring due to thermal expansion. Floating-style flooring (LVP - luxury vinyl plank or LVT - luxury vinyl tile) can be used, but it will reach temperatures up to 110 °F in a room with ambient temperature of 70 °F. Consult flooring specifications to ensure compatibility.

When using LVP/LVT flooring, HHT Recommends pellet stove and inserts have 29 inches of alternative flooring in front of the stove or insert before using LVP/LVT (luxury vinyl plank/tile flooring). Whether the stove or insert sits flush on the floor or is elevated on a raised hearth, 29 inches of alternative flooring is required in front of the stove or insert.

For all other flooring, continue to follow clearance to combustible requirements in the installation manual.

**NOTICE:** Clearances that do not meet the minimum guidelines could result in damage or buckling to the vinyl flooring and is done at the installer's risk.

### Parallel Installation:

Place the stove on a noncombustible floor or floor protector that extends a minimum of 6 inches (152mm) to the front of the load door opening, 6 inches (152mm) to the sides of the door opening, and 1 inches to the rear.

The minimum floor protector material is 20 gauge sheet metal (Not sold by Harman). **Note:** When using this method, installation of the included Bottom Heat Shield (1-00-777146) must be used. Other floor protector materials are ceramic tile, stone, brick, etc.

Minimum Size floor protection is 25-7/8" wide By 28" deep (658mm X 711mm). Figure 3.3

### Venting:

**US** - Follow PL vent manufacturers recommendations when configuring vent pipe installation.

**Canada** - Must extend 2" (51mm) beyond each side of any horizontal flue pipe.




Figure 3.3

Floor Protection Requirements		US	Canada
J	Sides	6"	152mm
K	Front	6"	152mm
L	Rear	1"	25mm

### Corner Installation:

Minimum size floor protection for a corner installation hearth pad is 25-7/8" Wide By 28" Deep (658mm X 711mm). **Note:** Floor protector **WILL NOT touch the wall using minimum clearances.**

If corner floor protection is desired to touch the wall, the floor protection will need to be at least 36" x 36" (914mm x 914mm).

**Note:** This will allow the floor protection to touch the wall as shown. Figure 3.4.

Alternate floor protector dimension may be used as long as they satisfy the measurement requirements shown below.




Figure 3.4

## F. Mobile Home Installation

When installing this unit in a mobile home, several requirements must be followed:

1. The unit must be bolted to the floor. This can be done using an appropriate fastener for the application.
2. The unit must be connected to an outside combustion air inlet. Proper supports and spark arresters must be considered when installing venting. See "Termination Location and Vent Information" Section D.
3. Floor protection and clearances must be followed as shown.
4. The appliance must be properly grounded to the frame of the mobile home using a minimum of 8 AWG copper solid or stranded, insulated or bare wire or equivalent.




Figure 3.5



# 4 Termination Location and Vent Information

## A. Vent Termination Minimum Clearances




Figure 4.1




Figure 4.2

**Note:** Follow venting manufacturer's recommendations for sealing pipe joints.

### #1 Preferred method (Figure 4.1)

This method provides excellent venting for normal operation and allows the stove to be installed closest to the wall. Two inches from the wall is safe; however, four inches allows better access to remove the rear panel. The vertical portion of the vent should be three to five feet high. This vertical section will help provide natural draft in the event of a power failure.

**Note:** Do not place joints within wall pass-through.

**THE CHIMNEY MUST BE OF A TYPE SUITABLE FOR SOLID-FUEL BURNING.**

 <b>WARNING</b>
<b>THE CHIMNEY AND CONNECTOR MUST BE MAINTAINED IN GOOD CONDITION AND KEPT CLEAN.</b>


 <b>CAUTION</b>
<b>DO NOT USE MAKE-SHIFT COMPROMISES WHEN INSTALLING THIS APPLIANCE. DAMAGE AND/OR INJURY MAY RESULT.</b>

### #2 Preferred method (Figure 4.2)

This method also provides excellent venting for normal operation but requires the stove to be installed farther from the wall. The vertical portion of the vent should be three to five feet high and at least 1" from a combustible wall. This vertical section will provide natural draft in the event of a power failure.

If the stove is installed below grade be sure the vent termination is at least 12" above grade (**with outside air only**). The outlet must also be 1 foot from the house/building.

**Note:** Do not place joints within wall pass-through.

 <b>CAUTION</b>
<b>Keep combustible materials (such as grass, leaves, etc.) at least 3 feet away from the flue outlet on the outside of the building.</b>




Figure 4.3

### #3 Installing into an existing chimney (Figure 4.3)

This method provides excellent venting for normal operation. This method also provides natural draft in the event of a power failure. If the chimney condition is questionable\* you may want to install a liner as in method #6.

In some places in the US and Canada it is required that the vent pipe extend all the way to the top of the chimney.

\*The chimney should be inspected and cleaned before installing your stove. If you discover that the chimney does not have a clay tile liner or has cracks or flaking of the tile liner you will need to install a stainless steel liner within the chimney. In most cases the inside diameter of this liner should be 4". Either flexible or rigid liner may be used for this purpose. *Refer to Method 5 & 6.*

Be sure to design the venting so that it can be easily cleaned.




Figure 4.4

### #4 Installing into an existing fireplace chimney (Figure 4.4)

This method provides excellent venting for normal operation. This method also provides natural draft in the event of a power failure. If the chimney condition is questionable\* you may want to install a liner as in method #5.

In some places in the US and Canada it is required that the vent pipe extend all the way to the top of the chimney.

\*The chimney should be inspected and cleaned before installing your stove. If you discover that the chimney does not have a clay tile liner or has cracks or flaking of the tile liner you will need to install a stainless steel liner within the chimney. In most cases the inside diameter of this liner should be 4". Either flexible or rigid liner may be used for this purpose. *Refer to Method 5 & 6.*

The chimney should be sealed at the damper using a steel plate. Kaowool, mineral wool or an equivalent non-combustible insulation is recommended to be installed on top of the sealing plate to reduce the possibility of condensation. The connector pipe should extend through the smoke chamber to the base or into the first flue tile.

Be sure to design the venting so that it can be easily cleaned.




Figure 4.5

#### #5 Installing into an existing fireplace chimney (Figure 4.5) w/Full Liner

This method provides excellent venting for normal operation. This method also provides natural draft in the event of a power failure.

In some places in the US and Canada it is required that the vent pipe extend all the way to the top of the chimney. The pipe or liner inside the chimney should be 4" diameter.

In this method a cap should also be installed on the chimney to keep out rain. Be sure to use approved pellet vent pipe fittings. Pipe size should be increased to 4" using this method.




Figure 4.6

#### #6 Installing into an existing chimney (Figure 4.6) w/Full liner

This method provides excellent venting for normal operation. This method also provides natural draft in the event of a power failure.

In some places in the US and Canada it is required that the vent pipe extend all the way to the top of the chimney. The pipe or liner inside the chimney should be 4" diameter.

In this method a cap should also be installed on the chimney to keep out rain.




Figure 4.7

**#7 Installing through the ceiling (Figure 4.7)**

Follow PL vent manufacturers recommendations when using wall and ceiling pass through.

**Note: Do not place joints within wall pass-through.**

<span style="font-weight: bold; font-size: 1.2em; vertical-align: middle;">CAUTION</span>
<p><b>DO NOT USE MAKESHIFT COMPROMISES WHEN INSTALLING THIS APPLIANCE. DAMAGE AND/OR INJURY MAY RESULT.</b></p>




Figure 4.8




Figure 4.9


**#8 Installing into an existing chimney using the Optional Top Vent option. (Figure 4.10)**

This method provides excellent venting for normal operation. This method also provides natural draft in the event of a power failure. If the chimney condition is questionable\* you may want to install a liner as in method #6.

In some places in the US and Canada it is required that the vent pipe extend all the way to the top of the chimney.



\*The chimney should be inspected and cleaned before installing your stove. If you discover that the chimney does not have a clay tile liner or has cracks or flaking of the tile liner you will need to install a stainless steel liner within the chimney.

Be sure to design the venting so that it can be easily cleaned.



**Figure 4.10**  
**Chimney Connectors**

- Follow venting manufacturer's recommendations for sealing pipe joints.



## B. Chimney Diagram




Figure 4.11

### Requirements for Terminating the Venting

#### **WARNING**

Venting terminals must not be recessed into a wall or siding.

#### **NOTE**

Only PL vent pipe wall pass-through and fire stops should be used when venting through combustible materials.

Always take into consideration the effect the prevailing wind direction or other wind currents will cause with flash and /or smoke when placing the termination.

In addition, the following must be observed:

- A. The clearance above grade must be a minimum of 12".
- B. The clearance to a window or door that may be opened must be a minimum of 48" to the side, 48" below the window/door, 12" above the window/door. **(with outside air installed, 12" to side and below)**
- C. A 12" clearance to a permanently closed window is recommended to prevent condensation on the window.
- D. The vertical clearance to a ventilated soffit located above the terminal within a horizontal distance of 2 feet (60 cm) from the center-line of the terminal must be a minimum of 18".
- E. The clearance to an unventilated soffit must be a minimum of 12".
- F. The clearance to an outside corner is 11" from center of pipe.
- G. The clearance to an inside corner is 12".
- H. A vent must not be installed within 3 feet (90 cm) above a gas meter/regulator assembly when measured from the horizontal center-line of the regulator.

- I. The clearance to service regulator vent outlet must be a minimum of 6 feet.
- J. The clearance to a non-mechanical air supply inlet to the building or the combustion air inlet to any other appliance must be a minimum of 48".
- K. The clearance to a mechanical air supply inlet must be a minimum of 10 feet. **(with outside air installed, 6 feet)**
- L. The clearance above a paved sidewalk or a paved driveway located on public property must be a minimum of 7 feet.
- M. The clearance under a veranda, porch, deck or balcony must be a minimum of 12 inches. **(B. also)**

#### **NOTE**

The clearance to vegetation and other exterior combustibles such as mulch is 36" as measured from the center of the outlet or cap. This 36" radius continues to grade.

Certain Canadian and or Local codes or regulations may require different clearances.

A vent shall not terminate directly above a side-walk or paved driveway which is located between two single family dwellings and serves both dwellings.

Only permitted if veranda, porch, deck, or balcony is fully open on a minimum of 2 sides beneath the floor.

**See NFPA 211 for more installation clearance reductions when using outside air.**

#### **NOTE**

Where passage through a wall, or partition of combustible construction is desired, the installation shall conform to CAN/CSA-B365. (if in Canada)

## C. Venting & Use of Elbows




Figure 4.12

Harman pellet stoves depend on a combustion fan to pull air through the unit for combustion. The venting system restricts the ability of the combustion fan to move the required amount of air through the unit. A system with too much resistance will result in incomplete combustion, more frequent required cleaning and poor unit performance. It is always best to choose a location for the appliance that will result in a venting system with the shortest equivalent vent length (EVL).

It is best to have your venting system designed by a Harman authorized dealer before you finalize your purchase of an appliance.

**Equivalent Vent Length: The equivalent vent length for common pellet vent components are:**

- 90° Elbows or Tee: 5 EVL Units
- 45° elbow: 3 EVL Units
- Vertical Pipe or Liner: ½ EVL Unit
- Horizontal Pipe or liner: 1 EVL Unit

**The total allowable equivalent vent length is:**

- 20 EVL for 3" pellet vent pipe or liner.
- 30 EVL for 4" pellet vent pipe or liner.

Due to the potential for fly ash accumulation in horizontal venting sections, the maximum permissible horizontal venting length is:

- 4 ft. for 3" & 4" pellet vent pipe.

### Example: First Floor Installation

A unit is to be installed using 3" Pellet Pipe with 3 feet of horizontal pipe, a Tee, 10 feet of vertical pipe, a 90° elbow and a termination cap.

**The equivalent vent length is:**

3 ft. of Horizontal Pipe (1 x 3 EVL)	= 3 EVL
90° Elbow or Tee (1 x EVL)	= 5 EVL
10 ft. of Vertical Pipe (10 x .5 EVL)	= 5 EVL
90° Elbow or Tee (1 x EVL)	= 5 EVL
<u>Termination Cap</u>	<u>= 0 EVL</u>
Equivalent Vent Length	= 18 EVL

In the example system detailed above, the EVL was 18 which is less than the maximum of 20 EVL for 3" pellet vent pipe, thus this is a satisfactory venting configuration.

### Example: Connection to Masonry Chimney

A unit is to be installed using 3" Pellet Pipe with 2 feet of horizontal pipe, a Tee, 4 feet of vertical pipe, an elbow, a Tee, 21 feet of vertical liner, and a termination cap.

**The equivalent vent length is:**


2 ft. of Horizontal Pipe (1 x 2 EVL)	= 2 EVL
90° Tee (1 x 5 EVL)	= 5 EVL
4 ft. of Vertical Pipe (4 x .5 EVL)	= 2 EVL
90° Elbow (1 x 5 EVL)	= 5 EVL
90° Tee (1 x 5 EVL)	= 5 EVL
21 ft. of Vertical Liner (21 x .5 EVL)	= 10.5 EVL
<u>Termination Cap</u>	<u>= 0 EVL</u>
Equivalent Vent Length	= 29.5 EVL

In the example system detailed above, the EVL was 29.5 which exceeds the maximum of 20 ft. for 3" pellet vent pipe, thus 3" vent pipe should not be used in this installation. However, since 4" pipe can support an EVL up to 30, the use of 4" pipe would create a satisfactory installation.

## C. Venting & Use of Elbows *continued*

**Note:** When the amount of vertical pellet vent pipe in the system exceeds 15 feet, 4" pellet vent pipe should be used.

**Note:** Equivalent Venting Length decreases as altitude increases.



### Example:

A unit with an EVL of 13, is to be installed at an altitude of 3,000 feet above sea level.

From the chart to the left, at 3,000 feet of altitude, the maximum permissible equivalent venting length is 26 feet. Therefore this would be an acceptable installation with no need to change the combustion blower fan.

However, if the same unit (EVL 13) was to be installed an altitude of 9,000 feet above sea level, the installation would no longer be acceptable and the equivalent vent length of the pipe would have to be reduced for proper unit operation.

- Long runs of flex or PL vent pipe installed directly vertical from the flue stub may require more frequent cleaning due to fly ash falling off inside and collecting directly above the combustion blower outlet.
- 4" stainless steel flex vent piping is only allowed for use in masonry fireplaces and chimneys or factory built wood-burning fireplaces with Class A metal chimneys.
- All pellet vent pipe must be secured together either by means provided by pipe manufacturer or by 3 screws at each joint.
- Use only the specified venting components. Use of any other components will void the product warranty and may pose a hazard.
- Do Not Install a Flue Damper In The Exhaust Venting System of This Appliance.
- DO NOT CONNECT THIS UNIT TO A CHIMNEY FLUE SERVING ANOTHER APPLIANCE.
- Simpson DuraVent PelletVent Pro Harman®Adapter Part #3PVP-ADHB and PelletVent Pro Harman®Adapter Increaser Part #3PVPX4ADHB are highly recommended to be installed on the starter collar to insure a proper pipe connection to the unit.
- **INSTALL VENT AT CLEARANCES SPECIFIED BY THE VENT MANUFACTURER**
- Use silicone to create an effective vapor barrier at the location where the chimney or outside air ducting passes through to the exterior of the structure



## D. Outside Air




Figure 4.13




Figure 4.14




Figure 4.15

### Outside Air:

**Hearth & Home Technologies recommend attaching outside air in all installations, especially lower level and main floor locations.**

Per national building codes, consideration must be given to combustion air supply to all combustion appliances. Failure to supply adequate combustion air for all appliance demands, may lead to back-drafting of those and other appliances.

When the appliance is side-wall vented: The air intake is best located on the same exterior wall as the exhaust vent outlet and located lower on the wall than the exhaust vent outlet.

When the appliance is roof vented: The air intake is best located on the exterior wall oriented towards the prevailing wind direction during the heating season.

The outside air connection will supply the demands of the pellet appliance, but consideration must be given to the total house demand. House demand may consume some air needed for the stove, especially during a power failure. It may be necessary to add additional ventilation to the space in which the pellet appliance is located. Consult with your local HVAC professional to determine the ventilation demands for your house.

To install outside air use 3" non-combustible flex pipe Figure 4.14. There is a break-away hole on the rear panel of the Absolute43-C stove which must be removed before connecting the flex pipe. Figure 4.13. The pipe should be run outside and terminate to the side or below the vent pipe outlet so the flue outlet is more than 12" from the inlet cover. The Termination Cap should be used to keep birds, rodents, etc. out of the pipe Figure 4.14.

You may choose to use the optional Direct Vent Wall Pass-through Kit which incorporates the venting pass-through and outside air inlet into one component. Figure 4.15.

## E. Locating Your Appliance & Chimney

Location of the appliance and chimney will affect performance.

- Install through the warm airspace enclosed by the building envelope. This helps to produce more draft, especially during lighting and die-down of the fire.
- Penetrate the highest part of the roof. This minimizes the effects of wind loading.
- Locate termination cap away from trees, adjacent structures, uneven roof lines and other obstructions.
- Minimize the use of chimney offsets.
- Consider the appliance location relative to floor and ceiling and attic joists.



### CAUTION

- DO NOT CONNECT THIS UNIT TO A CHIMNEY FLUE SERVICING ANOTHER APPLIANCE.
- DO NOT CONNECT TO ANY AIR DISTRIBUTION DUCT OR SYSTEM.

May allow flue gases to enter the house

## F. Draft

Draft is the pressure difference needed to vent appliances successfully. When an appliance is drafting successfully, all combustion byproducts are exiting the home through the chimney.

Considerations for successful draft include:

- Negative pressure in the firebox
- Location of appliance and chimney

To measure the draft or negative pressure on your appliance use a manometer or a digital pressure gauge capable of reading 0 - 1 inches of water column (W.C.).

The appliance should be running on high for at least 15 minutes for the test.

With the stove running on high you should have a negative pressure equal to or greater than the number given in the chart below. If you have a lower reading than you find on the chart, your appliance does not have adequate draft to burn the fuel properly.

<b>Minimum Vacuum Requirements:</b>	<b>.20 - .25</b>
-------------------------------------	------------------

Prior to installing the flue pipe, connect a draft meter. (The draft meter must have a minimum range of 0 - .5") Record the first reading. Connect flue pipe to stove and be sure all doors and windows in the home are closed. Record the second draft reading \_\_\_\_\_. If the second reading is more than .05" lower than the first reading, check for possible restrictions or the need for outside air. For more information on the draft test procedure, refer to "Appliance Set-Up" Section C.

## G. Negative Pressure



### WARNING

**Risk of Asphyxiation!** Negative pressure can cause spillage of combustion fumes and soot.

Negative pressure results from the imbalance of air available for the appliance to operate properly. It can be strongest in lower levels of the house.

Causes include:

- Exhaust fans (kitchen, bath, etc.)
- Range hoods
- Combustion air requirements for furnaces, water heaters and other combustion appliances
- Clothes dryers
- Location of return-air vents to furnace or air conditioning
- Imbalances of the HVAC air handling system
- Upper level air leaks such as:
  - Recessed lighting
  - Attic hatch
  - Duct leaks

To minimize the effects of negative air pressure:

- Install the outside air kit with the intake facing prevailing winds during the heating season
- Ensure adequate outdoor air for all combustion appliances and exhaust equipment
- Ensure furnace and air conditioning return vents are not located in the immediate vicinity of the appliance
- Avoid installing the appliance near doors, walkways or small isolated spaces
- Recessed lighting should be a "sealed can" design
- Attic hatches weather stripped or sealed
- Attic mounted duct work and air handler joints and seams taped or sealed

### NOTICE

HEARTH & Home Technologies assumes no responsibility for the improper performance of the chimney system caused by:

- Inadequate draft due to environmental conditions
- Downdrafts
- Tight sealing construction of the structure
- Mechanical exhausting devices

## H. Avoiding Smoke and Odors

### Negative Pressure, Shut-down, and Power Failure:

**To reduce the probability of back-drafting or burn-back in the pellet burning appliance during power failure or shut-down conditions, the stove must be able to draft naturally** without exhaust blower operation. Negative pressure in the house will resist this natural draft if not accounted for in the pellet appliance installation.

Heat rises in the house and leaks out at upper levels. This air must be replaced with cold air from outdoors, which flows into lower levels of the house. Vents and chimneys into basements and lower levels of the house can become the conduit for air supply, and reverse under these conditions.

### Outside Air

An outside air kit is recommended in all installations. The Outside Air Kit must be ordered separately.

Per national building codes, consideration must be given to combustion air supply to all combustion appliances. Failure to supply adequate combustion air for all appliance demands may lead to back drafting of those and other appliances.

When the appliance is roof vented (strongly recommended):

The air intake is best located on the exterior wall oriented towards the prevailing wind direction during the heating season.

When the appliance is side-wall vented:

The air intake is best located on the same exterior wall as the exhaust vent outlet and located lower on the wall than the exhaust vent outlet.

The outside air supply kit can supply most of the demands of the pellet appliance, but consideration must be given to the total house demand.

House demand may consume the air needed for the appliance. It may be necessary to add additional ventilation to the space in which the pellet appliance is located.

Consult with your local HVAC professional to determine the ventilation demands for your house.

### Vent Pipe

Be sure to use approved pellet vent pipe wall and ceiling pass-through fittings to go through combustible walls and ceilings. Be sure to use a starting collar to attach the venting system to the stove. The starting collar must be secured to the flue stub with at least three screws, and sealed with high temp silicone caulking.

4" stainless steel flex vent piping is only allowed for use in masonry fireplaces and chimneys or factory built wood-burning fireplaces with class A metal chimneys.

Pellet venting pipe is constructed of two layers with air space between the layers. This air space acts as an insulator and reduces the outside surface temperature to allow a clearance to combustibles of only 1 inch. The sections of pipe lock together to form an air tight seal. Follow venting manufacturer's recommendations for sealing pipe joints.

Where passing through an exterior wall or roof, use silicone to maintain an effective vapor barrier at the location where the chimney or component penetrates to the exterior of the structure.

### Vent Configurations:

To reduce probability of reverse drafting during shut-down conditions, Hearth & Home Technologies strongly recommends:

- Installing the pellet vent with a minimum vertical run of five feet, preferably terminating above the roof line.
- Installing the outside air intake at least four feet below the vent termination.

To prevent soot damage to exterior walls of the house and to prevent re-entry of soot or ash into the house:

- Maintain specified clearances to windows, doors, and air inlets, including air conditioners.
- Vents should not be placed below ventilated soffits. Run the vent above the roof.
- Avoid venting into alcove locations.
- Vents should not terminate under overhangs, decks or onto covered porches.
- Maintain minimum clearance of 12 inches from the vent termination to the exterior wall. If you see deposits developing on the wall, you may need to extend this distance to accommodate your installation conditions.

**Hearth & Home Technologies assumes no responsibility for, nor does the warranty extend to, smoke damage caused by reverse drafting of pellet appliances under shut-down or power failure conditions.**

## I. Fire Safety

To provide reasonable fire safety, the following should be given serious consideration:

- Install at least one smoke detector and CO detector on each floor of your home. The National Fire Protection Association (NFPA), recommends one Smoke Alarm on every floor, in every sleeping area, and in every bedroom.
- Locate smoke detector away from the heating appliance and close to the sleeping areas.
- Follow the smoke detector manufacturer's placement and installation instructions and maintain regularly.
- Conveniently locate a Class A fire extinguisher to contend with small fires.
- In the event of a hopper fire:
  - Evacuate the house immediately.
  - Notify fire department.

## J. Inspect Appliance & Components

- Remove appliance and components from packaging and inspect for damage.
- Report to your dealer any parts damaged in shipment.
- **Read all the instructions before starting the installation. Follow these instructions carefully during the installation to ensure maximum safety and benefit.**



### WARNING



Inspect appliance and components for damage. Damaged parts may impair safe operation.

- Do NOT install damaged components.
- Do NOT install incomplete components.
- Do NOT install substitute components.

Report damaged parts to dealer.

# 5 Appliance Set-Up

## A. Unpacking

The Absolute43-C is bolted (1/4 x 1" hex head bolts) to the skid to prevent movement during shipping.

To free the stove from the skid you must remove the hold-down bolts from both the left and right hand side shipping brackets using a 7/16" socket or wrench. Figure 5.1.




Figure 5.1

## B. Firebox Draft and Combustion Fan RPM

These units are pre-tested at the factory with exactly 120 VAC, 60 Hz. They are checked and adjusted for firebox tightness, gasket leakage, motor operation and igniter operation. The Allure50 is then factory set at a mid-point adjustment and in most cases will not need any adjustments.

Check and record the firebox draft before installing venting and after venting is installed (**before starting fire**).

There is a draft meter port located in the back of the unit where draft can be measured. Install the magnahelic meter (capable of at least .5" of water column) Figure 5.2.

Connect the power cord to a 120 VAC, 60Hz grounded receptacle. (A surge protector is recommended to protect the circuit board.) Also be sure that the polarity of the outlet that the stove is plugged into is correct.

Go to the "Home Screen", the power icon should be gray. Press menu, on the first menu page press "test" icon.

The test page has 4 component test modes. The second icon is for the combustion fan test.

One press of the icon turns the combustion fan to full line voltage. (**Note: During this test, the combustion fan will not achieve its top RPM of 3200 due to the density of the ambient air.**) All RPM displays could vary +/- 50 from that of the set RPM's. Allow several minutes for the fan motor to warm up.

Press the icon a second time, the combustion fan will go to "Maximum" (as set in the **Authorized Dealer Only** area under the combustion fan icon)




Figure 5.2

The "Maximum" is factory set at 3100 RPM. Allow the RPM to stabilize and record the firebox draft Maximum.

Before Install: \_\_\_\_\_ IWC

After Install: \_\_\_\_\_ IWC

### (Firebox Draft and Combustion Fan RPM Cont.)

Press the icon a third time, the combustion fan will go to "Minimum" (as set in the **Authorized Dealer Only** area under the combustion fan icon) allow the RPM to stabilize and record the firebox draft minimum.

Before Install: \_\_\_\_\_ IWC

After Install: \_\_\_\_\_ IWC

### Cold Stove Draft:

2400 RPM      Low -.20 and -.25

3100 RPM      High -.45 and -.50

Leaving the test page will end any tests in progress and goes back to whatever mode of operation it was set to on the home page.

If the unit is not adjusted properly, it does not cause a safety concern. If the unit is adjusted too high, only efficiency is lost. If the unit is adjusted too low, the low draft pressure switch will not allow the feed motor or the igniter to operate.

## C. Wireless Room Sensor

The Wireless Room Sensor was exclusively designed to communicate with the EASY Touch Controls on Harman pellet products. Simply place the wireless sensor up to 30 feet away, and enjoy the warmth of pellet heat exactly where you want it. The Wireless Room Sensor mounts on a wall wherever you want your heat measured.

The Wireless Room Sensor keeps your space within 1 degree of your set temperature. Simply sync to your EASY Touch Control (which takes about 20 seconds) and install with the provided screws.

### Smart Features:

- After a power outage, the wireless room sensor resets the controls to the current time, allowing your heat schedule to resume automatically.
- Communicates to the EASY Touch Control every 17 seconds, keeping your set temperature as accurate as possible, all day, every day.
- Easily mount up to 30 feet away from the stove or insert on any interior wall (mounting hardware included).
- We provide two AA batteries with a life expectancy of more than a year.
- Track connection strength and battery levels on EASY Touch Control Diagnostic page 6 (Located on unit).
- Low Battery Warning messages will be seen on the home screen.
- If connection is lost due to a dead battery the stove continues operation by automatically switching to its back-up sensor when the batteries are dead, and will display a “replace batteries” message on the home screen of the EASY Touch Control).

The Wireless Room Sensor has light indicators to communicate the following:

- A green LED flashes when good communication is made to the display.
- An amber LED flashes when searching.
- A red LED flashes when searching in energy saving mode – this may occur when the appliance has been unplugged, or is experiencing an extended power loss.

## D. Flame Guide

Install the cast iron flame guide on top of the burn pot. Make sure that the flame guide is fully seated on the vertical sides of the burn pot and that the back of the guide rests against the body of the stove. Figure 5.3.




Figure 5.3

# 6 Reference Material

## A. Safety Reminders

When installing and operating your Harman® Absolute43-C, respect basic safety standards. Read these instructions carefully before you attempt to install or operate the Absolute43-C. Failure to do so may result in damage to property or personal injury and may void the product warranty.

Consult with your local building code agency and insurance representative before you begin your installation to ensure compliance with local codes, including the need for permits and follow-up inspections.

Due to high temperatures, this stove should be placed out of traffic and away from furniture and draperies.

Children and adults should be alerted to the hazards of high surface temperatures and should stay away to avoid burn to skin and/or clothing.

Young children should be carefully supervised when they are in the same room as the stove.

Clothing and other flammable materials should not be placed on or near this stove.

Installation and repair of this stove should be done by a qualified service person. The appliance should be inspected before use and at least annually by a qualified service person. More frequent cleaning may be required. It is imperative that control compartments, burners, and circulating air passageways of this stove be kept clean.

 **WARNING**

**MOBILE/MANUFACTURED HOME GUIDELINES DO NOT ALLOW INSTALLATION IN A SLEEPING ROOM.**

 **CAUTION**

**THE STRUCTURAL INTEGRITY OF THE MOBILE HOME FLOOR, WALL, AND CEILING/ROOF MUST BE MAINTAINED.**

 **WARNING**

**KEEP COMBUSTIBLE MATERIALS SUCH AS GRASS, LEAVES, ETC. AT LEAST 3 FEET AWAY FROM THE POINT DIRECTLY UNDER THE VENT TERMINATION.**

 **WARNING**

**USE OF IMPROPER FUELS, FIRE STARTERS OR ALTERING THE STOVE FOR HIGHER HEAT OUTPUT MAY CAUSE DAMAGE TO THE STOVE AND COULD RESULT IN A HOUSE FIRE. USE ONLY APPROVED FUELS AND OPERATION GUIDELINES**

 **CAUTION**

**This appliance must be vented to the outside.**

 **CAUTION**

**THE STOVE IS HOT WHILE IN OPERATION. KEEP CHILDREN, CLOTHING AND FURNITURE AWAY. CONTACT MAY CAUSE SKIN BURNS.**





Harman®, a brand of Hearth & Home Technologies Inc.  
352 Mountain House Road, Halifax, PA 17032  
[www.harmanstoves.com](http://www.harmanstoves.com)

Please contact your Harman® dealer with any questions or concerns.  
For the location of your nearest Harman® dealer,  
please visit [www.harmanstoves.com](http://www.harmanstoves.com).

*Printed in U.S.A. - Copyright 2015*

# Owner's Manual

## Care and Operation

**INSTALLER:** Leave this manual with party responsible for use and operation.

**OWNER:** Retain this manual for future reference.

Contact your local dealer with questions on installation, operation or service.


**NOTICE: SAVE THESE INSTRUCTIONS**

# HARMAN®

**BUILT TO A STANDARD, NOT A PRICE**

**Model(s):**

**Absolute43-C  
Freestanding Pellet Stove**



### CAUTION

Tested and approved for wood pellet fuel only. Burning of any other type of fuel voids your warranty.

Installation and service of this appliance should be performed by qualified personnel. Hearth & Home Technologies recommends HHT Factory Trained or NFI certified professionals.



### WARNING



Please read this entire manual before installation and use of this pellet fuel-burning room heater.

Failure to follow these instructions could result in property damage, bodily injury or even death.

- Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
- Do not overfire - If any external part starts to glow, you are overfiring. Reduce feed rate. Overfiring will void your warranty.
- Comply with all minimum clearances to combustibles as specified. Failure to comply may cause house fire.

### WARNING



#### HOT SURFACES!

Glass and other surfaces are hot during operation AND cool down.

**Hot glass will cause burns.**

- Do not touch glass until it is cooled
  - NEVER allow children to touch glass
  - Keep children away
  - CAREFULLY SUPERVISE children in same room as stove.
  - Alert children and adults to hazards of high temperatures.
- High temperatures may ignite clothing or other flammable materials.**
- Keep clothing, furniture, draperies and other flammable materials away.

### NOTE

To obtain a French translation of this manual, please contact your dealer or visit [www.harmanstoves.com](http://www.harmanstoves.com)

Pour obtenir une traduction française de ce manuel, s'il vous plaît contacter votre revendeur ou visitez [www.harmanstoves.com](http://www.harmanstoves.com)

**Read this manual before operating this appliance.  
Please retain this Owner's Manual for future reference.  
Read the Installation Manual before making any installation or finishing changes.**

**Congratulations,** The Harman® Absolute43-C pellet stove you have selected is designed to provide the utmost in safety, reliability, and efficiency.

As the owner of a new pellet stove, you'll want to read and carefully follow all of the instructions contained in this owner's manual. Pay special attention to all cautions and warnings.

This owner's manual should be retained for future reference. We suggest that you keep it with your other important documents and product manuals.

Your new Harman® Absolute43-C Freestanding Pellet Stove will give you years of durable use and trouble-free enjoyment. Welcome to the Harman® family!

Harman® is a registered trademark of Hearth & Home Technologies.

**Note: Cast iron is an artisan crafted material, which is made the same way today as nearly 2000 years ago. Due to the intrinsic primitive nature of the casting process, part to part variation is normal and adds to the character of a hand built cast iron appliance**

**Listing Label Information/Location**      The model information regarding your specific stove can be found on the rating plate usually located in the control area of the stove.

**Model Name**      **Serial Number**

**MODEL / MODÈLE: "Absolute43-C"**

**Report / Rapport #013SPS039E, 013SPS032S**  
Test / testé à ASTM E 1509-12, ULC-S627-00, ASTM E 2515-11, ASTM E 2779-10  
Room Heater, Pellet Fuel-Burning Type, Also For Use in Mobile Homes. (UJI) 84-4HD

**"PREVENT HOUSE FIRES"** Install and use only in accordance with manufacturer's installation and operation instructions.

**WARNING: FOR MANUFACTURED HOMES:** Do not install appliance in a sleeping room. An outside combustion air inlet must be provided. The structural integrity of the manufactured home floor, ceiling and walls must be maintained. Refer to manufacturer's instructions and local codes for precautions required for passing chimney through a combustible wall or ceiling. Inspect and clean exhaust venting system frequently in accordance with manufacturer's instructions. Use a 3" or 4" diameter type "L" or "PL" venting system.

Do not connect this unit to a chimney flue servicing another appliance.  
Do not obstruct the space beneath the heater.

**FOR USE WITH PELLETIZED WOOD FUEL ONLY.**  
EPA Certified Emissions: 39 g/hr  
**Input Rating Max:** 5.0 lb. fuel/hr  
**Electrical Rating:** 240 VAC, 50 Hz, Start 1.75 AMPS, Run 1.25 AMPS  
**U.S. Electrical Rating:** 115 VAC, 60 Hz, Start 3.5 AMPS, Run 2.5 AMPS  
Fuel Type: Wood Pellet ONLY  
Route power cord away from unit.

**OPERATE ONLY WITH DOORS CLOSED**  
**DANGER:** Risk of electrical shock. Disconnect power supply before service.  
Replace glass only with 5mm ceramic available from your dealer.  
For further instruction refer to owner's manual.  
Keep viewing and ash removal doors tightly closed during operation.

**MINIMUM CLEARANCES TO COMBUSTIBLES**  
Back Wall to Appliance 2"  
Side Wall to Appliance 6"

**Corner Installation**  
Walls to Appliance 6.25"  
Use a non-combustible floor protector extending under and to the sides, front and back of the unit as shown in floor protection diagram. Measure front distance from the surface of the glass door.

**Recommended: Non-combustible floor protection extended beneath the flue pipe when installed with horizontal venting.**

**Floor Protection\***

USA	CANADA
Sides (A) 6"	152 mm
Back (B) 11"	25 mm
Front (C) 6"	152 mm

**Alcove Installation**  
Min. Alcove Height 42" (1067mm)  
Max. Alcove Depth 24" (610mm)

**US ENVIRONMENTAL PROTECTION AGENCY**  
The Absolute43-C is Certified to comply with the emission standards.  
L'Absolute43-C est certifié conforme aux normes de protection de l'environnement de 2020.

**Model Name**      **Serial Number**

**Modèle: "Absolute43-C"**  
Appareil de chauffage à granulés de bois  
CONÇU POUR MAISONS MOBILES

Test pour / testé à la norme ASTM E 1509-12, ULC-S627-00, ASTM E 2515-11, ASTM E 2779-10  
Chaudière à granulés de bois  
Conçu pour maisons mobiles

**DANGER:** Risque d'électrocution. Coupez l'alimentation électrique avant l'entretien.  
Remplacez le verre avec 5 mm miroir verre céramique de la même qualité disponible auprès de votre revendeur.  
En tenant la porte d'entrée et le couvercle de la trémie hermétiquement fermés pendant le fonctionnement de l'appareil.

**Précautions préfabriquées:** Ne pas installer l'appareil dans une chambre à coucher. Une entrée d'air extérieur doit être fournie. L'intégrité structurelle du toit, du plancher et des murs fabriqués doit être maintenue. Consultez les instructions du fabricant et les codes locaux pour les précautions nécessaires pour faire passer la cheminée à travers un mur ou un plafond combustible. Inspectez et nettoyez le système d'évacuation souvent en conformité avec les instructions du fabricant.

Utilisez un "ou 4" Type de diamètre «L» 3 ou le système de ventilation "PL".

Ne pas connecter cet appareil à un conduit de cheminée desservant un autre appareil.  
**Ne pas obstruer l'espace sous le chauffe-eau.**  
**À UTILISER AVEC LA GRANULE DE BOIS SEULEMENT.**  
Emissions certifiées EPA: 39 g / h  
**Entrée Max Note:** E 5.0 carburant / h  
**Note électrique:** 240 VAC, 50 Hz, Lancer 1,75 AMPS, Exécuteur 1,25 AMPS  
**US Note électrique:** 115 VAC, 60 Hz, 3.5 AMPS Démarreur, Exécuteur 2.5 AMPS  
Type de carburant: Bois Pellet SEULEMENT  
Route cordon électrique de l'appareil.  
**Fonctionner uniquement avec les portes fermées**  
Ce poêle à bois a besoin d'une inspection et d'une réparation périodiques pour fonctionner correctement. Consultez le manuel du propriétaire pour plus d'informations. Il est contraire à la réglementation fédérale d'utiliser ce poêle à bois d'une manière non conforme aux instructions d'utilisation du manuel du propriétaire.

**DISTANCES DE SECURITE PAR RAPPORT AUX MATERIAUX COMBUSTIBLES**

Paroi arrière à l'appareil	51 mm
Paroi latérale de l'appareil	152 mm
<b>Installation en angle</b> Entre murs et appareil	159 mm
<b>Installation en alcôve</b> Hauteur minimale de l'alcôve	1067 mm
Profondeur maximale de l'alcôve	610 mm

**PROTECTION DU SOL\***  
Côtés (A) 152 mm  
Arrière (B) 25 mm  
Avant (C) 152 mm

Utiliser une protection de sol non combustible sous l'appareil qui s'étend sur les côtés, l'avant et l'arrière du poêle (voir schéma). Pour la distance à l'avant, mesurer à partir de la surface de la porte en verre.

Il est recommandé que la protection s'étende jusque sous le conduit en cas d'installation d'un conduit horizontal ou sous le té en cas conduit vertical.

**Do not remove this label/Ne pas enlever cette étiquette.**  
Made in the USA/Fabrique aux E.-U.

**Date of Manufacture / Date de fabrication:**  
2021 2022 2023 JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC

**Manufactured by / Fabriqué par: Hearth and Home Technologies 352 Mountain House Road, Halifax PA 17032**

## **🔊 Safety Alert Key:**

- **DANGER!** Indicates a hazardous situation which, if not avoided **will** result in death or serious injury.
- **WARNING!** Indicates a hazardous situation which, if not avoided **could** result in death or serious injury.
- **CAUTION!** Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
- **NOTICE:** Used to address practices not related to personal injury.

## **Table of Contents**

### **1 Product Specifications and Important Safety Information**

A. Appliance Certification . . . . .	4
B. Glass Specifications . . . . .	4
C. Mobile Home Approvals . . . . .	4
D. BTU Specifications . . . . .	4
E. Electrical Codes . . . . .	4

### **2 Important Safety and Operating Information**

A. Appliance Safety . . . . .	5
B. Clear Space . . . . .	6
C. California Safety Information . . . . .	6
D. Helpful Hints . . . . .	6
E. Fuel Specifications . . . . .	7
F. Quick Start Guide . . . . .	8
G. Frequently Asked Questions . . . . .	9
H. Fire Safety . . . . .	9
I. Cleaning Prompts, Messages and Errors . . . . .	10

### **3 Maintenance and Service**

A. Proper Shutdown Procedure . . . . .	11
B. Quick Reference Maintenance Chart . . . . .	12
C. Unit Maintenance . . . . .	13
• Daily/Weekly Maintenance . . . . .	13
• Monthly Maintenance . . . . .	13
• Yearly Maintenance . . . . .	14

### **4 Reference Materials**

→ A. Service Parts . . . . .	16
B. Limited Lifetime Warranty . . . . .	21
C. Loss of Power . . . . .	23
D. Emergency Manual Ignition . . . . .	23
E. Troubleshooting . . . . .	24
F. Contact Information . . . . .	26

**→ = Contains updated information**

# 1 Product Specific and Important Safety Information

## A. Appliance Certification

<b>MODEL:</b>	Absolute43-C Pellet Stove
<b>LABORATORY:</b>	OMNI Test Laboratories, Inc
<b>REPORT NO.</b>	0135PS039E, 0135PS032S
<b>TYPE:</b>	Pellet Fueled/Supplementary For Residential Use
<b>STANDARD(s):</b>	ASTM E 1509-12, ULC-S627-00, ASTM E 2515-11, ASTM E 2779-10
<b>ELECTRICAL RATING:</b>	120 VAC, 60 Hz, Start 4.0 Amps, Run 3.0 Amps
<b>GLASS SPECIFICATION:</b>	5mm mirrored ceramic glass

The Absolute43-C is Certified to comply with 2020 particulate emission standards.



**NOTE:** This installation must conform with local codes. In the absence of local codes you must comply with the **ASTM E1509-2004, ULC S628-93, (UM) 84-HUD**

## B. Glass Specifications

This appliance is equipped with 5mm mirrored ceramic glass. Replace glass only with 5mm mirrored ceramic glass. Please contact your dealer for replacement glass.

## C. Mobile Home Approved

This appliance is approved for mobile home installations when not installed in a sleeping room and when an outside combustion air inlet is provided.

The structural integrity of the mobile home floor, ceiling, and walls must be maintained. The appliance must be properly grounded to the frame of the mobile home and use only listed pellet vent, Class "PL" connector pipe.

**A Harman® Outside Air Kit must be installed in a mobile home installation.**



### WARNING

**THE STRUCTURAL INTEGRITY OF THE MANUFACTURED HOME FLOOR, WALL, AND CEILING/ROOF MUST BE MAINTAINED.**

**DO NOT INSTALL IN SLEEPING ROOM.**

## D. BTU & Efficiency Specifications

<b>EPA Certification Number:</b>	126-18
<b>EPA Certified Emissions:</b>	.99 g/hr
<b>*LHV Tested Efficiency:</b>	82.3%
<b>**HHV Tested Efficiency:</b>	77%
<b>***EPA BTU Output:</b>	34,800 - 10,600
<b>****BTU Input</b>	44,200 - 14,100
<b>Vent Size:</b>	3 Inch
<b>Hopper Capacity:</b>	52 lbs
<b>Fuel</b>	Wood Pellet

\* *Weighted average LHV efficiency using data collected during EPA emissions test.*

\*\* *Weighted average HHV efficiency using data collected during EPA emissions test.*

\*\*\* *A range of BTU outputs based on EPA Default Efficiency and the burn rates from the low and high EPA tests.*

\*\*\*\* *Based on the maximum feed rate per hour multiplied by approximately 8600 BTU's which is the average BTU's from a pound of pellets.*

This wood heater has a manufacturer-set minimum low burn rate that must not be altered. It is against federal regulations to alter this setting or otherwise operate this wood heater in a manner inconsistent with operating instructions in this manual.

This wood heater needs periodic inspection and repair for proper operation. It is against federal regulations to operate this wood heater in a manner inconsistent with operating instructions in this manual.

## E. Electrical Codes

120 VAC, 60 Hz, Start 4.0 Amps, Run 3.0 Amps

**Notice:** *This appliance must be electrically wired and grounded in accordance with local codes or, in the absence of local codes, with National Electric Code ANSI/NFPA 70-latest edition or the Canadian Electric Code CSA C22.1.*

**NOTE:** Some generator or battery back-up systems may not be compatible with the micro-processor electronics on this appliance. Please consult the power supply manufacturer for compatible systems.

**NOTE:** Hearth & Home Technologies, manufacturer of this appliance, reserves the right to alter its products, their specifications and/or price without notice.

## 2 Important Safety and Operating Information

### A. Appliance Safety

#### WARNING

If you expect that small children or vulnerable adults may come into contact with this appliance, the following precautions are recommended:

- Install a physical barrier such as:
  - A decorative fire screen.
  - Adjustable safety gate.
- Never leave children alone near a hot stove, whether operating or cooling down.
- Teach children to **NEVER** touch the stove.
- Consider not using the stove when children will be present.
- Use only specified components as replacement parts. Other components may not allow your stove to operate as it was intended.

Contact your dealer for more information, or visit: [www.hpba.org/safety-information](http://www.hpba.org/safety-information).

To prevent unintended operation when not using your stove for an extended period of time (summer months, vacations, trips, etc):

- Unplug stove from receptacle.

Due to high temperatures, this stove should be placed away from traffic, furniture and draperies.

Children and adults should be alerted to the hazards of high surface temperatures and should stay away to avoid burns to the skin and/or clothing.

Young children should be carefully supervised when they are in the same room as the stove.

Clothing and other flammable materials should not be placed on or near this stove.

Installation and repair of this stove should be done by a qualified service person. The appliance should be inspected before use and at least annually by a qualified service person. More frequent cleaning will be required. It is imperative that control compartments and circulating air passageways of this stove be kept clean.

#### CAUTION

**This appliance must be vented to the outside**

#### DO NOT:

- *Install or operate damaged appliance*
- *Modify appliance*
- *Install other than as instructed by Hearth & Home Technologies*
- *Operate the appliance without fully assembling all components*
- *Overfire*
- *Install any component not approved by Hearth & Home Technologies*
- *Install parts or components not Listed or approved.*
- *Disable safety switches*

*Improper installation, adjustment, alteration, service or maintenance can cause injury or property damage.*

*For assistance or additional information, consult a qualified installer, service agency or your dealer.*

Connect the power cord into a 120 VAC, 60 Hz grounded receptacle. (A surge protector is recommended to protect the circuit board.) Be sure the polarity of the outlet the stove is plugged into is correct.

#### WARNING

**THIS WOOD HEATER HAS A MANUFACTURER-SET MINIMUM LOW BURN RATE THAT MUST NOT BE ALTERED. IT IS AGAINST FEDERAL REGULATIONS TO ALTER THIS SETTING OR OTHERWISE OPERATE THIS WOOD HEATER IN A MANNER INCONSISTENT WITH OPERATING INSTRUCTIONS IN THIS MANUAL.**

#### CAUTION

Check building codes prior to installation.

- Installation **MUST** comply with local, regional, state and national codes and regulations.
- Contact local building or fire officials about restrictions and installation inspection requirements in your area.

#### WARNING

***Risk of Fire, Explosion or Electric Shock! DO NOT use this appliance if any part has been under water. Call a qualified service technician to inspect the appliance and to replace any part of the control system which has been under water.***

## B. Clear Space



### WARNING

**RISK OF FIRE!** Do NOT place combustible objects in front or to the sides of the appliance. High temperatures may ignite clothing, furniture or draperies.

**NOTICE:** Clearances may only be reduced by means approved by the regulatory authority having jurisdiction.



### WARNING

**RISK OF FIRE!** Keep combustible materials, gasoline and other flammable vapors and liquids clear of appliance.

- Do **NOT** store flammable materials in the appliance's vicinity.
- Do **NOT** use gasoline, lantern fuel, kerosene, charcoal lighter fluid or similar liquids to start or "freshen up" a fire in this heater.

Keep all such liquids well away from the heater while it is in use as combustible materials may ignite.



### WARNING

**MOBILE/MANUFACTURED HOME GUIDELINES: DO NOT ALLOW INSTALLATION IN A SLEEPING ROOM.**

## C. California Safety Information



### WARNING

This product and the fuels used to operate this product (wood), and the products of combustion of such fuels, can expose you to chemicals including lead and carbon black, which is known to the State of California to cause cancer, and carbon monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## D. Helpful Hints

When operating your Harman® Absolute43-C Pellet Stove, follow basic safety standards. Read these instructions carefully before you attempt to operate the Absolute43-C Pellet Stove. Failure to do so may result in damage to property or personal injury and may void the product warranty.

**Cleaning Burn Pot:** Whenever your stove is not burning, take the opportunity to scrape the burn pot to remove carbon buildup. A vacuum cleaner is handy to remove the residue. Be sure the stove is cold if you use a vacuum.

Carbon buildup can be scraped loose with the fire burning using the special tool provided with your stove. Scrape the floor and sides of the burn pot. The carbon will be pushed out by the incoming fuel. Always wear gloves when scraping the burnpot.

**Disposal of Ashes:** Ashes should be placed in a steel container with a tight fitting lid. The closed container of ashes should be placed on a non-combustible floor or on the ground, well away from all combustible materials, pending final disposal. If the ashes are disposed of by burial in soil or otherwise locally dispersed, they should be retained in the closed container until all cinders have thoroughly cooled. Other waste shall not be placed in this container.

**Soot and Flyash Formation and Need for Removal:** The products of combustion will contain small particles of flyash. The flyash will collect in the exhaust venting system and restrict the flow of the flue gases. Incomplete combustion, such as occurs during startup, shutdown, or incorrect operation of the room heater will lead to some soot formation which will collect in the exhaust venting system. The exhaust venting system should be inspected at least once every year to determine if cleaning is necessary.

When burning wood pellets on low, the potential exists for creosote to form. The venting system should be inspected periodically throughout the heating season to determine if creosote buildup has occurred. If a significant layer of creosote has accumulated (1/8" or more), it should be removed to reduce the risk of a chimney fire. If a fire occurs, call the fire department, shut down the stove, and evacuate the residence. Before using the appliance, have the venting system thoroughly inspected and replace any damaged components.

With any hearth appliance, installation of smoke detectors is recommended on every level of the home.

### **Possible causes of smoke detector activation:**

Paint curing process - Open a window near the appliance for the first few hours of burning.

Exhaust being drawn back inside the dwelling - Outside air connection to the appliance is necessary.

Vent leakage - Follow venting manufacturer's recommendations for sealing pipe joints.

## E. Fuel Specifications

The Absolute43-C Pellet Stove is approved for burning premium grade pelletized bio-mass fuel.

Hearth & Home Technologies recommends using only fuel that is certified by the Pellet Fuels Institute (PFI).

It should be noted, however, that higher ash content will require more frequent cleaning.

The moisture content of pellets must not exceed 8%. Higher moisture will rob BTU's and may not burn properly.

Fuel should **not** be stored within the stove installation clearances or within the space required for cleaning and ash removal.

### Fuel and Fuel Storage

Pellet fuel quality can fluctuate from manufacturer to manufacturer, and even from bag to bag.

#### Fuel Material

- Made from sawdust and/or other wood by-products
- Source material typically determines ash content

#### Higher Ash Content Material

- Hardwoods with high mineral content
- Bark and leaves as source material
- "Standard" grade pellets and other biomass

#### Lower Ash Content Material

- Softwood; pine, fir, etc.
- Materials with lower mineral content
- "Premium" grade pellets

#### Performance

- Higher ash content requires more frequent maintenance.
- "Premium" grade pellets will produce the highest heat output.
- Burning pellets longer than 1-1/2 inches (38mm) can cause inconsistent feeding and/or ignition.

#### Clinkers

- Minerals and other non-combustible materials, like sand, will turn into a hard glass-like substance when heated.
- Trees from different areas will vary in mineral content. For this reason, some fuels will produce more clinkers than others.

#### Moisture

- Always burn dry fuel. Burning fuel with high moisture content takes energy to dry and tends to cool the appliance thus, robbing heat from your home.
- Damp pellet fuel could turn back into sawdust which does not flow properly through the feed system.

#### Storage

- Wood pellets should be left in their original sealed bag until ready to use, to prevent moisture.
- Do not store fuel within the specified clearance areas, or in a location that will interfere with routine cleaning and maintenance procedures.

### NOTICE

Hearth & Home Technologies is not responsible for stove performance or extra maintenance required as a result of using fuel with higher ash or mineral content.

### CAUTION

***Do not burn fuel that contains an additive.***

- May cause hopper fire
- Damage to product may result

Read the list of ingredients on the packaging.

### CAUTION

Tested and approved for use with wood pellets **ONLY**.  
Burning of any other fuel will void your warranty.

### WARNING

**BURNING COLORED PAPER, CARDBOARD, SOLVENTS, TRASH AND GARBAGE OR ALTERING THE STOVE FOR HIGHER HEAT OUTPUT MAY CAUSE DAMAGE TO THE STOVE AND COULD RESULT IN A HOUSE FIRE. USE ONLY APPROVED FUELS AND FOLLOW ONLY THESE OPERATION GUIDELINES.**

### WARNING


**NEVER USE GASOLINE, GASOLINE-TYPE LANTERN FUEL, KEROSENE, CHARCOAL LIGHTER FLUID, OR SIMILAR LIQUIDS TO START OR 'FRESHEN UP' A FIRE IN THIS HEATER. KEEP ALL SUCH LIQUIDS WELL AWAY FROM THE HEATER, WHILE IN USE.**

### WARNING

*Tested and approved for use with wood pellets **ONLY**.  
Burning of any other fuel will void your warranty.*



## F. Quick Start Guide



### Initial start-up Only

1. Select Language



2. Fill hopper with pellets



3. Adjust arrows to set room desired temperature.



4. Touch the On/Off Power Icon.

*Refer to Touch Manual for all other operations.*

**Please Note:** The USB port on the EASY Touch Control is not a charging port for smartphones, tablets etc.

## G. Frequently Asked Questions

With proper installation, operation, and maintenance your appliance will provide years of trouble-free service. If you do experience a problem, this troubleshooting guide will assist a qualified service person in the diagnosis of a problem and the corrective action to be taken.

**Contact your dealer for additional information regarding operation and troubleshooting. Visit [www.harmanstoves.com](http://www.harmanstoves.com) to find a dealer.**

ISSUES	SOLUTIONS
Metallic noise.	Noise is caused by metal expanding and contracting as it heats up and cools down, similar to the sound produced by a furnace or heating duct. This noise does not affect the operation or longevity of your appliance.
White ash buildup on glass.	This is normal. Clean the glass using any non-abrasive glass cleaner.
Glass has buildup of black soot	Excessive build-up of ash. The lower burn settings will produce more ash, the higher burn settings produce less. The more it burns on low the more frequent cleaning of the glass is required.
Glass has turned dirty.	Excessive build up of ash. The lower burn settings will produce more ash, the higher burn settings produce less. The more it burns on low the more frequent cleaning of the glass is required.
Fire has tall flames with black tails and is lazy.	The feed rate needs to be reduced or the burnpot needs cleaning. Heat exchanger or exhaust blower needs cleaning.
Smoky start-up or puffs of smoke from the airwash.	Burnpot may be dirty, Clean the burnpot.
Large flame at start-up.	This is normal. Flame will settle down once the fire is established.
Missed Ignition	Ensure pellets in burnpot Ensure holes in burnpot are clear of obstructions above the igniter. See Burnpot Maintenance. Check to see if the ignitor is getting hot, if not replace ignitor. *See addendum for manual ignition instructions for emergency heating needs.

## Touch Up Paint

The touch up paint provided with your unit is for fixing minor chips or blemishes that may occur after stove installation.

Unfortunately, because the finish of your stove is baked on, this touch up paint may not be a perfect match to the color of the original finish.

**To use this touch up paint:** Ensure the stove is cool and that the surface to be painted is clean. Apply in several light coats and take care to only coat the chipped area. Allow the paint to dry for 24 hours before touching or firing the stove.








## H. Fire Safety

To provide reasonable fire safety, the following should be given serious consideration:

- Install at least one smoke detector and CO detector on each floor of your home. The National Fire Protection Association (NFPA), recommends one Smoke Alarm on every floor, in every sleeping area, and in every bedroom.
- Locate smoke detector away from the heating appliance and close to the sleeping areas.
- Follow the smoke detector manufacturer's placement and installation instructions and maintain regularly.
- Conveniently locate a Class A fire extinguisher to contend with small fires.
- In the event of a hopper fire:
  - Evacuate the house immediately.
  - Notify fire department.

## I. Cleaning Prompts, Messages and Errors

Your EASY Touch Control communicates with you by showing messages on the top center of the EASY Touch Control home screen. If you have more than one message, the messages will show consecutively until you acknowledge the message by performing the task. These communications include:

<b>PROMPTS</b>	Scrape Burn Pot and Reset Here 	When prompted, scrape burnpot. Press check mark to reset.
	Empty Ash Pan and Press Here 	When prompted, inspect and empty ash pan as needed. Press check mark to reset.
	Total Clean and Reset 	When prompted, inspect and perform total clean. Press check mark to reset.
<b>MESSAGES</b>	Touch Here If Hopper Was Filled 	Press check mark if you filled the hopper. If you did not fill hopper, The message will disappear in 30 seconds.
	Wireless Sensor Low Battery Warning	Replace the 2 "AA" batteries in the Wireless Remote Sensor.
	Using Backup Sensor	If Wireless Remote Sensor batteries die, the Back Up Sensor will continue to heat your home.
<b>ERRORS</b>	Warning: Door Open	Check and close the front and ash doors for the stove to continue to heat.
	Warning: Hopper Lid Open	Close the hopper lid for the stove to continue to heat.
	Error: Check Fuel and Reset 	Fill the hopper with pellets. Press check mark to reset. If you did not fill the hopper, the message will stop after 30 seconds. This error only appears if "Show Fuel Gauges" is turned on.
	Wireless Signal Lost Replace Batteries in Wireless Sensor	Batteries in Wireless Remote Sensor have expired. Replace the 2 "AA" batteries.
	Return Air Sensor Failure	Return Air Sensor has failed. Call your Harman Dealer.
	Ignition Failure Correct and Reset 	Unit has failed to ignite. Scrape the burnpot. Call your Harman Dealer if problem persists.
	Connection Failure Control <====> Display	Touch Control has lost communication to the stove. Call your Harman Dealer.
	Exhaust Sensing Probe Failure	Exhaust Sensing Probe (ESP) as failed. Clean the ESP. If issue persists, call your Harman Dealer.
	Combustion Error Correct and Reset 	Clean your stove. Call your Harman Dealer if problem persists.

## 3 Maintenance & Service

When properly maintained, your stove will give you many years of trouble-free service. **Contact your dealer** to answer questions regarding proper operation, trouble-shooting and service for your appliance. Visit [www.harmanstoves.com](http://www.harmanstoves.com) to find a dealer. We recommend annual service by a qualified service technician.

**Note:** Do not use a household vacuum to clean the stove. We recommend that you use a shop vacuum that is equipped with a fine dust filter called a HEPA filter or a vacuum specially made for fly ash and soot. **USING A VACUUM WHICH IS NOT EQUIPPED WITH A FINE DUST FILTER WILL BLOW FLY ASH AND SOOT OUT INTO THE ROOM.**

**NOTE:** THE STOVE MUST BE COMPLETELY OUT BEFORE YOU VACUUM THE STOVE. LIVE PELLET EMBERS, IF SUCKED INTO THE VACUUM, WILL LIGHT THE VACUUM ON FIRE AND MAY ULTIMATELY CAUSE A HOUSE FIRE.

### NOTICE

The type of fuel you are burning will dictate how often you have to clean your burnpot. Clean more frequently if you encounter heavy build-up of ash at the recommended interval or you see soot coming from the vent. ***Not properly cleaning your appliance on a regular basis will void your warranty.***

### A. Proper Shutdown Procedure



#### CAUTION



#### Shock and Smoke Hazard

- Turn unit to the off position, let appliance completely cool and combustion fan must be off. Now you can unplug appliance before servicing.
- Smoke spillage into room can occur if appliance is not cool before unplugging.
- Risk of shock if appliance not unplugged before servicing appliance.

**Follow the detailed instructions found in this section for each step listed in the chart below.**

## B. Quick Reference Maintenance Chart

Frequency	Cleaning Procedure	Safety Measures	Tips
Daily	Scrape Burn pot	Wear flame resistant gloves <sup>3</sup>	Vigorous, strong scraping specifically near neck of burn pot. Scrape every time you add pellets or at least every 3 bags of fuel. <sup>2</sup>
Weekly	Empty Ash Pan	Wear protective gloves. <sup>1</sup> Put ashes into a steel non-combustible container with tight fitting lid outside.	Unit does not need to be turned off. Reduce to low burn during removal.
	Clean the Glass	Stove must be turned off and cold.	
Monthly	Scrape & Vacuum Heat Exchanger	Stove must be turned off and cold.	Use provided scraper. Scrape back and sides of firebox.
	Brush & vacuum the distribution fan	Stove must be turned off, cold and unplugged from power supply.	Use provided paint brush. This should be done approximately every 25 bags. <sup>2</sup>
	Inspect Hopper lid gasket for damage		Replace gasketing if frays, tears or other visible damage to gasket. This should be done approximately every 50 bags. <sup>2</sup>
	Clean Igniter	Stove must be turned off, cold and unplugged from power supply. Wear protective gloves. <sup>1</sup> Put ashes into a steel non-combustible container with tight fitting lid outside.	Use provided paint brush. Vacuum loose ash from around igniter and inside burn pot.
<b>Stove MUST be turned off, cold and unplugged from power supply for Yearly Cleaning.</b>			
Yearly <sup>4</sup>	Brush & vacuum the combustion fan and venting/exhaust path	Wear protective gloves. <sup>1</sup> Put ashes into a steel non-combustible container with tight fitting lid outside.	Use provided paint brush to brush fan blades. *Use flue brush to clean venting being careful not to damage the ESP. <sup>2</sup>
	Inspect door gasket		Replace gasketing if frays, tears or other visible damage to gasket.
	Brush & vacuum venting system	Wear protective gloves. <sup>1</sup> Put ashes into a steel non-combustible container with tight fitting lid outside.	

\* A flue brush of appropriate size and length may need to be purchased for proper maintenance.

1. Protective gloves will help prevent skin abrasion while working on steel surfaces.
2. Frequency of cleaning depends largely on fuel type. Lower quality pellets require most frequent cleaning.
3. Flame resistant gloves will help protect your skin from potential contact with heat or flames.
4. Yearly cleaning is also known as a Total Clean. This requires completing all the Daily, Weekly, Monthly and Yearly maintenance mentioned. This should be done before you begin burning the unit each heating season.

## C. Unit Maintenance

**Daily/Weekly Maintenance:** It is recommend that the burn pot be scraped whenever adding fuel; taking the opportunity to clean the burn pot will insure proper daily operation.

### Scraping the Burn Pot-

- Using flame resistant gloves, vigorously scrape the top holed surface and sides of the burn pot down to auger tube, be sure to concentrate in the neck of the burnpot. Figure 2.1.
- Scrape loosened material over edge of burnpot grate into the ashpan.
- If needed, empty the ash pan while adding fuel and after scraping the burn pot.




Figure 2.1

**Monthly Maintenance:** It is recommend that the unit be shut down and unplugged from any power source for a monthly cleaning. Monthly cleanings will insure proper operation of your unit throughout the heating season.

- Cleaning Glass - Once unit is cold, use a non-abrasive glass cleaner on glass and wipe clean.
- Scrape and Vacuum Heat Exchanger.

### Cleaning the Heat Exchanger-

Clean the heat exchanger with scraper as shown in Figure 2.2. Brush or scrape the inside of the stove to remove fly ash. Remove the ash pan and dispose of ashes in an approved manner, according to local codes.




Figure 2.2

### Cleaning the Burn Pot-

- Vigorously scrape the top holed surface and sides of the burn pot down to auger tube, as suggested in the Daily/Weekly Maintenance Section.
- Use the supplied allen wrench to remove any build-up that may have accumulated in the holes of the burn pot grate. Simply push the allen wrench down through each hole ensuring it is clear of any build-up paying attention not to damage the igniter element in the process. Figure 2.3.




Figure 2.3



**DANGER**

**Disconnect the power to the unit before removing cover.**

- Loosen (2) 1/4-20 Flange Bolts and pull up on cover and remove to gain access to igniter element and cradle. Figure 2.4.
- Using the brush supplied, brush the igniter element free of any ash or debris. Figure 2.4.




Figure 2.4 - Viewed from below through the ash pan opening.

The burnpot grate can be removed if needed. Figure 2.5.

- Remove the flame Enhancer by pulling straight up removing tabs from burn pot sides.
- Remove the (2) 1/2" allen head bolts from each side of the burn pot.
- Slide the grate toward you to remove.

**NOTE:** the grate **does not** need to be removed to properly clean the igniter. This part is removable for part(s) replacement only.

**NOTE:** The grate must be installed fully to the rear of the burnpot and the rear edge should be in contact with the front face of the burnpot flange before tightening the bolts.

#### Cleaning Igniter Bracket-

Check cleanliness of the igniter and inner burnpot. If the igniter has ash buildup it must be removed to insure proper ignition. Use the provided brush to remove ash buildup from in and around the igniter. Once ash is loose vacuum around igniter and at the base of burn pot.



#### WARNING

Use caution when cleaning burn pot clean-out chamber. Do not damage the high temperature igniter wires.

**Note: The hot lead/cold lead connection must always be pulled to the rear of the feeder body before operation.**

#### Yearly Maintenance: Cleaning the Combustion Fan Chamber-

The combustion inlet cover is located behind the ash pan that must be removed to properly clean the combustion fan blade. Figure 2.5.

- Remove combustion inlet cover by pulling up on cover. This allows access to the combustion fan blade and exhaust path. Figure 2.5.
- Remove any flyash or debris that has collected around combustion fan blade with the provided paint brush.
- Clean exhaust passage. Figure 2.5.

**NOTE: The ESP Sensor is located just inside the exhaust passage. Be sure not to damage the ESP Sensor while cleaning the exhaust passage.**

- Once cleaned replace combustion inlet cover and ashpan.




Figure 2.5

## Caring for your Glass-

The glass used in your stove is manufactured to exact standards to withstand the high heat of the fire, but like all glass, it must be treated with common sense and care. Never abuse the glass by slamming the door shut or striking the glass with a heavy object. If the glass is broken or damaged, do not operate the stove until it has been replaced.

### Glass - Replacement:

If the stove's glass is cracked or broken, you must replace it before operating your stove. Remove pieces carefully. Replace glass only with Harman® replacement glass; **do not use substitutes**.

Carefully remove damaged glass, gasket material, and glass clips (set aside). Figure 2.6.

Install the self adhesive 1/4" gasket material around the front face of the glass. Set the glass panel and gasket gently onto the door. Install the glass clips and 1/4-20 X 1/4" screws.


**Note:** 1/4-20 X 1/4" screws only need to be snug fit. Do not overtighten.

### Glass - Cleaning:

Sometimes it will be necessary to clean accumulated ash from the glass surface; allowing this ash to remain on the glass for long periods can result in "etching" due to the acidity of the ash. Never clean the glass while it is hot, and **do not** use abrasive substances. Wash the surface with cool water and rinse thoroughly. You may wish to use a non-abrasive cleaner specifically designed for use on stove glass. In any case, dry thoroughly before relighting your stove.

### Inspect all Gaskets-

While the unit is cool, inspect all door gaskets to insure proper seal. The gasket should be continuous without frays or tears; having plyable gasket means having a correct seal for proper operation. Figure 2.6.




**Figure 2.6** - Replace glass only with high temperature ceramic glass.

## Distribution Blower-

Checking the distribution blowers yearly is a good habit to get into. Dust, animal hair or anything else that can make its way into that area can drastically cut down on the air movement throughout the unit ultimately causing less of a heating efficiency.

Once the unit is shut down and cooled, unplug the unit from its power supply. Remove the left and right rear panels. Once removed, you will have access to the distribution blowers. Figure 2.7.

Once access is gained to the rear of the unit, thoroughly vacuum around the Distribution Blowers. Figure 2.7.



**Figure 2.7**

## Cleaning Venting System-

Its is recommend that a certified chimney sweep perform service and inspection to your chimney system to insure your unit is vented safely and in accordance to local code.



# 4 Reference Material

## A. Service Parts




### Service Parts

Pellet Stove

### Absolute43-C

Beginning Manufacturing Date: July 2018  
Ending Manufacturing Date: Active

- 1-90-777100-1 (Black)(Beginning Manufacturing Date: July 2018)(Ending Manufacturing Date: Feb 2020)
- 1-90-777100-14 (Majolica Brown)(Beginning Manufacturing Date: July 2018)(Ending Manufacturing Date: Feb 2020)
- 1-90-777101-1 (Black w/Wireless)(Beginning Manufacturing Date: Feb 2020)
- 1-90-777101-14 (Majolica Brown w/Wireless)(Beginning Manufacturing Date: Feb 2020)



Part number list on following page.

02/23


IMPORTANT: THIS IS DATED INFORMATION. Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



Stocked at Depot

ITEM	DESCRIPTION	COMMENTS	PART NUMBER	Stocked at Depot
1	Touch Control		1-00-777552	Y
	Touch Control Screws	Pkg of 30	SRV8787-011	
	Cable Cover Gasket		3-44-777549	
2	16 X 8 Hopper Lid Glass		3-40-777770	Y
	Screwposts/Washers	Pkg of 20 Sets	1-00-129004	Y
	Gasket 3/8 X 1/2	20 Feet	1-00-375501	Y
3	Black Plated Knob w/Screw		1-00-02000-1	
4	Complete Latch	2 Sets	1-00-0669697	
	5/16 X 1/2 Ball Plunger	Pkg of 3	3-31-5500-3	
	Bulk 5/16 Push Retainer	Pkg of 100	3-31-94807-100	
5	Hopper Lid Hinge w/Hardware		1-00-777147	Y
	Hopper Lid Hinge Pin Plates w/Hardware	1 Set	1-00-777560	
6	Cast Top	Black	4-00-247236S	
		Majolica Brown	1-00-247236-14	
7	Hopper Assembly	<b>No longer available</b>	1-10-777130A	
	Gasket Hopper Throat		3-44-677185	Y
	Gasket, 3/8 X 1/2	20 Feet	1-00-375501	Y
	Gasket, 5/8 X 1/2	20 Feet	1-00-625501	Y
8	Left Side Cast	Black	4-00-777645P	
		Majolica Brown	1-00-777645-14	
9	Combustion Blower Capacitor		1-00-00276	Y
10	Smoke Shield		1-00-777133	

### #11 Load Door



11	Load Door			
11.1	Cast Latch, Knob & Screw		1-00-0119	Y
	Wood Handle		3-40-00247	
11.2	Load Door Rope	Black	4-00-777565P	Y
		Majolica Brown	1-00-777565-14	Y
11.3	Latch Bracket w/Hardware	1 Set	1-00-777665	Y
	Rollers & Hardware	1 Set	1-00-77753	Y
11.4	Gasket 1/4 RD PSA	15 Feet	1-00-2312	Y
11.5	Glass w/Gasket		1-00-777000	Y
11.6	Glass Clips w/Hardware	1 Set	1-00-777619	Y
11.7	Load Door Hinge w/Hardware		1-00-777610	Y
11.8	Gasket 1/2" RD LD	20 Feet	1-00-1086204	Y

Additional service parts on following page.


IMPORTANT: THIS IS DATED INFORMATION. Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



Stocked at Depot

ITEM	DESCRIPTION	COMMENTS	PART NUMBER	
12	Burn Pot Scraper	Pkg of 10	2-00-777138-10	
13	Ashlip	Black	3-00-777644P	
		Majolica Brown	1-00-777644-14	
14	Ash Door, Complete		1-10-777135A	
	Gasket 1/2" RD LD	20 Feet	1-00-1086204	Y
15	Ash Door Handle Assembly	1 Set	1-00-777149	Y
	Rollers & Hardware	1 Set	1-00-77723	Y
16	Ash Pan		1-10-777121A	Y

### #17 Burn Pot Assembly



17	Burn Pot Assembly			
17.1	Burn Pot Weldment		1-10-777901A	Y
	Gasket, Burn Pot		3-44-237639	Y
	Flame Guide		3-00-03000	Y
17.2	Ingiter		3-20-677200	Y
		Pkg of 10	1-00-677200	Y
17.3	Igniter Bracket		1-00-777906	
17.4	Burn Pot Clean Out w/Hardware		1-00-777908	Y
	1/4"-20x1/2	Pkg of 50	3-30-2001-50	Y
18	Leg Leveling Kit	1 Set	1-00-12302	
19	Leg w/Hardware	Black	1-00-249100	Y
		Majolica Brown	1-00-249100-14	Y
20	Right Side Cast	Black	4-00-777646P	
		Majolica Brown	1-00-777646-14	
21	Combustion Blower		1-00-02275	Y
	Fan Blade		1-10-574500A	Y
	Pound In Stud 6-32 X 1 1/4 (Pre HF2265448)	Pkg of 30	1-00-53463220	
	Blower Mounting Screws (Post HF2265448)	5 Sets	1-00-832150	
22	Gasket Set, Burn Pot & Tailpipe	Pkg of 5 Sets	1-00-07381	Y
23	Pellet Tailpipe, Cast		3-00-247237	Y

Additional service parts on following page.


IMPORTANT: THIS IS DATED INFORMATION. Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



Stocked at Depot

ITEM	DESCRIPTION	COMMENTS	PART NUMBER	Stocked at Depot
24	Power Cord		3-20-51578	Y
	Line Filter		3-20-803744	Y
25	Gasket Set, Burn Pot & Tailpipe	Pkg of 5 Sets	1-00-07381	Y
26	ESP Probe-Red/Red		3-20-00844	Y
27	Distribution Blower, 100CFM	Qty 2 req	SRV3-21-07775	Y
28	Rear Cover, Right		1-00-777124	Y
29	Differential Switch		3-20-6866	Y
	Tubing, 1/8 Silicone	5 Feet	1-00-5113574	Y
30	Rear Cover, Left		1-00-777123	Y

### #31 Feeder Assembly



31	Feeder Assembly			
31.1	Feeder Body		1-10-777513A	Y
31.2	Slide Plate Assembly		1-10-777690A	Y
31.3	Feed Cover & Gasket	2 Sets	1-00-677122	Y
31.4	Pusher Arm		1-10-677187W	Y
	Pillow Block	Pkg of 4	3-31-3614087-4	Y
31.5	Auger		3-50-00565	Y
31.6	Bearing Retainer w/Hardware		1-00-04035	Y
	Cam Bearing		3-31-3014	Y
31.7	Cam Block Assembly		1-10-777950A	Y
31.8	4 RPM CW Outboard Motor, 120V		3-20-00677	Y
31.9	Motor Mount w/Hardware		1-00-777598	Y
31.10	Feeder Crossover Tube Kit		1-00-67900	Y
31.11	Gasket, Snout	Pkg of 10	3-44-677160-10	Y
31.12	Air Intake		1-10-06810A	
31.13	Gasket, Air Intake	Pgk of 6	3-44-72224-6	Y
	Silicone Cap	Pgk of 10	3-99-123/10	

Additional service parts on following page.



## B. Limited Lifetime Warranty

### Hearth & Home Technologies LLC

#### LIMITED LIFETIME WARRANTY

Hearth & Home Technologies LLC (“HHT”) extends the following warranty for HHT gas, wood, pellet and electric hearth appliances (each a “Product” and collectively, the “Product(s)”) and certain component parts set forth in the table below (“Component Part(s)”) that are purchased from a HHT authorized dealer or distributor.

#### **WARRANTY COVERAGE:**

HHT warrants that the Products and their Component Parts will be free from defects in materials and workmanship for the applicable period of Warranty coverage set forth in the table below (“Warranty Period”). If a Product or Component Parts are found to be defective in materials or workmanship during the applicable Warranty Period, HHT will, at its option, repair the applicable Component Part(s), replace the applicable Component Part(s), or refund the purchase price of the applicable Product(s). The maximum amount recoverable under this Warranty is limited to the purchase price of the Product. This Warranty is transferable from the original purchaser to subsequent owners, but the Warranty Period will not be extended in duration or expanded in coverage for any such transfer. This Warranty is subject to conditions, exclusions, and limitations as described below.

#### **WARRANTY PERIOD:**

Warranty coverage begins at the date of installation. In the case of new home constructions, Warranty coverage begins on the date of first occupancy of the dwelling or six months after the sale of the Product(s) by an independent, authorized HHT dealer or distributor, whichever occurs earlier. However, the Warranty coverage shall commence no later than 24 months following the date of Product shipment from HHT, regardless of the installation or occupancy date.

The term “Lifetime” in the table below is defined as: 20 years from the beginning date of warranty coverage for gas appliances, and 10 years from the beginning date of warranty coverage for wood and pellet appliances. These time periods reflect the minimum expected useful lives of the designated Component Parts under normal operating conditions.

Warranty Period		HHT Manufactured Appliances and Venting						
Component Parts	Labor	Gas	Pellet	Wood	Electric	Venting	Component Parts Covered by this Warranty	
1 Year		X	X	X		X	All parts including handles, external enameled components and other material except as covered by Warranty Conditions, Warranty Exclusions, and Warranty Limitations listed	
2 Years					X		All parts except as covered by Warranty Conditions, Warranty Exclusions, and Warranty Limitations listed	
2 years			X	X			Igniters, Auger Motors, Electronic Components, and Glass	
		X					Electrical components limited to modules, remotes/wall switches, valves, pilots, blowers, junction boxes, wire harnesses, transformers and lights (excluding light bulbs)	
		X		X			Molded Refractory Panels, Glass Liners	
3 years			X				Firepots, burnpots, mechanical feeders/auger assemblies	
5 years	1 year	X					Vent Free Burners, Vent Free Logs	
			X	X			Castings, Medallions and Baffles	
6 years	3 years			X			Catalysts	
7 years	3 years		X	X			Manifold tubes, HHT Chimney and Terminations	
10 years	1 year	X					Burners, logs and refractory	
Limited Lifetime	3 years	X	X	X			Firebox and heat exchanger, FlexBurn® System (engine, inner cover, access cover and fireback)	
1 Year	None	X	X	X	X	X	All purchased replacement parts	

## **WARRANTY CONDITIONS:**

- Because HHT cannot control the quality of any Products sold by unauthorized sellers, this Warranty only covers Products that are purchased through an HHT authorized dealer or distributor unless otherwise prohibited by law; a list of HHT authorized dealers is available on the HHT branded websites.
- This Warranty is only valid while the applicable Product remains at the site of original installation.
- This Warranty is only valid in the country in which the HHT authorized dealer or distributor that sold the applicable Product is authorized to sell applicable Product.
- Contact your installing distributor or dealer for Warranty service. If the installing dealer or distributor is unable to provide necessary parts, contact the nearest HHT authorized dealer or supplier. Additional service fees may apply if you are seeking Warranty service from a dealer other than the dealer from whom you originally purchased the applicable Product.
- No HHT consumer should bear cost of warranty service or costs incurred while servicing warranty claims (i.e., travel, gas, or mileage) when the service is performed within the terms of this Warranty. Check with your dealer or distributor in advance for any costs to you when arranging a warranty call. Travel and shipping charges for parts are not covered by this Warranty.

## **WARRANTY EXCLUSIONS:**

This Warranty does not cover the following:

- Changes in surface finishes as a result of normal use. As a heating appliance, some changes in color of interior and exterior surface finishes may occur. This is not a flaw and is not covered under the Warranty.
- Damage to printed, plated, or enameled surfaces caused by fingerprints, accidents, misuse, scratches, melted items or other external sources and residues left on the plated surfaces from the use of abrasive cleaners or polishes.
- Repair or replacement of parts that are subject to normal wear and tear during the Warranty Period are not covered. These parts include: paint, wood and pellet gaskets, firebricks, grates, flame guides, batteries and the discoloration of glass.
- Minor expansion, contraction, or movement of certain parts causing noise. These conditions are normal and complaints related to this noise are not covered by this Warranty.
- Damages resulting from: (1) failure to install, operate, or maintain the applicable Product in accordance with the installation instructions, operating instructions, and listing agent identification label furnished with the applicable Product; (2) failure to install the applicable Product in accordance with local building codes; (3) shipping or improper handling; (4) improper operation, abuse, misuse, continued operation with damaged, corroded or failed components, accident, or improperly/incorrectly performed repairs; (5) environmental conditions, inadequate ventilation, negative pressure, or drafting caused by tightly sealed constructions, insufficient make-up air supply, or handling devices such as exhaust fans or forced air furnaces or other such causes; (6) use of fuels other than those specified in the operation instructions; (7) installation or use of components not supplied with the applicable Product or any other components not expressly authorized and approved by HHT; (8) modification of the appliance not expressly authorized and approved by HHT in writing; and/or (9) interruptions or fluctuations of electrical power supply to the applicable Product.
- Non-HHT venting components, hearth connections or other accessories used in conjunction with the applicable Product.
- Any part of a pre-existing fireplace system in which an insert or a decorative gas applicable Product is installed.
- HHT's obligation under this Warranty does not extend to the Product's capability to heat the desired space. Information is provided to assist the consumer and the dealer in selecting the proper Product for the application. Consideration must be given to the Product location and configuration, environmental conditions, insulation and air tightness of the structure.

**This warranty is void if:**

- The applicable Product has been over-fired, operated in atmospheres contaminated by chlorine, fluorine, or other damaging chemicals. Over-firing can be identified by, but not limited to, warped plates or tubes, deformation/warping of interior cast iron structure or components, rust colored cast iron, bubbling, cracking and discoloration of steel or enamel finishes.
- The applicable Product is subjected to prolonged periods of dampness or condensation.
- There is any damage to the applicable Product due to water or weather damage which is the result of, but not limited to, improper chimney or venting installation.

## **LIMITATIONS OF REMEDIES AND LIABILITY:**

- **EXCEPT TO THE EXTENT PROVIDED BY LAW, HHT MAKES NO EXPRESS WARRANTIES OTHER THAN THE WARRANTY SPECIFIED HEREIN. The owner's exclusive remedy and HHT's sole obligation under this Warranty or in contract, tort or otherwise, shall be limited to replacement of the Component Part(s), repair of the Component Part(s), or refund of the original purchase price of the applicable Product(s), as specified above; provided, however, that (i) if HHT is unable to provide replacement of the Component Part(s) and repair of the Component Part(s) is not commercially practicable or cannot be timely made, or (ii) the customer is willing to accept a refund of the purchase price of the applicable Product(s), HHT may discharge all such obligations by refunding the purchase price of the applicable Product. In no event will HHT be liable for any incidental or consequential damages caused by defects in the applicable Product. Some States do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This Warranty gives you specific legal rights and you may also have other rights which vary from State to State. THE DURATION OF ANY IMPLIED WARRANTY IS LIMITED TO DURATION OF THE EXPRESSED WARRANTY SPECIFIED ABOVE FOR THE APPLICABLE PRODUCT. Some States do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.**

## B. Loss of Power

Harman pellet burning appliances rely on a combustion blower to remove exhaust from the firebox. A power failure will cause the combustion blower to stop running, which may lead to exhaust see page into the room. Vertical rise in the venting system can help create natural draft, which may reduce the likelihood of exhaust leakage into the home.

Installation of a low-cost uninterruptible power supply (UPS) or battery backup system can help ensure the units shuts down without any minor smoke leakage into the home. Harman recommends the installation of one of these two systems for areas prone to power outages.

**There is one Harman® approved UPS option for your appliance:**

**Uninterruptible Power Supply UPS** battery back-ups are available online or at computer and office equipment stores. Your Harman® appliance with Rev E or later software available beginning in November 2010 may be plugged directly into a Harman® approved UPS:

- **TrippLite model INTERNET750U** is tested and approved. Other brands or models may not be compatible.

When power is lost, a fully charged UPS will power a safe, combustion blower only shut-down. Your appliance will pulse the blower every few seconds to clear exhaust until the fire is out. **NOTE: The UPS provides safe shut-down only. It is not intended for continued operation.**

- A Inverter/Charger connects to a 12 volt deep cycle battery that will run your appliance for up to eight (8) hours. It includes a trickle charge feature that keeps your battery charged when power is available. **NOTE:** If the power is out for longer than battery life, smoke leakage may still occur unless your stove has been safely shut down.

**For an approved Inverter/Charger refer to [www.harmanstoves.com](http://www.harmanstoves.com).**

Your appliance will recognize when power is restored. What happens depends on ESP temperature and whether it is equipped with automatic ignition:

- In **“Automatic” Mode**, units equipped with automatic ignition will respond to the set point and ESP temperature and resume normal operation.
- In **“Idle” Mode**, or for units without automatic ignition:
  - If the ESP is cool, the appliance will remain shut down.
  - If the fire is out and the ESP is still warm, the feeder may restart. Since the fire is out, the ESP temperature will not rise. The unit will then shut-down, and may flash a six-blink status error. (See ESP error codes)
  - If the fire is still burning, it will resume normal operation.

Contact your dealer if you have questions about UPS compatibility with your appliance.

**IMPORTANT!** : UPS or Battery Backup cannot prevent smoke leakage from an improperly maintained unit. Keep the venting system clean and free from obstructions and maintain all gaskets to keep an airtight seal.

### **WARNING**

**Use only Harman® approved battery back-up devices. Other products may not operate properly, can create unsafe conditions or damage your appliance.**

### **CAUTION**

**Always keep appliance doors and hopper lid closed and latched during operation and during power failures to minimize risk of smoke or burn-back.**

## D. Emergency Manual Ignition

Harman® pellet stoves and inserts should be lit using the automatic ignition system. This is the safest and most reliable way for igniting the unit. In the event the automatic igniter is not functioning, the steps below may be followed to manually light the stove or insert in the “Constant Burn” mode. Manual lighting is for emergency purposes only, and the igniter should be repaired or replaced as soon as practical.

### **WARNING**

Only use firestarter commercially marketed for pellet stoves and inserts, including wax coated wood chips, pellet starter gel and pellet igniter blocks. Use of any other type of firestarter is prohibited.

To avoid serious injury or death read and follow manufacturer’s warning and instructions for use of firestarter. Use of firestarter is only permitted when performing a cold start.

Never attempt to manually light a stove or insert that has been operated recently and is not at room temperature. If automatic ignition was attempted, be sure to give the stove or insert at least 30 minutes or longer to cool to room temperature.

Be sure that the stove or insert is in the “Igniter - Disabled” mode of operation.

Once all the precautions have been taken, follow these steps:

1. On the touch control, select the Burn Mode icon then select “Constant Burn”.
2. Arrow back and select the Igniter icon then select “Manual” for the ignition method. Select the Home Icon to go back to the Main Menu.
3. Fill burn pot with pellets, only half way. (Do Not Over Fill).
4. Add firestarter to pellets following manufacturer’s instructions.
5. Light pellet firestarter with a match, and close the door, touch the On/Off icon on the home screen. Operation will begin when the fire reaches the proper temperature.



## E. Troubleshooting

ISSUES	SOLUTIONS
Stove does not feed	<ul style="list-style-type: none"> <li>• No fuel in hopper.</li> <li>• Firebox draft may be too low for sensing switch in feeder circuit to operate. <b>Check for closed doors</b>, loose or missing gasket on doors or hopper lid.</li> <li>• Feed motor will not run until the ESP control senses a certain temperature. Maybe you did not put enough fuel or starting gel in the burn pot before manually lighting the fire (In Constant Burn, Manual Light Only.)</li> <li>• Restriction in the hopper or feeder. Remove all fuel and examine. Clear the obstruction.</li> <li>• Feed motor has failed.</li> </ul>
Partially burned pellets	<ul style="list-style-type: none"> <li>• Feed rate too high.</li> <li>• Poor air to fuel mixture. (Check burn pot clean-out cover and air intake).</li> <li>• Burn pot may need to be cleaned.</li> <li>• Combination of all the above.</li> </ul>
Smoke smell	Seal the vent pipe joints and connection to stove with silicone. The exhaust vent is the only part of the system that is under positive pressure.
Fire has gone out	<ul style="list-style-type: none"> <li>• No fuel in hopper.</li> <li>• Draft is too low, blocked flue.</li> <li>• Something is restricting fuel flow.</li> <li>• Hopper lid not closed properly.</li> <li>• Feed motor or combustion fan has failed.</li> </ul>
Smoke is visible coming out of vent	<ul style="list-style-type: none"> <li>• Air-fuel ratio is too rich.               <ul style="list-style-type: none"> <li>- Feed rate too high.</li> <li>- Draft too low caused by a gasket leak.</li> </ul> </li> </ul>
Low heat output	<ul style="list-style-type: none"> <li>• Feed rate too low</li> <li>• Draft too low because of gasket leak.</li> <li>• Poor quality or damp pellets</li> <li>• Combination of 1 and 2.</li> </ul>





*Hearth & Home Technologies, Inc.*  
*Model: Absolute43-C*  
*Report: 0135PS039E*

*OMNI-Test Laboratories, Inc.*

## **Appendix B**

### **Revision History**

Date	Project No.	Tech. & Evaluator	Report Sect.	Summary of Changes
March 2018	0135PS039E	Aaron Kravits Ken Morgan	ALL	First Issue of Report
04/19/2018	0135PS039E Edition 001	Aaron Kravits Ken Morgan	Section 1	Appliance photos were added to report
05/24/2023	0135PS039E Edition 002	Riley Tiegs Ken Morgan	Preface	Edition of Report Updated
			Section 1	Corrected/Uncorrected Values added to Table 1.3 (pg 9)
				Statement mentioning anomalies and validity of run added to Summary of Results (pg 7)
			Appendix A	New Owners and Installation Manual Added to report
			Appendix B	Revision History added to report
			Section 2	Train Precision added to Test Results (pg29)
Dilution Tunnel Schematic Added (pg 11)				