KSTDVP Marquis Clear View See-Through Direct Vent Fireplace System





ACTUAL DIMENSIONS

Actual size: 395%" W x 385% " H x 24" D (1007 mm x 981 mm x 610 mm)

Viewing area: 36" W x 30" H

(914 mm x 762 mm)


Framing Dimensions: 50" W x 443/4" H x 23"D


(1270 mm x 1137 mm x 584 mm)


FIELD INSTALLED ACCESSORIES

- · Accent lighting with 3 step dimming standard
- Stainless steel outdoor Glass Kit (install before framing)
- Four liners to choose from: Cottage Clay, Tavern Brown, Vintage Brown Herringbone, and Olde English Herringbone
- Variable Remote Controlled Forced Air Blower BLOTKSTSC (2 needed if forced air out both sides is required)
- Field Fuel Conversion Kits
- 15' Command Center Wall Mount Extension Wire
- Safety Screen Barrier Included

FRAMING DIMENSIONS









KSTDVP Marquis Clear View See-Through Direct Vent Fireplace System




MANTEL CLEARANCES

NOTE: The combustibles area above the facing must not protrude more than 1/2" from the facing. If it does, it is considered a mantel and must meet the mantel requirements listed in the owner's manual.







TECHNICAL SPECIFICATIONS

Clear View ceramic glass: viewing area of 2,160 square inches

(both sides)

Btu Rating: 56,000 BTU/hr

Ignition System: Signature Command™ System

Gas Type: Natural or LP

Top venting only with 5" x 8" DVP Direct Vent Pipe

Total Signature Command™ Control (TSC) with full function TSFSC

hand held remote control included

Fit chases with 24" depth

Accent light provided standard with manual control dimmer

CSA Design Certified

CLEARANCE TO FLUE

Minimum 6" (152mm) clearance to the top along horizontal length until flue penetrates outside wall*

Minimum of 1" (25 mm) clearance to combustibles permitted at outside wall

CLEARANCE TO COMBUSTIBLES

Fireplace: 0" clearance to standoffs on all sides Floor of Unit to Ceiling: 72" (1829mm) to combustibles

Firebox Opening to Wall: 6" (152mm)

Hearth Requirement: 0"

EFFICIENCY DATA

Thermal Efficiency: Up to 80%

AFUE Efficiency: 67.4% (Nat) / 66.3% (LP) P4 Canada Efficiency: 77.3% (Nat) / 74.3% (LP)

If vertical rise is 7 1/2' (2.29 mm) or higher when in top vent configuration only, the vent clearance to combustibles is 1 (25 mm) on all sides of the horizontal run.











149 Cleveland Drive, Paris, Kentucky 40361 www.majesticproducts.com

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. ©2015 Hearth & Home Technologies® 1115v3