PRODUCT SPECIFICATIONS CFX32(U/DW) Chesapeake Vent Free Fireplace System



ACTUAL DIMENSIONS

61% W \times 50 % H \times 18¼ D (1564 mm \times 1289 mm \times 396 mm) Viewing area: 26"W \times 15¼"H, 392 in.² (660 mm \times 387 mm, 2555 cm²)

STANDARD FEATURES

- Colonial designed face
- Triple Play Burner System[®] ember bed burner with yellow flame, loose embers and 3 piece ceramic fiber glowing logs
- Mesh screen front
- Barrington wood cabinet surround in Dark Walnut or Unfinished

FIELD INSTALLED ACCESSORIES

- Cottage Clay Firebrick
- Thermostat Blower (160 cfm) BLO24T
- Remote Controls RCB, RCMT, TSMT, RCST, TSST


TECHNICAL INFORMATION

BTU/HR Input: 26,000 Max. / 20,000 Min. (Natural and LP) Ignition System: Millivolt Control - Standing Pilot w/piezo igniter Thermal Efficiency: Up to 99%

Clearance to Combustibles:

Fireplace - 0" to stand offs on all sides Top of Firebox Opening to Ceiling - 42" to combustibles Firebox Opening to Side Wall - 9" to combustibles Hearth Requirement: 0" Clearance Gas Line: 18" Flex line w/shut off 1/2" FPT CSA Design Certified

18 1/4" (464 mm) 50 3/4" (1289 mm) (1289 mm) (1289 mm) (1287 mm) (660 mm) (670 mm) (770 mm) (



(1564 mm)



A Brand of Vermont Castings Group 149 Cleveland Drive, Paris, Kentucky 40361 www.monessenhearth.com

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. v3 © 2014 Vermont Castings Group

