



0:41 ul V Outside Temp: 23* HEAT & GLO Ne and builds server for

Available IntelliFire® app and voice control



THE ONLY TRUE ARCHED FIREPLACE



1.1910

CERONA

The Cerona gas fireplace is a modern take on an enduring classic, ahead of the curve in comfort and convenience with an arched design that makes your home a unique reflection of you. Our best combination of beauty and warmth in 36" and 42" sizes.

AUTHENTIC DESIGN

The stunning beauty starts with that true arch of a classic masonry hearth, unlike a curved front over a square opening. It highlights the bold flame with true-to-life logs, glowing embers and dancing shadows off the hand-painted 3-D surface.

VARIABLE HEAT

Easily adjust the powerful heat output of the Cerona. Up to 50% turndown helps create your ideal warmth. Optional technologies can also distribute heat to other areas of the home.

FRONT OPTIONS

Each front ships with ClearVue® mesh, a virtually invisible safety screen.



CHATEAU FORGE Available in hand-crafted hammered steel.



IRON AGE Available in Black, Gun Metal and New Bronze.





ack, FIRESCREEN Available in Black, ee. Gun Metal and New Bronze.

GUN METAL

TECHNOLOGIES



INTELLIFIRE TOUCH® IGNITION SYSTEM

IntelliFire Touch is the most advanced and intuitive IntelliFire system, making operating your fireplace simple, smart and safe. IntelliFire® touchscreen remote comes standard; add the IntelliFire app or wireless wall switch for the solution that fits your life.



FIREBRICK TECHNOLOGY

FireBrick is a patented, energy-saving ceramic material molded into an authentic masonry design. FireBrick produces up to 25% more radiant heat than metal fireboxes—heating rooms faster and using less fuel. This increases efficiency and reduces heating costs.



DIRECT VENT TECHNOLOGY

Direct Vent fireplaces remove 100% of combustion exhaust and odors outside of the home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality.

HEAT MANAGEMENT SOLUTIONS

Bring the warmth from your fireplace to the rest of your home, up to 20 feet away. Heat management solutions can redirect up to 50% of the heat to another area, and reduce wall temperatures above the fireplace. Choose between:

- HEAT-ZONE® KIT transfers heat where you want it
- HEAT-OUT[®] KIT redirects heat from the fireplace outside the home
- PASSIVE HEAT^{**} KIT allows heat to naturally rise and disperse at ceiling height without the use of a fan. When using a mantel, Passive Heat enables a TV or heat sensitive materials to be placed just 12" above fireplace opening. Choose side, front or open wall register.

CONTROLS

INTELLIFIRE APP

All the features of a remote control with an app installed on your smart device. Monitor your fire from anywhere or even control it with the sound of your voice. IntelliFire is compatible with voice assistants Amazon Alexa and Google Assistant.



TOUCHSCREEN REMOTE

Features: on/off, flame height adjustment, fan speed, lights adjustment, thermostat mode, room temperature readout, child lock, timer mode, battery backup, cold climate mode, power vent, wall docking station (fan, lights and power vent are dependent on your fireplace).



WIRELESS WALL SWITCH Features: on/off, battery strength indicator, cold climate mode

SPECIFICATIONS

MODEL	FRONT WIDTH		BACK WIDTH		HEIGHT		DEPTH		GLASS SIZE	BTU/HR INPUT
	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING	GERSS SIZE	Brojnik ini or
CERONA-36-IFT	41-1/8 [1046]	42-1/8 [1070]	28-1/2 [724]	42-1/8 [1070]	49-7/8 [1268]	50-1/2 [1283]	21-3/4 [551]	22-1/4 [565]	30-1/4 X 23-1/2 [767 X 595]	20,000-36,000 (NG)
CERONA-42-IFT	48-1/8 [1223]	49-1/8 [1248]	35-3/8 [900]	49-1/8 [1248]	54 [1372]	54-1/2 [1384]	21-3/4 [551]	22-1/4 [565]	35-7/8 X 27-3/4 [912 X 704]	25,000-48,000 (NG)
	TOP VIEW		LEFT SIDE VIEW			FRONT VIEW		RIGHT SIDE VIEW MINIMUM 12" VERTICAL RISE REQUIRED BEFORE 90" ELBOW		
←28-1/2*[724] → 14-1/4* ←[362] → 114*] ←					43"	41-1/8"[1046]		34-1/2*	65-1/2" [1664]	

21-3/4"[551] -1/8 8"[204



GAS LINE ACCESS

2-1/4

[56

9-1/4"

[235]-



2-1/4" i no. ELECTRICAL ACCESS [130]-

MINIMUM 12" VERTICAL RISE

12-5/8





പപ്പ 70" [1778] **∎**0•

CERONA-42-IFT





ELECTRICAL ACCESS

Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Actual product appearance, including flame, may differ from product images.

you do NOT cover the decorative door opening.



OUR SUSTAINABILITY STORY

Our history of leadership in the hearth industry compels us to now lead the way in developing manufacturing practices that ensure our planet remains as durable, beautiful and long-lasting as our products. Find out how we are leading the industry in sustainable practices by scanning the code above.

For complete information on this model, please contact us at:

HEAT

No one builds a better fire



voutube.com/HeatandGlo

x.com/HeatandGlo

HNG-1065U-0324











LIMITED LIFETIME WARRANTY*

The strongest in the industry, Heat & Glo[®] provides a limited lifetime warranty on the most important aspects: firebox and heat exchanger.

*For full warranty details, go to www.heatnglo.com.

Fireplace glass and other surfaces get extremely HOT and can cause severe burns if touched. Do not remove the protective safety screen from the front of the glass. Keep a safe distance away. To learn more visit www.heatnglo.com/fireplacesafety.

Google, YouTube and Google Home are trademarks of Google LLC. Amazon, Alexa, and all related logos are trademarks of Amazon. com, Inc. or its affiliates.

EFFICIENCIES

EnerGuide (CSA 2.33-2019) — EnerGuide is a rating used in Canada to measure annual fireplace efficiency.

FIREPLACE	RATING
CERONA-36-IFT	64.1% (NG), 65.6% (LP)
CERONA-42-IFT	63.0% (NG), 64.1% (LP)

Dimensions in diagrams are in inches and millimeters. Dimensions in table are in inches. Product information is not complete and is subject to change without notice. Product installation must adhere strictly to instructions shipped

with product. We recommend measuring individual units

at installation. Assumes the use of 1/2" sheetrock. NOTE:

Combustible material should not cover the face. Make sure