



— & —  
**SLR-X**

BALANCED FLUE GAS FIREPLACE

— **HEAT & GLO** —



FUNDAMENTALLY  
**MODERN**

*SLR-X shown with clean face trim front in black, natural logs and fade-resistant reflective black glass interior panels.*




SLR-X shown with clean face trim in black, river rock and fade-resistant reflective black glass interior panels.

## SLR-X

Warmth, ambiance and chic contemporary detail. An experience only the SLR-X can provide. A linear design and long ribbon flame form a broad, hypnotic firescape. Several finishing options create a fundamentally modern look for any space while a standard fan circulates the heat.


Reap the benefits of form and function. Clean lines and elegant ambiance never go out of style.

### INTERIOR OPTIONS



#### FADE-RESISTANT REFLECTIVE BLACK GLASS INTERIOR OPTION


Create a mood so cool, it's hot. A reflective glass liner radiates the fire and intensifies the flame.



CRYSTAL GLASS



EBONY GLASS




AMBER GLASS



COBALT GLASS



RIVER ROCK



BLACK GLASS BEADS



WHITE GLASS BEADS



CLEAR GLASS BEADS



NATURAL LOGS




DRIFTWOOD LOGS


### TRIM FINISHES



CLEAN FACE TRIM  
(shown with driftwood logs)



EBONY



BLACK



GRAPHITE



FOG GRAY



NEW BRONZE



STAINLESS STEEL

# SLR-X PLUS TECHNOLOGIES



## INTELLIFIRE PLUS IGNITION SYSTEM

An advanced intermittent pilot ignition system with memory settings and a programmable wireless RC300 remote control. IPI Plus constantly monitors ignition, ensures safe functioning and conserves up to \$10/month in energy costs.



## BALANCED FLUE TECHNOLOGY

Balance Flue fireplaces remove 100% of combustion exhaust and odors outside of the home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality.



## FLEX HEAT TECHNOLOGY

Draw heat from your fireplace into another room of the home, up to 6 meters away. When flex heat is run continuously, it will redirect up to 25% of the fireplace's heat to another area, thus reducing wall temperatures above the fireplace. Two flex heat registers run continuously will redirect up to 50% of the fireplace's heat.




## FADE-RESISTANT BLACK GLASS PANELS

A clean modern look that reflects the fire and never gets dull. Just like this black glass interior. It's hot. And looks that way, too. For the life of your fireplace.


## SLR-X SPECIFICATIONS

MODEL	FRONT WIDTH		BACK WIDTH		HEIGHT		DEPTH		GLASS SIZE	mJh INPUT	EFFICIENCY	FUEL TYPE/ IGNITION SYSTEM
	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING				
SLR-X	1219	1245	959	1016	856	832	451	451	991 x 387	N - 31.7 L - 27.4 B - 28.0	77%	Gas, IntelliFire Plus


LEFT SIDE VIEW




FRONT VIEW



RIGHT SIDE VIEW



TOP VIEW



Dimensions above are in millimeters. Reference dimensions only. We recommend measuring individual units at installation. NOTE: Combustible material should not be installed over the face. Make sure you do NOT cover the decorative door opening.

Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Pictures in this brochure are not a true representation of the fireplace and/or flames.

For complete information on this model, please contact us at:

**HEAT & GLO**

No one builds a better fire

[www.heatnglo.com](http://www.heatnglo.com)