



DESIGNED | *to inspire*

6000/8000 MODERN
Direct Vent Gas Fireplace

6000/8000 MODERN Design Highlights Innovation

Innovations in technology, design and safety unite in the 6000 / 8000 Modern—resulting in a dramatic, yet elegant fireside experience. Sleek flames rise through colored glass and multiply with a reflective black glass interior.

Create a functional focal point in your space. Customize your 6000 / 8000 Modern and experience how “No One Builds A Better Fire.”



Above: 8000 Modern shown with modern front in black and crystal glass media.

Cover: 6000 Modern shown with modern front in fog gray and black glass media.

6000/8000 MODERN



DRAMATIC FOCAL POINT

Outfit your 6000 / 8000 Modern to enhance or contrast your style. Explore unique wall placements, front styles and different colored glass options to create a custom look.

6000 Modern shown above with modern front in fog gray and black glass media.



FEATURES & BENEFITS

- 36 or 42-inch viewing area
- Reflective black glass interior
- Enhanced safety with the IntelliFire™ Plus ignition system and Direct Vent technology

8000 Modern shown above with modern front in black and amber glass media.

FRONT OPTIONS

Choose a front design to complement your media and accent your décor.



FRONT FINISHES



Black



Graphite
(Folio front only)



Gray
(Modern front only)



New Bronze
(Folio front only)

MEDIA OPTIONS



Crystal Glass (Standard)



Cobalt Glass



Black Glass



Amber Glass

CONTROLS

Add an optional wall switch or remote for enhanced convenience.

For more information on the control options available, please visit heatnglo.com



INTELLIFIRE PLUS IGNITION SYSTEM

The IntelliFire™ Plus Ignition System (IPI Plus) is an advanced intermittent pilot ignition system with memory settings and a programmable wireless control. IPI Plus constantly monitors ignition, ensures safe functioning and conserves up to \$10/month in energy costs. To learn more about IntelliFire Technology, scan the code to the right with your smartphone, or visit heatnglo.com.



DIRECT VENT TECHNOLOGY


Direct Vent fireplaces remove 100% of combustion exhaust and odors outside of the home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality. To learn more about Direct Vent Technology, scan the code to the right with your smartphone, or visit heatnglo.com.




6000/8000 MODERN SPECIFICATIONS

MODEL	FRONT WIDTH		BACK WIDTH		HEIGHT		DEPTH		GLASS SIZE	BTU/HOUR INPUT
	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING		
6000CMOD	41 [1041]	42 [1067]	28-1/2 [724]	42 [1067]	39-7/8 [1013]	40-1/8 [1019]	21-1/2 [546]	22 [559]	32 x 21-1/2 [813 x 546]	28,000 (NG) 20,000 (LP)
8000CMOD	48 [1219]	49 [1245]	35-1/2 [901]	49 [1245]	41-7/8 [1064]	42-1/8 [1070]	21-1/2 [546]	22 [559]	39 x 23-5/8 [991 x 600]	32,000 (NG) 22,000 (LP)


LEFT SIDE VIEW




TOP VIEW



RIGHT SIDE VIEW



FRONT VIEW



MODEL	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
6000CMOD	41 [1041]	36-1/8 [918]	33-1/2 [851]	34-5/8 [879]	2-1/4 [57]	9-11/16 [246]	26-7/8 [683]	6 [152]	39-7/8 [1013]	21 [533]	11-11/16 [297]	28-1/2 [724]	14-1/4 [362]	8-1/2 [216]	2-7/8 [73]	8-1/2 [216]	1 [25]	40-7/8 [1038]
8000CMOD	48 [1219]	43-1/8 [1096]	35-1/2 [902]	36-5/8 [930]	2-3/8 [60]	9-15/16 [252]	28-7/8 [734]	6 [152]	41-7/8 [1064]	21 [533]	11-11/16 [297]	35-1/2 [901]	17-3/4 [451]	8-1/2 [216]	2-7/8 [73]	8-1/2 [216]	1 [25]	42-7/8 [1089]

Dimensions above are in inches. Reference dimensions only. We recommend measuring individual units at installation. NOTE: Combustible material should not be installed over the face. Make sure you do NOT cover the decorative door opening.

Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Pictures in this brochure are not a true representation of the fireplace and/or flames.

U.S. EFFICIENCIES

Steady State - Since most homeowners use their fireplaces for an extended time while they are in the room, Steady State measures how efficiently your fireplace converts fuel to heat once it is warmed up and running in a “steady state”.

AFUE - AFUE rating is more typically used with appliances, like your furnace, that continually cycle on and off to maintain a constant temperature.

RATING	6000M	8000M
STEADY STATE	78.5% (NG)	77.5% (NG)
AFUE	61.1% (NG)	55.9% (NG)

CANADA EFFICIENCIES

EnerGuide (CSA P.4.1-02) - EnerGuide is a rating used in Canada to measure annual fireplace efficiency.

RATING	6000M	8000M
ENERGUIDE (CSA P.4.1-02)	63.0% (NG)	61.7% (NG)

For complete information on this model, please contact us at:

HEAT & GLO

No one builds a better fire

A brand of Hearth & Home Technologies®

7571 215th Street West, Lakeville, MN 55044

Web: heatnglo.com

Phone: (888) 427-3973 (952) 985-6000

E-mail: info@heatnglo.com

[facebook.com/HeatandGlo](https://www.facebook.com/HeatandGlo)

twitter.com/HeatandGlo


[youtube.com/HeatandGlo](https://www.youtube.com/HeatandGlo)

LIMITED LIFETIME WARRANTY*

The strongest in the industry, Heat & Glo® provides a limited lifetime warranty on the most important aspects: firebox and heat exchanger.

Fireplace glass and other surfaces get extremely HOT and can cause severe burns if touched. Do not remove the protective safety screen from the front of the glass. Keep a safe distance away. To learn more visit www.heatnglo.com/fireplacesafety.

* For more details visit heatnglo.com



HNG-1115U-1013