



Outside Temp: 23° HEATঔGLO No one builds a bottler fire



Available IntelliFire® app and voice control

SLIMLINE

SlimLine fireplaces fit where others don't. Slender profiles make unique installations a reality. Bring your vision to life with multiple models, sizes and finishing options. The ideal combination of flame, glow and logs create a fireside experience you never want to leave.

Upgrade the ambiance with the X collection. These enhanced fireplaces offer more heat, detailed high-definition logs, eye-catching LED embers, touchscreen remote control and more.



RIGHT SIZE FOR ANY SPACE a constraint.

CREATIVE VERSATILITY



and 42-inch wide sizes. Let creative installations inspire you. At just 16 inches deep, space is no longer



FEEL THE REALISM

Find the right fire to fill your space. Select from 28, 32, 36 Flame, glow and logs come together for an immersive experience. Take it to the next level with the additional heat and options of the X collection, and lose yourself in the looks and warmth of your SlimLine.




FIT YOUR STYLE

Personalize the aesthetics of the fireplace. Style the front with decorative trims and finishes, choose interior elements, and enrich the appearance with advanced selections. Opt for modern drama, authentic masonry, or somewhere in-between.



Consider heat output, room dimensions and venting in your space. And then select a 28, 32, 36 or 42-inch wide model.



SL MODELS: The ideal combination of flame, glow and logs.

X COLLECTION MODELS: More heat, detailed high-definition logs, eye-catching LED embers and more.

| SL-3X | SL-5 | SL-5X | SL-7 | SL-7X | SL-9 | SL-9X |
|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| 28" | 32" | 32" | 36" | 36" | 42" | 42" |
| Small | Small to medium | Small to medium | Medium to large | Medium to large | Medium to large | Medium to large |
| 11,500-21,000 | 14,900-21,000 | 14,500-27,500 | 17,500-25,000 | 17,500-30,500 | 23,500-30,000 | 18,000-35,000 |
| Standard (four-piece) | Optional (three-piece) | Standard (four-piece) | Optional (three-piece) | Standard (four-piece) | Optional (three-piece) | Standard (four-piece) |
| Standard | Not Available | Standard | Not Available | Standard | Not Available | Standard |
| Standard | Optional | Standard | Optional | Standard | Optional | Standard |
| Standard | Optional | Standard | Optional | Standard | Optional | Standard |
| Standard | Optional | Standard | Optional | Standard | Optional | Standard |
| Optional IntelliFire Wi-Fi module |
| Optional |
| 5 high-definition logs | 5 standard- definition logs | 5 high-definition logs | 5 standard- definition logs | 5 high-definition logs | 5 standard- definition logs | 5 high-definition logs |
| LED illuminated embers | Glowing embers | LED illuminated embers | Glowing embers | LED illuminated embers | Glowing embers | LED illuminated embers |
| Ceramic | Tempered | Ceramic | Tempered | Ceramic | Tempered | Ceramic |
| IntelliFire Touch® | IntelliFire Touch |
| 50% | 50% | 50% | 50% | 50% | 50% | 50% |









FRONT OPTIONS



CHATEAU FORGE Available for SL-5/5X, SL-7/7X and SL-9/9X models in handcrafted, hammered steel.



ARCADIA Available for SL-5/5X, SL-7/7X and SL-9/9X models in black, new bronze or gun metal.



CLEAN FACE Available for SL-5/5X, SL-7/7X and SL-9/9X models in black, new bronze or gun metal.



HALSTON Available for all models in black, new bronze or gun metal.



FIRESCREEN Available for all models in black.



INTERIOR PANEL OPTIONS

Change the look of the fireplace with interior panel options. Choices range from brick panels that give the appearance of an authentic masonry fireplace, to reflective fade-resistant black glass for modern drama.



STRATFORD BRICK PANELS Included standard on X collection models. Optional upgrade for SL models.



TRANQUIL GREIGE INTERIOR BRICK PANELS



FADE-RESISTANT BLACK GLASS PANELS Included standard on X collection models. Optional upgrade for SL models.

CONTROLS

INTELLIFIRE APP

All the features of a remote control with an app installed on your smart device. Monitor your fire from anywhere or even control it with the sound of your voice. IntelliFire is compatible with voice assistants Amazon Alexa and Google Assistant.









TOUCHSCREEN REMOTE

Features: on/off, flame height adjustment, fan speed, lights adjustment, thermostat mode, room temperature readout, child lock, timer mode, battery backup, cold climate mode, power vent, wall docking station (fan, lights and power vent are dependent on your fireplace).



Features: on/off, battery strength indicator, cold climate mode

SLIMLINE TECHNOLOGIES

INTELLIFIRE TOUCH® IGNITION SYSTEM

IntelliFire Touch is our most advanced intermittent-pilot ignition (IPI) system, making operating your appliance simple, smart and safe. Select the IntelliFire app, touch-screen remote control or wireless wall switch for the solution that fits your lifestyle.



LED EMBER BED

Add an extra layer of dimension and light to your fire. Realistic illuminated LED embers let you enjoy the ambiance, with or without the fire.

DIRECT VENT TECHNOLOGY

With direct vent fireplaces and inserts, 100% of combustion exhaust and fumes are removed from your home. These sealed fireplaces provide optimal heat, conserve energy and ensure clean, safe indoor air quality.



FADE-RESISTANT BLACK GLASS PANELS

A clean modern look never gets dull. Just like this black glass interior. It's hot. And looks that way, too. For the life of your fireplace.

POWER VENTING TECHNOLOGY

Fireplaces aren't just for exterior walls. A fan-powered accessory with slim venting can zigzag throughout your home—up, down, over or under making it possible to install a gas fireplace virtually anywhere. This ensures safe fireplace operation and the best flames. Check with your local hearth professional to determine if your home or fireplace could benefit from power venting technology.



HEAT MANAGEMENT TECHNOLOGY

Bring the warmth from your fireplace to the rest of your home, up to 20 feet away. Heat management technology can redirect up to 50% of the heat to another area, also reducing wall temperatures above the fireplace. Choose between a Heat-Zone[®] kit to transfer heat where you want it, or redirect up to 40% of the heat outside with a Heat-Out[®] kit.

SLIMLINE SPECIFICATIONS


| MODEL | FRONT | WIDTH | BACK | WIDTH | HEI | GHT | DEF | Ϋ́́ΤΗ | | BTU/HR | |
|---------|-------------|-------------|-----------------|-------------|-----------------|-----------------|-----------------|-----------------|----------------------------|--------------------|--|
| | ACTUAL | FRAMING | ACTUAL | FRAMING | ACTUAL | FRAMING | ACTUAL | FRAMING | GLASS SIZE | INPUT (NG) | |
| SL-3X | 33 [838] | 34 [864] | 22-3/4 [578] | 34 [864] | 32-3/8 [822] | 32-3/4 [832] | 16-1/4 [413] | 16-1/4 [413] | 24-1/8 X 16 [613 x 406] | 11,500-21,000 | |
| SL-5/5X | 36 | 37 | 25-3/4 | 37 | 34-3/8 | 34-3/4 | 16-5/16 | 16-1/4 | 27-3/16 X 18-1/16 | 14,900-21,000 (5) | |
| | [913] | [940] | [653] | [940] | [873] | [882] | [415] | [413] | [691 x 459] | 14,500-27,500 (5X) | |
| SL-7/7X | 41 | 42 | 30-3/4 | 42 | 37-7/8 | 38-1/4 | 16-5/16 | 16-1/4 | 32-1/16 X 21-1/2 | 17,500-25,000 (7) | |
| | [1041] | [1067] | [781] | [1067] | [962] | [972] | [415] | [413] | [814 x 546] | 17,500-30,500 (7X) | |
| SL-9/9X | 48 | 49 | 37-3/4 | 49 | 39-9/16 | 40-1/4 | 16-5/16 | 16-1/4 | 39-1/16 X 23-9/16 | 23,500-30,000 (9) | |
| | [1218] | [1245] | [959] | [1245] | [1005] | [1022] | [415] | [413] | [992 x 599] | 18,000-35,000 (9X) | |


TOP VIEW


LEFT SIDE VIEW


FRONT VIEW

RIGHT SIDE VIEW









| MODEL | A | В | C | D | E | F | G | Н | I | J | К | L | М | N | 0 | Р | Q | R | S | Т | U | V | W | Х | Y |
|---------|--------|--------|---------|---------|---------|--------|-------|--------|--------|----------|-------|---------|---------|------|--------|--------|--------|-------|--------|-------|------|---------|-------|-------|-------|
| SL-3X | 33 | 28-1/8 | 24-1/8 | 16 | 32-1/8 | 3-1/2 | 6-7/8 | 21-3/8 | 32-3/8 | 34-1/2 | 8 | 8-3/4 | 16-1/4 | 1/2 | 22-3/4 | 11-3/8 | 15-7/8 | 6-5/8 | 2-1/8 | 6 | 1 | 28 | 5 | 14 | 9-1/8 |
| | [838] | [714] | [613] | [406] | [816] | [89] | [175] | [543] | [822] | [876] | [203] | [222] | [413] | [13] | [578] | [289] | [403] | [168] | [54] | [152] | [25] | [711] | [127] | [356] | [232] |
| SL-5/5X | 36 | 31-1/8 | 27-3/16 | 18-1/16 | 34-1/16 | 3-9/16 | 6-7/8 | 23-3/8 | 34-3/8 | 36-7/16 | 8 | 8-13/16 | 16-5/16 | 1/2 | 25-3/4 | 12-7/8 | 15-7/8 | 6-5/8 | 2-3/16 | 6 | 1 | 30-1/16 | 5 | 14 | 9-1/8 |
| | [914] | [791] | [691] | [459] | [865] | [90] | [175] | [594] | [873] | [926] | [203] | [224] | [414] | [13] | [654] | [327] | [403] | [168] | [56] | [152] | [25] | [764] | [127] | [356] | [232] |
| SL-7/7X | 41 | 36-1/8 | 32-1/16 | 21-1/2 | 37-5/8 | 3-9/16 | 6-7/8 | 26-7/8 | 37-7/8 | 39-15/16 | 8 | 8-13/16 | 16-5/16 | 1/2 | 30-3/4 | 15-3/8 | 15-7/8 | 6-5/8 | 2-3/16 | 6 | 1 | 33-9/16 | 5 | 14 | 9-1/8 |
| | [1041] | [918] | [814] | [546] | [956] | [90] | [175] | [683] | [962] | [1014] | [203] | [224] | [414] | [13] | [781] | [391] | [403] | [168] | [56] | [152] | [25] | [853] | [127] | [356] | [232] |
| SL-9/9X | 48 | 43 | 39-1/16 | 23-9/16 | 39-9/16 | 3-9/16 | 6-7/8 | 28-7/8 | 39-7/8 | 41-15/16 | 8 | 8-13/16 | 16-5/16 | 1/2 | 37-3/4 | 18-7/8 | 15-7/8 | 6-5/8 | 2-3/16 | 6 | 1 | 35-9/16 | 5 | 14 | 9-1/8 |
| | [1219] | [1092] | [992] | [599] | [1005] | [90] | [175] | [733] | [1013] | [1065] | [203] | [224] | [414] | [13] | [959] | [479] | [403] | [168] | [56] | [152] | [25] | [903] | [127] | [356] | [232] |

Dimensions above are in inches and millimeters. Product installation must adhere strictly to instructions shipped with product. We recommend measuring individual units at installation. Assumes the use of 1/2-inch drywall. NOTE: Combustible material should not cover the face. Make sure you do NOT cover the decorative door opening.

Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Actual product appearance, including flame, may differ from product images.



OUR SUSTAINABILITY STORY

Our history of leadership in the hearth industry compels us to now lead the way in developing manufacturing practices that ensure our planet remains as durable, beautiful and long-lasting as our products. Find out how we are leading the industry in sustainable practices by scanning the code.

For complete information on this model, please contact us at:

| SL-3X | SL-5 | SL-5X | SL-7 | SL-7X | SL-9 | SL-9X |
|-------|-------|-------|-------|-------|-------|-------|
| 69.1% | 57.9% | 64.0% | 59.0% | 66.4% | 62.1% | 69.0% |



No one builds a better fire

Web: heatnglo.com Phone: (888) 427-3973 (952) 985-6000 Email: info@heatnglo.com

facebook.com/HeatandGlo

x.com/HeatandGlo

▶ youtube.com/HeatandGlo



LEARN MORE



1 on CSA R4 1.11

EFFICIENCIES

EnerGuide (CSA P.4.1-15) EnerGuide is a rating used in Canada to measure annual fireplace efficiency.

LIMITED LIFETIME WARRANTY*

The strongest in the industry, Heat & Glo[®] provides a limited lifetime warranty on the most important aspects: firebox and heat exchanger.

Fireplace glass and other surfaces get extremely HOT and can cause severe burns

*For full warranty details, go to www.heatnglo.com.



HNG-1148U-0324