

VELLIS Gas Fireplace Guide



MAJESTIC

NEW! VELLIS



Vellis 60" with Architectural interior panels and Driftwood logs

Features

- Tall 18" viewing height for generous view of flickering flames
- 48", 60" and 72" wide in single-sided or double-sided models
- Safely install combustible materials up to the fireplace opening
- Multi-colored LED ember lighting highlights crushed glass
- Five interior panel styles and three log set options for a custom look
- SafeSurface glass keeps hands safe without a safety screen
- Easy control with touchscreen remote (included), or optional wireless wall switch, app or voice control
- Cool-wall technology enables installation of TV or artwork just inches above the fireplace
- Optional automatic heat distribution in your space for warmth when it's wanted
- Optional indoor/outdoor kit for double-sided installation



Product Details


Make It Your Own

Interior Panels


Interior panels add depth, dimension and personality to your fireplace. This backdrop enhances the flame and transforms the entire look of your fireplace.



Stone Column



Architectural Panels



Fluted Black Glass



Marble Black Glass



Reflective Black Glass

Logs, Stones and Crystals

Reflect your design style with a wide variety of accessories that bring the whole look of the fire together.



Birch



Driftwood



Oak



Crystal Glass



Copper Glass



Smoked Glass



Graphite Glass



River Rock Stones

Ember Bed

Seven colors to fit any mood.



Controls

Whether it's the IntelliFire® app that lets you start the fire from your phone (even when you're not home), a sleek touchscreen remote that gives you easy access to flame height and fan speed, or a simple wall switch for quick on-off convenience, there's an option that fits your life.


INTELLIFIRE APP



WIRELESS WALL SWITCH



TOUCHSCREEN REMOTE (Included)



Technologies

POWERFLOW II TECHNOLOGY

Our exclusive PowerFlow II technology redirects the flow of heat to the outside of the home to keep outer glass temperatures safe and maintain a cool wall, enabling you to add a TV or heat-sensitive materials just inches above your fireplace.

Although the Vellis is specifically designed for no heat, an optional heat management system (LPR-HEAT-DUCT) may be utilized to capture a low amount of heat. This heat can be transferred into the same room or directed to another area of the home up to 25 feet away.

SAFESURFACE GLASS

SafeSurface glass keeps hands safe without the need for a safety screen thanks to double-pane glass and internal cooling technology.

DIRECT VENT TECHNOLOGY

Direct vent fireplaces are sealed systems that pull fresh air from outside and send 100% of combustion exhaust back outdoors. That means no fumes enter your home. The result is efficient heating, better energy use and cleaner indoor air quality.

MULTI-COLORED LED LIGHTING TECHNOLOGY

Superior performance and extended efficiency. This technology supplies high-contrast, brilliant lighting to accentuate the flames and can be used as mood lighting with or without the fire. You can easily control the lighting with the included touchscreen remote (RC450).

INTELLIFIRE TOUCH® TECHNOLOGY

IntelliFire Touch is an advanced intermittent pilot ignition (IPI) system that makes starting and controlling your fireplace simple, safe and reliable. Applies to all control types (app, wall switch and touchscreen remote).

Measurements

MODEL	WIDTH		HEIGHT		DEPTH		VIEWING SIZE	BTU/HOUR INPUT
	ACTUAL	FRAMING	ACTUAL	FRAMING	ACTUAL	FRAMING		
VELLIS-II-48, VELLIS-II-48ST	64-3/8" [1635]	66-3/4" [1695]	40-13/16" [1037]	45" [1143]	18-1/4" [464]	18" [457] ST: 17" [432]	48" x 18" [1219 X 457]	31,500 - 45,000 BTUs (NG) 31,000 - 42,000 BTUs (LP)
VELLIS-II-60, VELLIS-II-60ST	76-3/8" [1940]	78-3/4" [2000]	40-13/16" [1037]	45" [1143]	18-1/4" [464]	18" [457] ST: 17" [432]	60" x 18" [1524 X 457]	39,500 - 57,000 BTUs (NG) 36,500 - 50,000 BTUs (LP)
VELLIS-II-72, VELLIS-II-72ST	88-3/8" [2245]	90-3/4" [2305]	40-13/16" [1037]	45" [1143]	18-1/4" [464]	18" [457] ST: 17" [432]	72" x 18" [1829 x 457]	42,000 - 58,500 BTUs (NG) 40,500 - 55,000 BTUs (LP)



Architect Guide

Dimensions are in inches and millimeters. Product information is not complete and is subject to change without notice. Product installation must adhere strictly to instructions shipped with product. We recommend measuring individual units at installation. Assumes the use of 1/2" sheetrock. NOTE: Combustible material should not cover the face. Refer to installation manual for detailed specifications on installing this product. Majestic® reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Actual product appearance, including flame, may differ from product images.