




Efficient, Eco-Friendly Heating

Powerful heat production, automatic ignition and temperature control, and a small footprint make the PB105 an ideal choice for central heating. A 3-pass heat exchanger design increases efficiency and an extra large hopper provides extended performance with minimal maintenance. Eco-friendly fuel options help Mother Nature and save you money, too.

For even heating, easy maintenance and uncompromising quality, turn to the PB105.



This cut away shows air flow and the Patented Pellet Pro Feeder System at work in the PB105.

Features

- Triple-pass heat exchanger
- 205 lb. hopper capacity
- Greater than 85% efficiency
- PelletPro[™] Feed System

Included Accessories

- Combination water temperature Outside air and pressure gauge
- Pressure relief valve

Options

- Outside air kit
- Domestic hot water coil
- BioFuel Bulk Hopper
- Atmospheric Conversion Kit 165 kit (Required in

temperature sensor

some states)

PelletPro System


Scan with your smartphone to learn more about the PelletPro System, or visit HarmanStoves.com.



PB105 pellet boiler	BTU/hr Input	Heating Capacity ¹	Hopper Capacity	Fuel Type	Flue Size	Outside Air Size	Fuse Rating
	113,900	2,500 - 6,500 sq. ft.	205 lbs.	Biomass Wood Pellets	4" pellet vent	2-3/4"	6 amp

Front (Door Side) View

Right Side View





Clearances to Combustibles

Front (Fire door & ash pan door)	36"		
Left (Hopper end)	18"		
Right (Blower end)	20"		
Rear (Opposite doors)	6" (16.5" recommended for access)		

YOUR HARMAN DEALER IS:



A brand of Hearth & Home Technologies Inc.

352 MOUNTAIN HOUSE ROAD HALIFAX, PA 17032 WWW.HARMANSTOVES.COM

F facebook.com/HarmanStoves

twitter.com/HarmanStoves

youtube.com/HarmanStoves

LIMITED LIFETIME WARRANTY²

The strongest in the industry, Harman provides a limited lifetime warranty on most important aspects: firebox and heat exchanger.

 $^{\rm I}$ See your local authorized Harman dealer for help in determining the product that best suits your heating needs based on climate and home efficiency. ² For full warranty details, visit www.harma

Actual product appearance, including flame, may differ from image, specifications and pricing subject to change without notice. Safety tu Testing Laboratory ASTN-E1509 • ULC-(1492-H1990. The image, an in this brochuse are provided to assits you in product isalection on installation manual for complete dearance requirements and specific store and insert proface get extremely HOT and can cause severe Keep a safe distance away. To learn more visit www.harmanstores.co

Temp sensor cable Direct vent 120 VAC

ESP Technology with Aqua