

Paint Application Instructions

⚠ WARNING

Review all safety information on individual paint containers.

⚠ WARNING



Explosion Risk
Turn OFF gas to appliance.

1. Remove decorative front (if present).
2. Remove glass assembly.
3. Remove logs from unit.
4. Remove grate from unit.
5. Remove pilot bracket from burner.
6. Remove burner from unit.
7. Shake mineral wool from top of burner and discard.
8. Remove Mystic Embers from bottom of the firebox and discard.
9. Mask off (4) edges of the firebox with masking tape provided.
10. Spray bark brown paint on brick faces, sides, back and top (see Figure 1).
11. Spray black paint on the bottom of firebox (see Figure 2).
12. Spray black paint around the flue pipe opening at the top of the firebox (see Figure 3).



Figure 1



Figure 2



Figure 3

13. Spray black paint around the outside 2 inch edge of the firebox (see Figure 4).



14. With paint roller apply rust to the brick face sides, back and top. (See Figure 5).



15. Lightly spray, or fog top of firebox with the black paint (see Figure 6).



16. Lightly spray, or fog the front edges of the unit on the left and right sides (see Figure 7).



17. Remove all the masking tape.
18. Replace the burner in the unit.
19. Replace mineral wool (057-721) on the burner following instructions in the Owner's Manual. **DO NOT COVER PORT HOLES.**
20. Replace log grate in the unit.
21. Replace logs in the unit. Follow the log placement instructions in the Owner's Manual.
22. Place provided Mystic Embers in unit, following instructions in the Owner's Manual (see Figure 8).

