


Log Placement Instructions

Models: PH24-R, PH30-R

AWARNING!

The positioning of the logs is critical to the safe, clean operation of this gas log set. Sooting and other problems may result if the logs are not properly positioned per these instructions. Failure to position in accordance with the diagrams below, or failure to use only parts specifically approved for this log set may result in property damage or personal injury.



Ref.	Description	Qty.	PH24-R	PH30-R
1.	Rear Log #1	1	20303855	65D2015
2.	Left Middle Log #2	1	20303856	65D2017
3.	Right Middle Log #3	1	20303857	65D2018
4.	Front Log #4	1	20303858	65D2016
5.	Left Top Log #5	1	20303859	65D2013
6.	Right Top Log #6	1	20303860	65D2014

PLACE PH24-R LOGS, PH30-R LOGS

- 1. Place Rear Log (#1) on rear support. See Figure 1.
- 2. Place Left Middle Log (#2) on middle support and burner. See Figure 2.
- 3. Place Right Middle Log (#3) on middle support. See Figure 2.

NOTE: Logs #1, #2 and #3 have ridges on the bottom which secure the logs to burner frame. After installing each log, check to be sure it is stable.



Figure 1



Figure 2

CAUTION

DO NOT sprinkle volcanic rock on the logs or around the pilot or the main burner. This may cause sooting. Only place volcanic rock on the floor of the fireplace.

During initial operation of the new heater, burning logs will give off a paper burning smell and orange flames will be present. Simply open the windows for a few hours to vent the odor.

 Place Front Log (#4) in between burner and grate so that notched areas fit between grate supports. See Figure 3.




Figure 3

- 5. Rest Left Top Log (#5) on front and rear log cutouts. See Figure 4.
- 6. Rest Right Top Log (#6) on front and rear log cutouts. See Figure 4.



Figure 4



LOVE AT FIRST LIGHT

Monessen, a brand of Hearth & Home Technologies 7571 215th Street West, Lakeville, MN 50044 www.monessenhearth.com